

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Yardworks](#) /

› [Yardworks 50 Ft Rubber Garden Hose Soaker Instruction Manual](#)

## Yardworks 1351

# Yardworks 50 Ft Rubber Garden Hose Soaker Instruction Manual

Model: 1351

## PRODUCT OVERVIEW

---

The Yardworks 50 Ft Rubber Garden Hose Soaker is designed to provide efficient and even watering for your garden, whether placed above or below ground. This hose is an excellent solution for conserving water, utilizing up to 70% less water compared to traditional watering methods by preventing evaporation and runoff.



Image: The Yardworks 50 Ft Rubber Garden Hose Soaker, coiled, showcasing its length, diameter, and key features such as water savings, even soaking, removable coupler cap, and recycled rubber composition.

## Key Features:

- Provides even soaking both above and below the ground.
- Equipped with plastic couplings on both ends, allowing easy connection to additional soaker hoses for extended length.
- Manufactured using 65% recycled rubber, contributing to environmental sustainability.
- Dimensions: 5/8 Inch diameter x 50 Ft length.
- Designed to save up to 70% water by minimizing evaporation and runoff.

## SETUP INSTRUCTIONS

1. **Uncoil the Hose:** Carefully uncoil the soaker hose from its packaging.
2. **Connect to Water Source:** Attach one end of the soaker hose to your garden spigot or main garden hose. Ensure the connection is secure to prevent leaks.
3. **Position the Hose:** Lay the soaker hose along the base of plants, in garden beds, or wherever targeted watering is desired. For optimal water distribution, ensure the hose is laid as evenly as possible.

4. **Extend Length (Optional):** If more length is needed, remove the coupler cap from the end of the soaker hose and connect another soaker hose using its plastic coupling. Securely tighten the connection.
5. **Burying (Optional):** For discreet watering and to further reduce evaporation, the soaker hose can be buried just below the soil surface. Ensure the hose is not kinked or pinched when burying.

## OPERATING INSTRUCTIONS

The Yardworks Soaker Hose delivers water slowly and directly to the root zone of plants, promoting deep root growth and minimizing water waste.

- **Water Pressure:** The hose is designed to operate effectively at typical residential water pressures. Avoid excessively high pressure, which can cause uneven soaking or damage to the hose. The maximum working pressure is 180 PSI.
- **Watering Duration:** The ideal watering duration depends on soil type, plant needs, and climate. Start with shorter durations (e.g., 30 minutes to 1 hour) and adjust as needed. Observe the soil moisture to determine if plants are receiving adequate water.
- **Water Conservation:** By delivering water directly to the roots, this soaker hose significantly reduces water loss due to evaporation and runoff, making it an environmentally friendly watering solution.

## MAINTENANCE

- **Cleaning:** Periodically check the hose for any blockages or debris in the pores. If necessary, gently clean the exterior with water and a soft brush.
- **Storage:** Before freezing temperatures, drain all water from the hose. Store the hose in a cool, dry place away from direct sunlight to prolong its lifespan. Coiling the hose neatly can prevent kinks and damage.
- **Inspection:** Regularly inspect the hose for any signs of wear, cracks, or damage. Address any issues promptly to maintain optimal performance.

## TROUBLESHOOTING

| Problem                   | Possible Cause                                    | Solution  |
|---------------------------|---|---|
| Uneven Water Distribution | Low water pressure; Kinks in hose; Clogged pores. | Increase water pressure slightly (do not exceed 180 PSI); Straighten any kinks; Clean hose pores. |
| No Water Flow             | Water source off; Hose kinked; Connection loose.  | Ensure water source is on; Check for and remove kinks; Tighten all connections.                   |
| Leaks at Connections      | Loose connection; Damaged washer.                 | Tighten connections; Replace washer if damaged.   |

## SPECIFICATIONS

| Attribute    | Detail    |
|--------------|-----------|
| Brand        | Yardworks |
| Model Number | 1351      |

| Attribute                | Detail                                  |
|--------------------------|---|
| Material                 | Plastic, Rubber (65% Recycled Rubber)   |
| Color                    | Black                                   |
| Length                   | 50 Feet (600 inches)                    |
| Diameter                 | 5/8 Inch (0.63 inches Outside Diameter) |
| Item Weight              | 4.63 pounds                             |
| Maximum Working Pressure | 180 PSI                                 |
| Nominal Wall Thickness   | 0.3125 inches                           |

## WARRANTY INFORMATION

---

This Yardworks Soaker Hose comes with a **3-Year Limited Guarantee**. Please retain your proof of purchase for warranty claims. For specific terms and conditions of the guarantee, refer to the product packaging or contact customer support.

## CUSTOMER SUPPORT

---

For further assistance, questions, or to report any issues with your Yardworks Soaker Hose, please contact our customer support team:

- **Website:** Visit the official Yardworks website for FAQs and contact options.
- **Phone:** Refer to the product packaging for customer service phone numbers.
- **Email:** Check the official website for email support.

Please have your product model number (1351) and purchase details ready when contacting support.