

VSYSTO Universal Anti-Theft Handlebar Mount for VSYSTO Drive Recorders

VSYSTO Motorcycle Drive Recorder Anti-Theft Handlebar Mount User Manual

Model: Universal Anti-Theft Handlebar Mount for VSYSTO Drive Recorders

1. INTRODUCTION

Thank you for purchasing the VSYSTO Motorcycle Drive Recorder Anti-Theft Handlebar Mount. This all-metal bracket is designed to securely hold your drive recorder on motorcycle handlebars, offering robust protection and flexible positioning. It features a durable construction and an anti-theft design to safeguard your device. This mount is compatible with various VSYSTO drive recorder models and standard GoPro-style camera adapters.

2. PACKAGE CONTENTS

- VSYSTO Anti-Theft Handlebar Mount (1 unit)
- Dedicated Hex Wrench (1 unit)
- Mounting Hardware (screws, nuts)

3. COMPATIBILITY

This mount is specifically designed for the following VSYSTO drive recorder models:

- VSYSTO A6F
- VSYSTO A2F
- VSYSTO A2X
- VSYSTO B2U
- VSYSTO P4.5

It also supports various commercially available camera adapters and brackets that utilize the GoPro standard mounting interface.

4. SAFETY INFORMATION

- Ensure all screws are tightened securely before riding to prevent the device from falling off.
- Do not obstruct your view or interfere with the operation of your motorcycle controls when installing the mount.
- Regularly check the mount for any signs of wear or loosening, especially after long rides or exposure to vibrations.
- Installation should be performed by an adult or under adult supervision.

5. SETUP AND INSTALLATION

Follow these steps to install the VSYSTO handlebar mount and attach your drive recorder:

5.1. Attaching the Mount to the Handlebar

1. Identify a suitable position on your motorcycle's handlebar that does not obstruct your view or interfere with controls.
2. Loosen the screws on the handlebar clamp section of the mount using the dedicated hex wrench.
3. Place the clamp around the handlebar and align it to your desired position.
4. Tighten the screws firmly with the hex wrench until the mount is securely fixed to the handlebar. Do not overtighten.

360度回転

盗難防止ブラケット

角度調整 振れ止め 固定用

.....



Image: The VSYSTO handlebar mount shown with its hex wrench and examples of installation on motorcycle handlebars, demonstrating its secure fit and adjustability.

5.2. Attaching Your Drive Recorder

1. The mount features a universal interface compatible with GoPro standard brackets. Attach your drive recorder's adapter or bracket to the mount's top plate.
2. Secure the drive recorder to the mount using the appropriate screws or locking mechanisms provided with your recorder or adapter.
3. Ensure the connection is firm and the drive recorder is stable.



Image: The VSYSTO mount displaying its compatibility with various VSYSTO drive recorder models (A2F, A2X, P4.5, P6F, A6X) and its adjustable design.

6. OPERATION AND ADJUSTMENT

The VSYSTO mount offers extensive adjustability for optimal viewing angles:

- **360° Rotation:** The entire mount can be rotated 360 degrees around the handlebar axis, allowing for flexible positioning.
- **270° Tilt Adjustment:** The tripod head section, which secures the main unit (drive recorder), can be adjusted up to 270 degrees vertically. This allows you to fine-tune the camera's tilt angle.

To adjust the angle, slightly loosen the relevant adjustment screws, position the device as desired, and then re-tighten the screws firmly using the hex wrench.

7. MAINTENANCE

- **Cleaning:** Wipe the mount with a soft, damp cloth to remove dust and dirt. Avoid using harsh chemicals or abrasive cleaners.
- **Inspection:** Periodically inspect all screws and joints for tightness. Re-tighten any loose components using the dedicated hex wrench.
- **Storage:** If removing the mount for extended periods, store it in a dry, cool place away from direct sunlight.

8. TROUBLESHOOTING

- **Mount feels loose on handlebar:** Ensure the handlebar clamp screws are fully tightened with the hex wrench. If the handlebar diameter is too small, consider using rubber shims (not included) for a tighter fit.
- **Device wobbles or shakes:** Check that the connection between the drive recorder and the mount's top

plate is secure. Ensure all adjustment screws on the mount are tightened.

- **Difficulty adjusting angle:** Loosen the adjustment screws slightly more before attempting to reposition. Ensure no debris is obstructing the moving parts.

9. SPECIFICATIONS

Feature	Detail
Brand	VSYSTO
Manufacturer	V-SYS Technology
Material	All-metal construction
Mounting Type	Handlebar Clamp
Compatible Device Interface	GoPro Standard
Handlebar Rotation	360° Adjustable
Device Tilt Adjustment	270° Adjustable
Water Resistance	Water resistant
Compatible Vehicle Type	Motorcycle
UPC	680904799929
ASIN	B07WBXV3X4



Image: Detailed dimensions of the VSYSTO handlebar mount, including height, width, and clamp diameter, for reference during installation.

10. WARRANTY AND SUPPORT

The VSYSTO Motorcycle Drive Recorder Anti-Theft Handlebar Mount (under the Motocam product line) comes with a **six-month warranty period** from the date of purchase. This warranty covers manufacturing defects and material flaws under normal use.

For warranty claims, technical support, or any inquiries regarding your product, please contact VSYSTO customer service through the retailer where you purchased the product or visit the official VSYSTO website for contact information.

Please retain your proof of purchase for warranty validation.

