

[manuals.plus](#) /› [10L0L](#) /› [10L0L Golf Cart Battery Lifting Strap Instruction Manual \(Model 001\)](#)**10L0L 001**

## 10L0L Golf Cart Battery Lifting Strap Instruction Manual

Model: 001 | Brand: 10L0L

### 1. PRODUCT OVERVIEW

The 10L0L Golf Cart Battery Lifting Strap (Model 001) is designed to facilitate the safe and easy removal and installation of deep cell batteries in golf carts. This universal carrier strap is compatible with Trojan, Yamaha, Club Car, and EZGO golf cart batteries. It features a hook-style lift mechanism with a rubber handle for improved grip and reduced strain during use.



**THE PREFERRED BRAND  
FOR HIGH-END CUSTOMERS**



Image 1: The 10L0L Golf Cart Battery Lifting Strap securely attached to a deep cell battery, demonstrating its primary function of lifting.

## 2. FEATURES

- **Universal Compatibility:** Works with most deep cell batteries, including those found in Trojan, Yamaha, Club Car, and EZGO golf carts.
- **Ergonomic Design:** Features a rubber handle with an anti-slip design for a comfortable and secure grip, minimizing hand fatigue.
- **Durable Construction:** Manufactured with high-quality steel hooks and advanced rivet technology for enhanced longevity and reliability.
- **Reduced Strain:** Engineered to minimize back strain and physical effort when handling heavy batteries.
- **Enhanced Safety:** Provides superior control over heavy batteries during removal and installation, reducing the risk of injury and contact with battery acid.



Image 2: A close-up of the lifting strap highlighting its key features: robust steel hooks, advanced rivet technology, and the anti-slip rubber handle for secure handling.

### 3. SETUP

- Safety First:** Always ensure the golf cart is turned off and the battery is disconnected from the electrical system before handling. Wear appropriate personal protective equipment, including gloves and eye protection.
- Position the Strap:** Place the 10L0L Battery Lifting Strap directly over the battery you intend to lift.
- Attach the Hooks:** Carefully engage each steel hook of the strap onto the designated lifting points or terminals of the battery. Ensure both hooks are fully seated and secure.
- Verify Security:** Gently tug on the strap to confirm that it is firmly attached to the battery and will not slip during lifting.

Your browser does not support the video tag.

Video 1: Demonstration of how to properly attach the 10L0L Golf Cart Battery Lifting Strap to a battery for secure lifting.

## 4. OPERATING INSTRUCTIONS

- 1. Grip the Handle:** Grasp the rubber handle of the lifting strap firmly with both hands.
- 2. Lift with Proper Technique:** Maintain a straight back and bend your knees. Lift the battery slowly and steadily using your leg muscles, not your back.
- 3. Guide the Battery:** Carefully guide the battery out of its compartment, ensuring it does not snag on any cables or components.
- 4. Lowering the Battery:** When placing the battery, lower it gently and precisely into its new position. Ensure the battery is stable and properly seated before releasing the lifting strap.
- 5. Multiple Straps (Optional):** For extremely heavy or awkward batteries, consider using two lifting straps for better balance and distribution of weight.



Image 3: Illustrates the ease of lifting a heavy battery with the strap, emphasizing reduced back strain.

Your browser does not support the video tag.

Video 2: A practical demonstration of using the 10L0L Battery Lifting Strap to move a battery, showcasing its effectiveness.

## 5. MAINTENANCE

- **Regular Inspection:** Before each use, inspect the entire strap for any signs of wear, cuts, cracks, or damage to the rubber handle, strap material, or steel hooks.
- **Cleaning:** If the strap becomes dirty, clean it with a damp cloth and a mild, non-corrosive soap. Rinse thoroughly and ensure it is completely dry before storing.
- **Storage:** Store the lifting strap in a cool, dry place away from direct sunlight, extreme temperatures, and corrosive chemicals (such as battery acid) to prolong its lifespan.
- **Avoid Overloading:** Do not use the strap to lift batteries heavier than its intended capacity.

## 6. TROUBLESHOOTING

- **Strap Not Attaching Securely:** Ensure the battery terminals or lifting points are clean and free of debris. Verify that the hooks are correctly aligned and fully engaged.
- **Battery Slipping During Lift:** Double-check that both hooks are securely fastened and the strap is centered on the battery. Ensure the lifting motion is smooth and controlled.
- **Difficulty Lifting:** If the battery feels too heavy or awkward, consider using a second lifting strap or seeking assistance. Always prioritize safety and proper lifting techniques.
- **Damaged Strap:** If any part of the strap (handle, material, or hooks) is damaged, discontinue use immediately and replace the product to prevent accidents.

## 7. SPECIFICATIONS

<b>Model</b>	001
<b>Brand</b>	10L0L
<b>Material</b>	Rubber, Stainless Steel
<b>Number of Pieces</b>	2
<b>Approximate Length</b>	14 inches (35.5 cm)
<b>Approximate Width</b>	1 inch (2.5 cm)
<b>Item Weight</b>	8.6 ounces (244 grams)

## PRODUCT SIZE

Universal Deep Cell Battery Carrier Strap for Yamaha, Club Car and EZGO Golf Carts



**EZGO** 



**Yamaha** 



**Club Car** 

Image 4: Visual representation of the lifting strap's dimensions, indicating a length of 14 inches and a width of 1 inch.

### 8. WARRANTY AND SUPPORT

For detailed warranty information regarding your 10L0L Golf Cart Battery Lifting Strap, please refer to the official 10L0L website or the documentation included with your purchase. For product support, technical assistance, or any inquiries, please contact 10L0L customer service. It is recommended to retain your purchase receipt for any warranty claims.