

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Ikea](#) /

› [Ikea KALLROR 503.570.02 Stainless Steel Cabinet Handle Set - Instruction Manual](#)

## Ikea 503.570.02

### Ikea KALLROR 503.570.02 Stainless Steel Cabinet Handle Set - Instruction Manual

#### INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your Ikea KALLROR 503.570.02 Stainless Steel Cabinet Handles. Please read these instructions carefully before proceeding with installation to ensure proper and safe use.

#### PRODUCT OVERVIEW

The Ikea KALLROR 503.570.02 handles are designed to offer a modern aesthetic and functional grip for your kitchen cabinets or drawers. This set includes two handles and all necessary screws for a complete installation.



This image displays two sleek, cylindrical stainless steel cabinet handles, along with four silver screws. The handles have a brushed finish, and each handle is shown with two mounting posts. The screws are designed to secure the handles to cabinet doors or drawers.

## SPECIFICATIONS

<b>Model Number</b>	503.570.02
<b>Brand</b>	Ikea
<b>Quantity per set</b>	2 handles
<b>Handle Length</b>	213 mm
<b>Handle Depth</b>	38 mm
<b>Hole Spacing (center-to-center)</b>	160 mm
<b>Drilled Hole Diameter</b>	5 mm
<b>Suitable Door Thickness</b>	16 mm to 21 mm
<b>Handle/End Cap Material</b>	Stainless Steel
<b>Plastic Parts Material</b>	Polyethylene Plastic
<b>Included Components</b>	Installation Hardware (screws)
<b>Weight</b>	170 Grams

## SETUP AND INSTALLATION

Installing your Ikea KALLROR cabinet handles is a straightforward process. Follow these steps carefully for a secure attachment.

### Required Tools

- Drill
- Drill bit (5 mm diameter)
- Measuring tape or ruler
- Pencil
- Screwdriver (Phillips head recommended)

### Installation Steps

- Measure and Mark:** Carefully measure and mark the desired position for the handle on your cabinet door or drawer front. Ensure the marks for the two screw holes are precisely 160 mm apart (center-to-center).
- Drill Holes:** Using a 5 mm drill bit, carefully drill through the cabinet door or drawer front at the marked positions. Ensure the holes are straight and clean.
- Attach Handle:** Align the handle with the drilled holes. Insert the provided screws from the inside of the cabinet door or drawer through the drilled holes and into the handle posts.
- Secure Handle:** Tighten the screws firmly with a screwdriver until the handle is securely attached. **Do not overtighten**, as this may damage the cabinet material.
- Repeat:** Repeat the process for the second handle if installing a set.

**Important:** These handles are suitable for door thicknesses between 16 mm and 21 mm. Verify your cabinet door thickness before drilling.

## OPERATION

The Ikea KALLROR cabinet handles are designed for simple and reliable operation. Grasp the handle firmly to open or close cabinet doors and drawers as needed.

## MAINTENANCE

To ensure the longevity and appearance of your stainless steel handles, follow these maintenance guidelines:

- **Cleaning:** Wipe regularly with a soft, damp cloth. For stubborn marks, use a mild detergent solution. Avoid abrasive cleaners, scouring pads, or chemical solvents, as these can damage the stainless steel finish.
- **Drying:** Always dry the handles thoroughly after cleaning to prevent water spots and maintain their luster.
- **Inspection:** Periodically check the screws for tightness. If a handle feels loose, gently tighten the screws with a screwdriver.

## TROUBLESHOOTING

### Handle is Loose

If the handle feels loose, gently tighten the screws from the inside of the cabinet door or drawer. Ensure not to overtighten.

### Difficulty Installing

Ensure the drilled holes are precisely 160 mm apart (center-to-center) and that the drill bit used was 5 mm in diameter. Verify your cabinet door thickness is within the specified 16-21 mm range.

## SUPPORT

For further assistance or inquiries regarding your Ikea KALLROR cabinet handles, please refer to the official Ikea website or contact Ikea customer service directly.