



Manuals.plus /

› SEIZMIK /

› SEIZMIK UTV Framed Door Kit Instruction Manual for Can-Am Defender (HD9, HD10, MAX, PRO) Models 2016-2023 (Model 6027)

SEIZMIK 6027

SEIZMIK UTV Framed Door Kit Instruction Manual

For Can-Am Defender (HD9, HD10, MAX, PRO) Models 2016-2023 (Model 6027)

1. IMPORTANT SAFETY INFORMATION

Read all instructions carefully before installation and use. Failure to follow these instructions may result in property damage or personal injury. Always wear appropriate safety gear when operating your UTV. Ensure all components are securely fastened before each use.

- Do not operate the UTV with doors improperly installed or damaged.
- Regularly inspect doors for wear, damage, or loose fasteners.
- Ensure clear visibility through windows at all times. Clean as necessary.
- Be aware of increased vehicle width when doors are installed.

2. PACKAGE CONTENTS

Verify that all components are present before beginning installation.

- Driver Side Framed Door Assembly
- Passenger Side Framed Door Assembly
- EPDM Foam Gasket (Perimeter Seal)
- Mounting Hardware Kit
- Installation Instructions (this document)



Image: The SEIZMIK UTV Framed Door Kit shown installed on a Can-Am Defender UTV in a grassy field. The doors provide a full cab enclosure.

3. SETUP AND INSTALLATION

The SEIZMIK Framed Door Kit is designed for straightforward installation. For 2020 and newer models, minor drilling may be required.

1. **Prepare the UTV:** Ensure the UTV is parked on a level surface with the engine off and parking brake engaged. Clean the door frame area thoroughly.
2. **Attach Door Frames:** The door frames are constructed of 3/4 inch steel tubing. Align the door hinges with the UTV's existing hinge points. The pinned hinges allow for quick removal and installation.
3. **Secure Mounting Hardware:** Use the provided mounting hardware to secure the door frames. For 2020 and newer models, two holes may need to be drilled to accommodate the new bolt pattern. Refer to the specific drilling template if included.
4. **Apply Perimeter Seal:** The automotive-grade EPDM foam gasket should be applied along the contours of the door perimeter. This gasket provides an excellent seal against wind and water and facilitates easier closing. Ensure the surface is clean and dry before application for optimal adhesion.
5. **Adjust Fitment:** After initial installation, check the door alignment and gap. Minor adjustments to the hinges may be necessary to achieve an even gap before the seal fully adheres.



- Durable .75" steel frame and UV resistant PVC coated heavyweight nylon
- Tight all-around seal resists water and wind intrusion into the cab
- Windows unzip and store easily for more ventilation
- Pinned hinges allow the whole door to come off in seconds
- Extra window at bottom provides added visibility



Image: A Can-Am Defender UTV with the SEIZMIK framed door open, illustrating the hinge mechanism and the interior space. This view highlights the ease of access and the door's construction.

4. OPERATING INSTRUCTIONS

The SEIZMIK Framed Door Kit enhances your UTV experience with features designed for convenience and protection.

- **Opening and Closing Doors:** The doors operate like standard vehicle doors. Ensure they latch securely when closed.
- **Window Operation:** The clear UV-resistant PVC windows are dual-zippered. They can be rolled down for ventilation and tucked away into integrated storage spaces within the door panel.
- **Enhanced Visibility:** An additional window panel on the bottom half of the doors provides extra visibility, which is beneficial for maneuvering in tight spaces.
- **Quick Removal:** The pinned hinges allow the entire door to be removed in seconds when not needed, offering flexibility for different weather conditions or tasks.



TAILORED PROTECTION

The SEIZMIK Framed Door Kit features premium materials that prevent wind, water, and dust from getting in the cab, all in one easy-to-install package.

Image: A Can-Am Defender UTV equipped with SEIZMIK framed doors, illustrating key features such as the durable steel frame, UV-resistant PVC windows, and the tight all-around seal.

5. MAINTENANCE

Proper maintenance ensures the longevity and performance of your SEIZMIK Framed Door Kit.

- **Cleaning:** Clean the fabric and PVC windows with mild soap and water. Avoid abrasive cleaners or solvents that could damage the materials.
- **Inspection:** Periodically inspect the steel frames for any signs of corrosion or damage. Check all fasteners for tightness and re-tighten as necessary.
- **Gasket Care:** Ensure the EPDM foam gasket remains clean and free of debris to maintain its sealing effectiveness.
- **Storage:** If removing doors for storage, clean them thoroughly and store in a dry, protected area away from direct sunlight to prevent material degradation.

6. TROUBLESHOOTING

Address common issues that may arise during installation or use.

- **Weather Strip Not Adhering:** Ensure the UTV frame surface is thoroughly cleaned with alcohol and completely dry before applying the EPDM foam gasket. Apply firm, even pressure during installation. If issues persist, contact customer support for replacement adhesive or gasket.
- **Uneven Door Gaps:** Adjustments to the hinge pins or mounting points may be required. For some installations, adding small spacers to the hinge pins can help achieve an even gap.
- **Difficulty Closing Doors:** Check for obstructions. Ensure the EPDM gasket is properly seated and not interfering with the latch mechanism. Lubricate latches if necessary.

7. SPECIFICATIONS

Feature	Detail
Model Number	6027
Compatibility	Can-Am Defender (HD9, HD10, MAX, PRO) 2016-2023
Frame Material	3/4 inch Steel Tubing
Cover Material	Heavy-duty water and UV resistant fabric (PVC coated heavyweight nylon)
Window Material	Clear UV-resistant PVC
Seal Type	Automotive grade EPDM foam gasket
Item Weight	45 pounds
Product Dimensions	51 x 41 x 7.5 inches (Packaging/Shipping)
UPC	814657020126, 685717097712

8. WARRANTY INFORMATION

For specific warranty details regarding your SEIZMIK UTV Framed Door Kit, please refer to the warranty card included with your product or visit the official SEIZMIK website. Warranty terms typically cover manufacturing defects for a specified period from the date of purchase.

9. CUSTOMER SUPPORT

If you have any questions, require assistance with installation, or need to report a missing or damaged part, please contact SEIZMIK customer support. Contact information can typically be found on the product packaging or the official SEIZMIK website.

Online Resources: For additional product information, installation videos (if available), and FAQs, please visit the SEIZMIK Brand Store.