

Ecolab Greaselift RTU (6100284)

Ecolab Greaselift RTU Non-Caustic Degreaser User Manual

Model: Greaselift RTU (6100284)

INTRODUCTION

This manual provides essential information for the safe and effective use of Ecolab Greaselift RTU Non-Caustic Degreaser. Please read all instructions carefully before use to ensure optimal performance and user safety. This product is designed for the removal of baked-on grease.



Image: Ecolab Greaselift RTU Non-Caustic Degreaser in a 32 FL OZ spray bottle. The bottle is white with an orange trigger spray nozzle. A prominent orange label on the front displays "ECOLAB Greaselift™ RTU" and "Non-Caustic Degreaser for Removal of Baked-On Grease Only". The model number "6100284" is also visible.

PRODUCT OVERVIEW

- **Product Name:** Ecolab Greaselift RTU
- **Form:** Liquid, Ready-To-Use (RTU)
- **Volume:** 32 Fluid Ounces per bottle
- **Key Feature:** Non-Caustic formulation

- **Primary Use:** Effective for removing baked-on grease
- **Scent:** Unscented

SAFETY INFORMATION

Always prioritize safety when using cleaning products. Refer to the product's Safety Data Sheet (SDS) for comprehensive safety information. Key precautions include:

- **Ventilation:** Use in a well-ventilated area.
- **Protective Gear:** Wear appropriate personal protective equipment (PPE), such as gloves and eye protection, to prevent skin and eye contact.
- **Storage:** Store in a cool, dry place, away from direct sunlight and out of reach of children and pets. Keep container tightly closed.
- **Disposal:** Dispose of contents and container in accordance with local, regional, national, and international regulations.
- **First Aid:** In case of contact, rinse thoroughly with water. If irritation persists, seek medical attention.

SETUP

Before applying the degreaser, ensure the area to be cleaned is prepared:

1. Ensure the surface is cool to the touch. Do not apply to hot surfaces.
2. Remove any loose debris or food particles from the surface.
3. Ensure adequate ventilation in the work area.
4. Put on appropriate personal protective equipment (gloves, eye protection).

OPERATING INSTRUCTIONS

Follow these steps for effective grease removal:

1. **Spray:** Spray Greaselift RTU directly onto the baked-on grease. Ensure complete coverage of the soiled area.
2. **Dwell Time:** Allow the product to penetrate the grease for 5-15 minutes. For heavily baked-on grease, a longer dwell time may be necessary, but do not allow the product to dry on the surface.
3. **Agitate (Optional):** For stubborn deposits, gently agitate the area with a non-abrasive brush or pad.
4. **Wipe:** Wipe the treated surface clean with a damp cloth or sponge.
5. **Rinse:** Rinse the surface thoroughly with clean water to remove any residue.
6. **Dry:** Allow the surface to air dry or wipe dry with a clean cloth.

MAINTENANCE AND STORAGE

Proper maintenance and storage ensure the longevity and effectiveness of the product:

- **Bottle Care:** Keep the spray nozzle clean and free of blockages. If the nozzle becomes clogged, rinse it with warm water.
- **Storage Conditions:** Store the product in its original container, tightly closed, in a cool, dry, well-ventilated area.
- **Temperature:** Avoid extreme temperatures. Do not freeze.
- **Shelf Life:** Refer to the product packaging for specific shelf life information.

TROUBLESHOOTING

If you encounter issues while using Ecolab Greaselift RTU, consider the following:

- **Grease Not Fully Removed:**
 - Ensure sufficient product was applied to cover the entire soiled area.
 - Increase the dwell time. For very heavy or old baked-on grease, a longer penetration time is often required.
 - Agitate the area with a non-abrasive brush or pad to help break down the grease.
 - Reapply the product if necessary and repeat the process.
- **Residue Left Behind:**
 - Ensure the surface was thoroughly rinsed with clean water after wiping.
 - Use a clean, damp cloth for wiping and rinsing.
- **Nozzle Clogging:**
 - Remove the nozzle and rinse it under warm running water to clear any dried product.

SPECIFICATIONS

Attribute	Detail
Brand	Ecolab
Product Name	Greaselift RTU
Item Form	Liquid
Scent	Unscented
Specific Uses For Product	All Purpose, Baked-On Grease Removal
Material Feature	Non-Toxic, Non-Caustic
Volume	32 FL OZ (946 mL) per bottle
ASIN	B083YVHTWZ

WARRANTY AND SUPPORT

For specific warranty information or technical support regarding Ecolab Greaselift RTU, please contact Ecolab directly through their official website or customer service channels. Product support and safety data sheets (SDS) are typically available from the manufacturer.

You can visit the official Ecolab Store for more information:[Ecolab Store on Amazon](#)





[\[pdf\]](#) Borchure

EFFECTIVE DEGREASER MADE SAFER Greaselift Degreaser SAFER* Effective degreaser that requires no gloves or goggles to clean ovens grills stove hoods and vents 18 nov 2020 — features a unique technology actually penetrates tough baked on grease lifts it away from the surface It is powerful eco6100155 brochure hillnmarkes ASSETS DOCUMENTS ITEMS EN ||| PDREEGSROEAAKSER SOLUTIONS EFFECTIVE DEGREASER. MADE SAFER*. Greaselift Degreaser Penetrates grease and lifts it from surfaces Requires no gloves or goggles Foaming for vertical clinging Aluminum safe Biodegradeable *When compared with caustic degreasers. Greaselift is non-corrosive and less ir... lang:en score:29 filesize: 2 M page_count: 2 document date: 2012-08-21



[\[pdf\]](#)

PDREEGSROEAAKSER SOLUTIONS EFFECTIVE DEGREASER. MADE SAFER*. Greaselift Degreaser Penetrates grease and lifts it from surfaces Requires no gloves or goggles Foaming for vertical clinging Aluminum safe Biodegradeable *When compared with caustic degreasers. Greaselift is non-corrosive and less ir... lang:en score:29 filesize: 2 M page_count: 0 document date: 0000-00-00