

Nemo 811666031693

NEMO Helio Portable Pressure Camp Shower User Manual

Model: 811666031693

PRODUCT OVERVIEW

The NEMO Helio Portable Pressure Camp Shower is an indispensable part of your outdoor gear, designed for convenience and efficiency. It features a pressurizing foot pump that delivers continuous, steady spraying power without needing to be hung. Ideal for showering, rinsing gear, or washing dishes in remote locations.



Figure 1: NEMO Helio Portable Pressure Camp Shower (11 Liter model).

KEY FEATURES

- **Generous Capacity:** 2.9-gallon / 11-liter tank provides 5–7 minutes of continuous, steady water pressure.
- **Extended Hose:** 7-foot neoprene sprayer hose with spray nozzle, long enough to hold overhead for a shower.
- **Ground-Based Operation:** No need to hang; the unit sits securely on the ground and is pressurized by a foot pump.
- **Easy Refill:** Can be refilled anywhere without requiring a hose connection.
- **Compact Design:** Folds down small for easy transport and storage.
- **Durable Materials:** Constructed from PU coated polyester, TPU, and Neoprene tubing for longevity.

KEY FEATURES



- 1 2.9-gallon tank
(5–7 minutes of continuous spray)
- 2 7-foot neoprene hose
- 3 Designed to rest on the ground
- 4 Attached foot pump for easy inflation
- 5 Black exterior naturally warms water when set in the sun
- 6 Non-absorbent, breezy mesh
- 7 Built to integrate with NEMO's Heliopolis shower tent

Figure 2: Diagram highlighting key features of the NEMO Helio shower, including tank, hose, foot pump, and warming capabilities.

SETUP INSTRUCTIONS

1. **Unpack the Shower:** Remove the Helio shower from its compact carrying case. Unroll the main tank and lay it flat on a stable surface.
2. **Connect the Foot Pump:** Ensure the foot pump hose is securely connected to the designated port on the main tank.
3. **Fill the Tank:** Locate the large port on the tank. Unscrew the cap and fill the tank with water. The 11-liter capacity is approximately 2.9 gallons. Ensure the cap is securely tightened after filling to prevent leaks and allow for proper pressurization.
4. **Position the Shower:** Place the Helio shower on a flat, stable surface. It is designed to sit on the ground and does not require hanging.
5. **Prepare the Nozzle:** Uncoil the 7-foot neoprene sprayer hose. The nozzle can be held by hand or, if available, placed in a nozzle holder within a compatible shower tent like the Heliopolis.

SITS SECURELY

No need to hang, sits securely on the ground and is pressurized by foot pump.



Figure 3: The NEMO Helio shower positioned securely on the ground, ready for use.

OPERATING INSTRUCTIONS

1. **Pressurize the Tank:** Use the integrated foot pump to pressurize the tank. Pump until the tank feels firm. The tank cannot be overinflated, allowing for easy top-up of pressure during use.
2. **Adjust Water Temperature (Optional):** For warmer water, place the black tank in direct sunlight. The material is designed to naturally warm the water. Alternatively, fill directly with pre-heated water.
3. **Initiate Water Flow:** Point the spray nozzle away from yourself. The nozzle has a two-stage mechanism:
 - **Manual Trigger:** Squeeze the trigger for intermittent spray.
 - **Continuous Spray:** Engage the lock mechanism on the nozzle for a continuous flow, ideal for showering or extended tasks.
4. **Maintain Pressure:** If the water flow weakens during use, simply pump the foot pump a few more times to restore pressure.

5. **After Use:** Release any remaining pressure by opening the nozzle.

WARM IN THE SUN

Warm in the sun or fill directly with hot water for a hot shower or dirty dishes.



Figure 4: The NEMO Helio tank absorbing sunlight to warm the water, demonstrating its passive heating capability.

MAINTENANCE

- **Drying:** After each use, especially when storing for extended periods, ensure the interior of the tank is thoroughly dry to prevent mold and mildew. The large opening facilitates drying and cleaning.
- **Cleaning:** Rinse the tank and hose with clean water. For deeper cleaning, a mild soap solution can be used, followed by thorough rinsing. Avoid harsh chemicals or abrasive cleaners.
- **Storage:** When not in use, fold the pressure shower down small. The hose and foot pump can be neatly nested under its base. Store in a cool, dry place away from direct sunlight and extreme temperatures.
- **Inspection:** Periodically inspect the hose, pump, and tank for any signs of wear, cracks, or damage. Ensure all connections are secure.

TROUBLESHOOTING

Problem	Possible Cause	Solution
No water flow or weak pressure.	Insufficient pressure; air leak; clogged nozzle.	Pump the foot pump more to build pressure. Check all connections for tightness. Inspect nozzle for blockages and clear if necessary.
Water leaking from tank or connections.	Cap not sealed properly; hose connection loose; damage to tank/hose.	Ensure fill cap is tightly secured. Check hose connections and tighten. Inspect for visible damage; if damaged, contact support.
Difficulty filling the tank.	Tank not fully open; awkward angle.	Ensure the tank is fully unrolled and the opening is wide. Use a funnel if needed.

SPECIFICATIONS

Attribute	Detail
Model	811666031693
Capacity	11 Liter (2.9 Gallons)
Hose Length	7 feet
Weight	605 Grams (1 lb 5 oz)
Dimensions (LxWxH)	10 x 10 x 6 inches (Packed: 5.5 x 8.5 in dia / 14 x 22 cm dia)
Color	Black Dark Verglas
Material	PU coated polyester, TPU, Neoprene tubing



Figure 5: Detailed specifications for the NEMO Helio Portable Pressure Camp Shower.

Every NEMO product is backed by a **lifetime warranty** against defects in workmanship and materials to the original owner. For warranty claims, technical support, or any inquiries regarding your NEMO Helio Portable Pressure Camp Shower, please visit the official NEMO website or contact their customer service directly.

SPECIFICATIONS

Weight	1 lb 5 oz / 605 g
Packed Size	5.5 x 8.5 in dia / 14 x 22 cm dia
Dimensions	9 x 17 in / 24 x 42 cm
Color	Black / Dark Verglas
Materials	PU coated polyester, TPU, Neoprene tubing
Stuff Sack Style	Drawstring stuff sack

Figure 6: Information regarding NEMO's commitment to quality and lifetime warranty.

