

[Manuals.plus](#) /

› [NGOSEW](#) /

› NGOSEW Industrial Sewing Machine Hinged Guide Presser Foot Set User Manual

NGOSEW 1set: 1/8"R, 3/16"R, 1/4"R, 3/16"L, 1/4"L

NGOSEW Industrial Sewing Machine Hinged Guide Presser Foot Set User Manual

Model: 1set: 1/8"R, 3/16"R, 1/4"R, 3/16"L, 1/4"L

Brand: NGOSEW

INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your NGOSEW Industrial Sewing Machine Hinged Guide Presser Foot Set. Please read this manual thoroughly before using the product to ensure proper function and longevity. Retain this manual for future reference.

PRODUCT OVERVIEW

The NGOSEW Hinged Guide Presser Foot Set is designed for industrial single needle sewing machines, facilitating precise top-stitching with integrated guides. This set includes five presser feet, each crafted from durable metal to withstand rigorous industrial use.



Image: The complete set of five hinged guide presser feet, including various sizes for both right and left top-stitching applications.

Included Presser Feet:

- 1/8" Right Guide (R)
- 3/16" Right Guide (R)
- 1/4" Right Guide (R)
- 3/16" Left Guide (L)
- 1/4" Left Guide (L)

Each foot features a hinged design for smooth fabric feeding and a spring guide for consistent seam allowances during top-stitching.

COMPATIBILITY

This presser foot set is compatible with most industrial single needle sewing machines. Specific compatible models include, but are not limited to:

- **JUKI:** DDL-127, DDL-227, DDL-500, DDL-552, DDL-553, DDL-555, DDL-5550, DDL-5600, DDL-8300, DDL-8500, DDL-8700, TL98E
- **BROTHER:** B705, B707, B715, B716, B735, B737, B738, B745, B755, B757, B758, B767, B781, PQ1300, PQ1500
- **ARTISAN:** 196R, 5550N, 8500N, ZJ-100
- **CONSEW:** 30, 98, 99, 102, 103, 105, 210, 217, 218, 219, 220, 230, 290, 310, 2230, 7360R-1
- **GEMSY:** 8700

- **MITSU:** DB-120, DB-121, DB-122, DB-126, DB-130, DB-170, DB-189, DB-199, LS2-130, LS2-150, LS2-180, LS2-190, LS2-1130
- **RELIABLE:** MSK-8800, MSK-8550M, MSK-8870M
- **REX:** RX8500
- **SINGER:** 95, 96, 120U, 121C, 121D, 188K, 191D, 195K, 196K, 241, 251, 281, 366K, 400W, 402W, 451K, 491D, 591D, 600W, 660A, 691D, 770D, 771D, 2191, 2491D
- **SUNSTAR:** KM-123A, KM-123B, KM-137A, KM-137B, KM-146BL, KM-250
- **TACSEW:** 5550, T8700
- **TAIKO:** TK-505, TK-510

If your machine model is not listed, compare your current presser foot attachment mechanism with the standard industrial single needle presser foot design to confirm compatibility.

INSTALLATION AND SETUP

Safety Precautions:

- Always turn off and unplug your sewing machine before installing or changing any parts.
- Ensure the needle is in its highest position to prevent accidental injury.

Installation Steps:

1. **Remove Existing Presser Foot:** Loosen the thumb screw that holds the current presser foot to the presser foot bar. Carefully remove the old foot.
2. **Select the Correct Foot:** Choose the desired hinged guide presser foot (e.g., 1/8"R, 3/16"R, 1/4"R, 3/16"L, 1/4"L) based on your stitching requirements.
3. **Attach New Presser Foot:** Align the new NGOSEW presser foot with the presser foot bar. Ensure the pin on the foot fits into the slot on the bar.
4. **Secure the Foot:** Tighten the thumb screw firmly to secure the presser foot in place. Do not overtighten.
5. **Verify Alignment:** Gently lower the presser foot and check that the needle passes cleanly through the center of the foot's opening without striking any part of the foot. Adjust if necessary.

OPERATING INSTRUCTIONS

These hinged guide presser feet are designed to assist in creating consistent top-stitching lines by providing a physical guide against the fabric edge or a previous seam.

Using the Guide:

1. **Position Fabric:** Place your fabric under the presser foot.
2. **Align Guide:** Position the edge of your fabric or the existing seam against the guide on the presser foot. The guide will maintain a consistent distance from the needle.
3. **Begin Sewing:** Start sewing slowly, ensuring the fabric edge remains in contact with the guide. The hinged design allows the foot to glide smoothly over varying fabric thicknesses and seams.
4. **Right (R) vs. Left (L) Guides:**
 - **Right Guide (R):** Used when the guide needs to be on the right side of the needle, typically for stitching along the left edge of the fabric or a seam.
 - **Left Guide (L):** Used when the guide needs to be on the left side of the needle, typically for stitching along the right edge of the fabric or a seam.

5. **Adjusting Stitch Length/Tension:** As with any sewing operation, adjust your machine's stitch length and tension settings as needed for your specific fabric and thread type.

MAINTENANCE

Proper maintenance ensures the longevity and optimal performance of your presser feet.

- **Cleaning:** After each use, wipe the presser feet with a soft, dry cloth to remove any lint, dust, or fabric fibers. For stubborn residue, a slightly damp cloth can be used, followed by thorough drying.
- **Inspection:** Periodically inspect the feet for any signs of wear, bending, or damage to the guide or the foot plate. Ensure the hinge mechanism moves freely.
- **Storage:** Store the presser feet in a dry, clean environment, preferably in a dedicated storage box or compartment to prevent damage and loss.
- **Lubrication:** These presser feet do not require lubrication. Avoid applying oils or greases, as they can attract lint and dirt.

TROUBLESHOOTING

If you encounter issues while using the presser feet, consider the following common solutions:

Problem	Possible Cause	Solution
Uneven stitching or skipped stitches	Incorrect needle size/type, improper tension, foot not securely attached.	Ensure the foot is tightened correctly. Check needle compatibility with fabric. Adjust machine tension.
Fabric not feeding smoothly	Lint buildup, foot not suitable for fabric thickness, feed dogs not engaged.	Clean the foot and feed dogs. Ensure the hinged foot can accommodate the fabric. Check feed dog settings.
Guide not maintaining straight line	Fabric not consistently against the guide, guide bent.	Practice maintaining consistent pressure against the guide. Inspect the guide for damage; replace if bent.

If problems persist, consult your sewing machine's manual or contact a qualified technician.

SPECIFICATIONS

Feature	Detail
Brand	NGOSEW
Model (Set)	1set: 1/8"R, 3/16"R, 1/4"R, 3/16"L, 1/4"L
Material	Metal
Type	Hinged Guide Presser Foot
Compatibility	Industrial Single Needle Sewing Machines (e.g., Juki DDL series)
UPC	611417903701

WARRANTY AND SUPPORT

For information regarding warranty coverage or technical support, please contact NGOSEW directly or refer to the seller's policies where the product was purchased. Keep your purchase receipt as proof of purchase. You can visit the official NGOSEW store for more information:[NGOSEW Store on Amazon](#).

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question