Magicshine RN 1200

Magicshine RN 1200 Bike Light Instruction Manual

Model: RN 1200

Introduction

Thank you for choosing the Magicshine RN 1200 Bike Light. This high-performance headlight is designed to provide superior illumination and safety for various cycling activities, from mountain biking to street commuting. Featuring a powerful CREE LED, IPX7 waterproof rating, and a versatile Type-C rechargeable battery with reverse charging capabilities, the RN 1200 is built for reliability and convenience. Please read this manual thoroughly before use to ensure proper operation and maintenance.



Figure 1: The Magicshine RN 1200 Bike Light.

Safety Information

- Always ensure the light is securely mounted before riding.
- Do not look directly into the light beam when it is on, as it can cause temporary vision impairment.
- Keep the light away from children.
- Do not disassemble or modify the light. This will void the warranty and may cause damage.
- Ensure the USB-C port cover is securely closed to maintain IPX7 waterproof rating, especially in wet conditions.
- Use only the provided or recommended charging cables and adapters.
- The light may become warm during extended use; this is normal.

Package Contents

Verify that all items are present in your package:

- Magicshine RN 1200 Bike Light
- Handlebar Mount (Garmin compatible)
- 5 x Handlebar Straps (for 25.4mm, 28mm, 31.8mm, 35mm, and certain aero bars)

- USB-C Charging Cable
- Hex Key
- User Manual



Figure 2: Contents of the Magicshine RN 1200 package.

Setup

Mounting the Light

1. **Select Appropriate Strap:** Choose one of the five provided handlebar straps that best fits your handlebar diameter (25.4mm, 28mm, 31.8mm, 35mm, or aero bars).
2. **Attach Mount to Handlebar:** Position the handlebar mount on your desired location on the handlebar. Secure it firmly using the selected strap and the included hex key. Ensure the mount is stable and does not rotate.
3. **Attach Light to Mount:** The RN 1200 features a Garmin-compatible base. Align the light with the mount and twist it clockwise until it clicks securely into place.



Figure 3: The RN 1200 light mounted on a bicycle handlebar.




Figure 4: Different mounting configurations for the RN 1200.

Operating Instructions

Power Button Functions

The single power button controls all functions of the RN 1200.

- **Check Battery (Light Off):** Short click the power button to display the current battery level indicator.
- **Turn On:** Press and hold the power button for approximately 1 second to turn the light on. It will activate in the last used constant mode.
- **Cycle Brightness Modes (Light On):** Single click the power button to cycle through the constant brightness modes: Low (300 LM) → Mid (600 LM) → High (1200 LM).
- **Switch to Flash Mode:** Double click the power button to switch to flash modes.
- **Cycle Flash Modes (Flash Mode On):** Single click the power button to cycle through flash modes: Flash 1 (0-600 LM) → Flash 2 (0-900 LM).
- **Switch back to Constant Mode:** Double click the power button to switch back to constant modes.
- **Turn Off:** Press and hold the power button for approximately 1 second to turn the light off.



Figure 5: Easy operation of the RN 1200 via its single button.




Figure 6: The five light modes and their respective brightness and runtimes.

Battery Level Indicator

The power button also serves as a battery level indicator:

- **Green:** 21% - 100% battery remaining.
- **Constant Red:** 11% - 20% battery remaining.
- **Flashing Red:** 1% - 10% battery remaining.



Figure 7: Battery level indications.

Anti-Glare Beam

The RN 1200 features an anti-glare design that diffuses the top portion of the beam. This helps prevent blinding oncoming traffic or pedestrians, enhancing safety for everyone on the road.




Figure 8: Anti-glare beam technology for increased safety.

Charging and Power Bank Function

The RN 1200 is equipped with a USB-C port for convenient charging and can also function as a power bank.

- **Charging the Light:** Connect the provided USB-C cable to the light's USB-C port and to a USB power source (e.g., wall adapter, computer USB port). The charging time is approximately 2.5 hours with a 5V 3A charger.

- **Power Bank Function:** The RN 1200 can reverse charge your compatible mobile devices via its Type-C port. It supports up to 15W fast charging (5V/3A). A Type-C to Type-C cable is required for this function (not included).



Figure 9: USB-C fast charging and power bank capabilities.

Maintenance

- **Cleaning:** Wipe the light with a soft, damp cloth. Do not use abrasive cleaners or solvents.

- **Storage:** Store the light in a cool, dry place when not in use. For long-term storage, charge the battery to approximately 50% every 3-6 months to preserve battery life.
- **Water Resistance:** The light has an IPX7 waterproof rating, meaning it can withstand immersion in water up to 1 meter for 30 minutes. Always ensure the USB-C port cover is sealed tightly before exposing the light to water.




Figure 10: The RN 1200's IPX7 waterproof design.

Troubleshooting

Problem	Possible Cause	Solution
Light does not turn on.	Low battery; incorrect operation.	Charge the light fully. Press and hold the power button for 1 second to turn on.
Light turns off unexpectedly.	Battery depleted; overheating.	Recharge the battery. Allow the light to cool down if it feels excessively hot.
Light flickers or dims.	Low battery; thermal management activation.	Charge the battery. This is normal behavior for thermal management to prevent damage.
Cannot switch modes.	Incorrect button press.	Single click to cycle brightness, double click to switch between constant and flash modes.

Specifications

Feature	Detail
Model Name	RN 1200
Brightness	1200 Lumens (Max)
LED Type	CREE LED
Battery Capacity	4000mAh
Charging Port	USB Type-C (Input/Output)
Charging Time	Approx. 2.5 hours (with 5V 3A charger)
Runtime	1.5 hours (High) to 7 hours (Low/Flash)
Water Resistance	IPX7
Material	Metal
Dimensions (LxWxH)	4.21" x 1.22" x 1.22"
Weight	172 Grams




Figure 11: Detailed light mode specifications and runtimes.

Warranty and Support

Magicshine offers a **24 Months Manufacturer's Warranty** for the RN 1200 Bike Light. If you encounter any quality issues or require technical assistance, please contact Magicshine customer support through their official website or the retailer where you purchased the product.
For further information and support, visit the official Magicshine website:www.magicshine.com

Official Product Video

Watch the official operation demo for the Magicshine RN 1200 to see its features in action:

Your browser does not support the video tag.

Video 1: Magicshine RN1200 Light Modes Operation Demo. This video demonstrates how to operate the light, including turning it on/off, cycling through brightness modes, and switching to flash modes.

© 2024 Magicshine. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question