



[Manuals.plus](#) /

> [Justrite](#) /

> Justrite Talon SX Berm T8426 Instruction Manual

## Justrite T8426

# Instruction Manual for Justrite Talon SX Berm T8426

Model: T8426 | Product: Talon SX Berm 5X10X1'BLK

## INTRODUCTION

---

This manual provides essential information for the proper setup, operation, and maintenance of your Justrite Talon SX Berm, model T8426. This product is designed for reliable spill containment, offering a robust solution for temporary or permanent storage of drums, tanks, and equipment that may leak hazardous materials. Please read this manual thoroughly before use to ensure safe and effective deployment.

## SAFETY INFORMATION

---

Always prioritize safety when handling and deploying the berm. Failure to follow these guidelines may result in injury, property damage, or environmental contamination.

- Ensure the deployment area is level, free of sharp objects, and capable of supporting the weight of the berm and its contents.
- Do not exceed the berm's stated containment capacity.
- Always wear appropriate Personal Protective Equipment (PPE) when handling hazardous materials or deploying the berm.
- Inspect the berm for any damage before each use. Do not use a damaged berm.
- Keep the berm away from open flames or extreme heat sources.
- Properly dispose of any contained liquids according to local, state, and federal regulations.

## COMPONENTS

---

The Justrite Talon SX Berm (T8426) typically consists of the following primary components:

- **Berm Fabric:** Durable, chemical-resistant material forming the base and walls.
- **L-Brackets:** Integrated or removable L-shaped supports that maintain the wall's upright position.
- **Ground Mat (Optional):** A protective layer placed beneath the berm to prevent punctures.



Image: The Justrite Talon SX Berm T8426, illustrating its robust black fabric construction and the upright L-bracket walls designed for spill containment. This view highlights the overall structure of the berm when deployed.

## SETUP INSTRUCTIONS

---

Follow these steps for proper deployment of your Talon SX Berm:

1. **Prepare the Site:** Select a flat, stable, and clean surface. Remove any sharp objects, debris, or uneven terrain that could damage the berm fabric. If available, lay down a protective ground mat.
2. **Unfold the Berm:** Carefully unroll and unfold the berm at the chosen location. Ensure the base is fully extended and flat.
3. **Erect the Walls:** The Talon SX Berm features L-brackets that automatically spring into an upright position as the berm is unfolded. Ensure all four walls are fully extended and locked into their vertical position. Verify that the corners are properly formed.
4. **Inspect:** Perform a final visual inspection of the berm for any creases, tears, or improper wall setup before placing any items inside.

## OPERATING INSTRUCTIONS

---

Once the berm is set up, it is ready for use as a spill containment area.

- **Placement of Items:** Carefully place drums, tanks, or equipment within the berm's containment area. Avoid dragging heavy or sharp objects across the berm's floor.
- **Spill Response:** In the event of a spill, the berm will contain the liquid. Do not allow the contained liquid to exceed the berm's capacity.
- **Liquid Removal:** Once a spill is contained, remove the liquid using appropriate methods such as pumps, absorbents, or vacuum systems. Ensure proper disposal of hazardous waste according to all applicable regulations.
- **Vehicle Entry/Exit (if applicable):** For berms designed for vehicle traffic, ensure vehicles enter and exit slowly and carefully to avoid damaging the berm walls or fabric. The L-brackets are designed to temporarily collapse under wheel pressure and spring back up.

## MAINTENANCE

---

Regular maintenance will extend the lifespan of your berm and ensure its effectiveness.

- **Cleaning:** After use, especially after a spill, clean the berm thoroughly with mild soap and water. Rinse completely and allow to air dry before folding for storage. Avoid harsh chemicals or abrasive cleaners.
- **Inspection:** Periodically inspect the berm for any signs of wear, tears, punctures, or damage to the fabric or L-brackets. Pay close attention to seams and corners.
- **Storage:** When not in use, fold the berm neatly and store it in a cool, dry place away from direct sunlight, extreme temperatures, and sharp objects.
- **Repairs:** Small punctures or tears may be repaired using a compatible patch kit. Consult Justrite's official resources or contact customer support for recommended repair procedures and materials.

## TROUBLESHOOTING

---

This section addresses common issues you might encounter.

Problem	Possible Cause	Solution
Berm walls not standing upright.	L-brackets not fully extended or locked.	Ensure the berm is fully unfolded and gently pull the walls outwards to allow the L-brackets to fully extend and lock into position.
Liquid leaking from berm.	Puncture or tear in fabric; improper wall setup.	Immediately remove contents. Inspect for damage. Repair with a patch kit or replace the berm if damage is severe. Re-check wall setup.
Berm appears dirty or stained.	Accumulated dirt or residue from spills.	Clean with mild soap and water. Rinse thoroughly and air dry.

## SPECIFICATIONS

---

Key technical specifications for the Justrite Talon SX Berm T8426:

- **Model:** T8426
- **Dimensions (L x W x H):** 5 ft x 10 ft x 1 ft (approximately 152 cm x 305 cm x 30.5 cm)
- **Containment Capacity:** Varies by exact model and fill level, typically calculated based on dimensions. (e.g., 5'x10'x1' = 50 cubic feet = approx. 374 gallons)
- **Material:** Chemical-resistant fabric (e.g., PVC-coated fabric)

- **Wall Type:** L-Bracket (auto-erecting)
- **Color:** Black
- **Manufacturer:** Justrite

## WARRANTY AND SUPPORT

---

For information regarding product warranty, technical support, or to purchase replacement parts, please refer to the official Justrite website or contact their customer service department. Keep your purchase receipt and product model number (T8426) handy when contacting support.

**Justrite Official Website:** [www.justrite.com](http://www.justrite.com)

