iSpring FSF3

iSpring FSF3 15-Stage Shower Filter Replacement Cartridge Instruction Manual

1. Product Overview

The iSpring FSF3 is a replacement cartridge designed for iSpring SF series shower filters, including models like SF3S. This cartridge features a scientifically formulated process utilizing 12 different premium quality filtration media across 15 stages. Its primary function is to significantly reduce common water impurities such as chlorine, sediment, hydrogen sulfide, and heavy metals, which can impact skin, hair, and nails. The filter also incorporates elements like Vitamin C and mineralized balls to enhance water quality. This replacement cartridge is engineered for high output and a 'Never Clog' design, ensuring consistent water flow and preventing limescale buildup. It is compatible with standard 1/2-inch shower connections and various showerhead types (fixed, handheld, rain).



Image 1: The iSpring FSF3 replacement cartridge shown within its chrome shower filter housing.




Image 2: Detailed diagram showing the 15 distinct filtration stages of the iSpring SF3S shower filter, including sand filter, stainless steel mesh, PP cotton, Vitamin C, Maifan stones, mineralized balls, magnetic energy balls, ceramic balls, alkaline balls, KDF-55, coconut activated carbon, and micro-porous PP cotton.

2. Installation Instructions

The iSpring FSF3 replacement cartridge is designed for easy, tool-free installation into compatible iSpring SF series shower filters. Ensure you have plumber's tape ready before beginning.

2.1 Preparing for Installation

1. Turn off the water supply to your shower.
2. Unscrew and remove your existing shower filter housing from the shower arm.
3. Remove the old filter cartridge from the housing. Dispose of the old cartridge responsibly.

2.2 Cartridge Replacement Steps

1. Unpack the new iSpring FSF3 replacement cartridge.
2. Insert the new cartridge into the shower filter housing, ensuring it is seated correctly.
3. Apply 3 to 4 wraps of plumber's tape to the threads of the shower arm.
4. Attach the top end of the shower filter housing (1/2" Female Adapter) to the shower arm or adapter.

Hand-tighten securely.

5. Apply 3 to 4 wraps of plumber's tape to the threads of the shower filter's bottom outlet.
6. Attach your shower head or hose to the bottom end of the shower filter (1/2" Male Adapter). Hand-tighten securely.
7. Turn on the water supply and check for any leaks. If leaks occur, tighten connections slightly or reapply plumber's tape.



Image 3: Visual guide for easy installation, detailing the connection points for the shower arm and shower head, and the placement of the FSF3 cartridge.



Image 4: Examples of the iSpring shower filter installed with different shower configurations, demonstrating its versatility with fixed, handheld, and rain showerheads without impacting water pressure.

3. Operating Instructions

Once installed, the iSpring FSF3 replacement cartridge operates automatically as water flows through your shower. No further user interaction is required for its filtration process.

3.1 Water Pressure

The filter is designed to have minimal impact on your shower's water pressure, ensuring a consistent and comfortable showering experience.

4. Maintenance

Regular maintenance ensures the longevity and effectiveness of your iSpring shower filter system.

4.1 Cartridge Replacement Schedule

The iSpring FSF3 replacement cartridge typically lasts for 6-9 months or filters up to 16,000 gallons of water, whichever comes first. Replace the cartridge according to this schedule to maintain optimal filtration performance.

4.2 Flushing for Sediment Buildup

If your source water has high levels of sediment, particularly common with well water, the filter may experience buildup over time. To address this:

1. Turn off the water supply to your shower.
2. Remove the shower filter housing.
3. Carefully remove the FSF3 cartridge.
4. Flip the cartridge over and flush it with hot water to remove any accumulated sediment.
5. Reinsert the cartridge in its original position and reassemble the filter housing.
6. Turn on the water supply and check for leaks.

5. Troubleshooting

This section addresses common concerns related to the shower filter cartridge.

5.1 Reduced Water Pressure

If you experience a noticeable reduction in water pressure, it may indicate sediment buildup within the filter cartridge. Refer to Section 4.2 for instructions on flushing the cartridge to clear sediment.

5.2 Leaks After Installation

If leaks occur after installation, ensure all connections are hand-tightened securely. Verify that plumber's tape was applied correctly and sufficiently (3-4 wraps) to all threaded connections. If necessary, disassemble, reapply plumber's tape, and reassemble.

5.3 Filter Clogging

The iSpring FSF3 features a 'Never Clog' design intended to prevent limescale buildup and clogging, even with hard water. If you suspect a clog, perform the flushing procedure described in Section 4.2.

6. Specifications

Specification	Detail
Model Number	FSF3
Material	Activated Carbon, Polypropylene (PP), Resin
Item Weight	340 Grams (12 ounces)
Product Dimensions	3 x 3 x 3.6 inches
Filtration Stages	15-Stage
Product Benefits	Removes chlorine, sediment, heavy metals, hydrogen sulfide; improves skin, hair, and nails
Lifespan	6-9 months or 16,000 gallons
Included Components	Filter cartridge
Color	White

UPC	810004171916



Image 5: Dimensional drawing of the iSpring SF3S shower filter and its FSF3 replacement cartridge, indicating measurements for both components.

7. Warranty and Support

7.1 Warranty Information

The iSpring FSF3 replacement cartridge comes with a 3-Month Warranty. Please retain your proof of purchase for warranty claims.

7.2 Customer Support

For any questions, technical assistance, or warranty support, please contact iSpring customer service. Experienced support staff are available to provide prompt and efficient assistance.
Contact information can typically be found on the iSpring official website or through the retailer where the product was purchased.