



[Manuals.plus](#) /

› [Shurtape](#) /

› Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape User Manual

## Shurtape 104067 PE 333

# Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape User Manual

Comprehensive instructions for proper use and maintenance.

## 1. INTRODUCTION

---

This manual provides detailed instructions for the Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape. This product is designed for various construction and painting applications, including flexible masking during stucco application, sealing to poly-sheeting, and creating vapor barriers. It is engineered to maintain a watertight seal.



**Figure 1:** Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape. This image displays a collection of red tape rolls, each labeled with "Shurtape PE 333 Non-UV-Resistant Polyethylene Tape" and specifications like "1.88 in x 60.1 yd". The rolls are arranged in a casual stack, highlighting the product's packaging and color.

## 2. SETUP AND PREPARATION

---

Proper preparation of the application surface is crucial for optimal adhesion and performance of the Shurtape PE 333 tape.

- 1. Surface Cleaning:** Ensure the application surface is clean, dry, and free from dust, dirt, grease, oil, and any other contaminants. Use an appropriate cleaner if necessary, and allow the surface to dry completely before tape application.
- 2. Temperature Conditions:** For best results, apply the tape within the recommended temperature range. The tape is designed for use in environments with lower temperature ratings of 32°F (0°C) and upper temperature ratings of 160°F (71°C).
- 3. Unrolling the Tape:** Carefully unroll the desired length of tape from the core. Avoid stretching the tape excessively during unrolling, as this can affect its adhesive properties.

## 3. OPERATING INSTRUCTIONS

---

The Shurtape PE 333 tape is versatile and can be used for several applications. Follow these guidelines for effective use.

### 3.1. Stucco Masking

- **Application:** Apply the tape firmly along the edges of areas to be protected from stucco, such as windows, doors, and trim.
- **Pressure:** Press down firmly along the entire length of the tape to ensure a strong bond and prevent stucco bleed-through.
- **Removal:** Remove the tape carefully once the stucco has set but is not fully cured, to avoid damaging the stucco finish or leaving adhesive residue.

### 3.2. Sealing to Poly-Sheeting and Vapor Barriers

- **Overlap:** When joining poly-sheeting or creating vapor barriers, ensure an adequate overlap of the sheeting material.
- **Seal Application:** Apply the tape directly over the overlapped seams, ensuring full coverage and a continuous seal.
- **Watertight Seal:** Apply consistent, firm pressure across the tape to activate the adhesive and create a watertight and airtight seal. The tape's polyethylene material and strong adhesive contribute to its ability to maintain a watertight seal.

## 4. MAINTENANCE AND STORAGE

---

Proper maintenance and storage will extend the shelf life and ensure the performance of your Shurtape PE 333 tape.

- **Storage Conditions:** Store tape rolls in a cool, dry place away from direct sunlight and extreme temperatures. Ideal storage temperature is typically between 60°F and 80°F (15°C and 27°C) with relative humidity between 40% and 60%.
- **Protection:** Keep tape rolls in their original packaging until ready for use to protect them from dust and physical damage.
- **Handling:** Avoid dropping or deforming the tape rolls, as this can damage the edges and affect application.

## 5. TROUBLESHOOTING

---

If you encounter issues during the application or performance of the Shurtape PE 333 tape, consider the following common solutions.

- **Poor Adhesion:**
  - Ensure the surface is clean, dry, and free of contaminants.
  - Verify that the application temperature is within the recommended range (32°F to 160°F).
  - Apply sufficient pressure during application to ensure proper adhesive contact.
- **Tape Tearing During Application:**
  - Check for nicks or damage on the tape roll edge.
  - Ensure the tape is not being stretched excessively during unrolling.
- **Residue Upon Removal (if applicable):**
  - While this tape is designed for specific applications, if residue occurs, it might be due to prolonged exposure to high temperatures or leaving the tape on for an extended period beyond its intended use.

- Remove tape as soon as the job allows, especially for temporary masking.

## 6. PRODUCT SPECIFICATIONS

---

Key technical specifications for the Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape.

Feature	Detail
Brand	Shurtape
Model Number	104067
Material	Polyethylene, Synthetic Adhesive, Rubber
Color	Red
Size	2 inches x 60.1 yards (48 mm x 55 m)
Item Thickness	7 Mils
Water Resistance Level	Water Resistant
Upper Temperature Rating	160 Degrees Fahrenheit (71°C)
Lower Temperature Rating	32 Degrees Fahrenheit (0°C)
Recommended Uses	Construction, Painting (Stucco Masking, Sealing to Poly-Sheeting, Vapor Barriers)
Special Feature	Maintains a watertight seal

## 7. WARRANTY INFORMATION

---

For specific warranty details regarding the Shurtape 104067 PE 333 Non-UV-Resistant Stucco Tape, please refer to the official Shurtape website or contact Shurtape customer support directly. Warranty terms typically cover manufacturing defects and material integrity under normal use conditions.

## 8. CUSTOMER SUPPORT

---

If you have any questions, require technical assistance, or need further information about the Shurtape 104067 PE 333 tape, please contact Shurtape customer support.

- **Website:** Visit the official [Shurtape website](#) for product information and resources.
- **Contact Information:** Refer to the Shurtape website for current contact methods, including phone numbers and email addresses for customer service.