Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

MeeFar MF-BAG-PP

MeeFar Car Roof Bag XBEEK Rooftop Cargo Carrier Manual

Model: MF-BAG-PP (15 Cubic Feet)
Brand: MeeFar

1. Introduction

The MeeFar XBEEK Rooftop Cargo Carrier is designed to provide additional storage space for your vehicle, making long trips and family vacations more convenient. This soft-shell carrier is 100% waterproof and tear-proof, ensuring your belongings remain safe and dry in various weather conditions. Its universal compatibility allows it to be used with any sized car or SUV, with or without a roof rack.
Key features include:

- **100% Waterproof & Tear-proof Material:** Constructed from durable 600D PVC tarpaulin with high-frequency voltage technology.
- **Easy to Use:** Quick and simple installation in minutes, foldable for compact storage when not in use.
- **Universal Compatibility:** Works with vehicles both with and without roof racks.
- **Enhanced Security:** Includes a combination lock to prevent zipper slipping and add security.
- **Large Storage Space:** 15 cubic feet capacity (44” L x 34” W x 17” H) can hold 4-6 suitcases, sleeping bags, and more.

2. What's in the Box

Your MeeFar XBEEK Rooftop Cargo Carrier package includes the following components:

- 1 x MeeFar XBEEK Rooftop Cargo Bag
- 1 x Anti-Slip Mat
- 1 x Luggage Combination Lock
- 6 x Security Door Hooks (for vehicles without roof racks)
- 8 x Reinforced Straps (pre-attached to the bag)
- 1 x Storage Bag



Figure 2.1: Included accessories with the MeeFar XBEEK Rooftop Cargo Bag.

3. Specifications

Feature	Detail
Brand	MeeFar
Model	MF-BAG-PP
Item Volume	15 Cubic Feet
Product Dimensions	44"L x 34"W x 17"H
Item Weight	8.6 Pounds

Material	Polyvinyl Chloride (PVC)
Water Resistance Level	Waterproof
Mounting Type	Roof Mount
Automotive Fit Type	Universal Fit
Color	Black and Orange



Figure 3.1: Product dimensions and example capacity.

4. Setup and Installation

The MeeFar XBEEK cargo carrier is designed for easy installation on various vehicle types. Follow these steps for proper

setup:

4.1. Preparation

1. Ensure your vehicle's roof is clean and dry.
2. Unfold the cargo bag and lay it flat on a clean surface.
3. Place the provided anti-slip mat on the vehicle's roof where the cargo bag will sit. This protects your car's paint and prevents the bag from shifting.



Figure 4.1: Anti-slip mat placement for roof protection and stability.

4.2. Loading the Bag

1. Open the main zipper of the cargo bag.
2. Load your luggage and items into the bag. Distribute weight evenly to maintain vehicle balance.
3. Once loaded, close the main zipper. Ensure the zipper is fully closed.
4. Fold the orange flap over the zipper and secure it using the Velcro strips. This creates a waterproof seal.



Figure 4.2: Waterproof sealing mechanism of the cargo bag.

4.3. Securing the Bag to the Vehicle

The MeeFar XBEEK offers two primary methods for securing the bag:

4.3.1. For Vehicles WITHOUT Roof Racks (using Door Hooks)

1. Open your vehicle's doors.
2. Attach the 6 provided security door hooks to the reinforced straps on the cargo bag.
3. Carefully insert the flat end of each door hook under the weather stripping of your vehicle's door frame. Ensure the hook is securely seated.
4. Close the vehicle doors. The pressure from the closed door will hold the hooks firmly in place.
5. Tighten the reinforced straps to secure the bag firmly to the roof. Ensure there is no slack in the straps.



Figure 4.3: Installation method for vehicles without roof racks.

4.3.2. For Vehicles WITH Roof Racks (Side Rails, Cross Bars, or Baskets)

1. Place the loaded cargo bag on the anti-slip mat on your vehicle's roof, centered over your roof rack.
2. Thread the reinforced straps (pre-attached to the bag) around your vehicle's roof rack bars (side rails, cross bars, or basket).
3. Securely buckle and tighten all straps. Ensure the bag is taut and does not shift.



Figure 4.4: Installation method for vehicles with roof racks.

4.4. Final Security

1. Once the bag is fully secured with the straps, use the provided combination lock to secure the main zipper pullers. This adds an extra layer of security against theft and accidental opening.
2. Double-check all straps and buckles to ensure they are tight and the bag is stable before driving.



Figure 4.5: Using the combination lock for added security.

5. Operating Instructions

To ensure optimal performance and safety while using your MeeFar XBEEK Rooftop Cargo Carrier, consider the following operational guidelines:

- **Weight Distribution:** Always distribute the weight of your cargo evenly inside the bag. Avoid placing all heavy items on one side.
- **Aerodynamics:** For best aerodynamic performance and fuel efficiency, try to keep the bag as streamlined as possible. Avoid overfilling, which can cause bulging.
- **Regular Checks:** During long trips, periodically check the tightness of the straps and the stability of the bag, especially after the first few miles and during rest stops.
- **Driving Conditions:** While the bag is waterproof, extreme weather conditions (e.g., severe crosswinds, torrential rain) may require extra caution. Adjust driving speed as necessary.

- **Vehicle Clearance:** Be mindful of your vehicle's increased height when entering garages, car washes, or areas with low overhead clearance.

6. Maintenance and Storage

Proper maintenance and storage will extend the lifespan of your cargo carrier:

- **Cleaning:** After use, especially after exposure to dirt, dust, or road grime, clean the bag with a damp cloth and mild soap. Rinse thoroughly and allow to air dry completely.
- **Drying:** Ensure the bag is completely dry before folding and storing to prevent mold or mildew growth.
- **Storage:** The soft-shell design allows the bag to be folded compactly into the provided storage bag. Store in a cool, dry place away from direct sunlight and extreme temperatures.
- **Inspect Straps and Zippers:** Periodically inspect all straps, buckles, and zippers for any signs of wear, fraying, or damage. Replace components if necessary.



Figure 6.1: The cargo bag folds compactly for easy storage.

7. Troubleshooting

If you encounter any issues with your MeeFar XBEEK Rooftop Cargo Carrier, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Water inside the bag	Zipper not fully closed or Velcro flap not sealed.	Ensure zipper is completely closed and the Velcro flap is pressed down firmly over the zipper.
Bag shifting on roof	Straps are loose or anti-slip mat is not properly placed.	Re-tighten all straps. Ensure the anti-slip mat is flat and centered under the bag.

Excessive noise/flapping	Loose straps or unevenly distributed cargo.	Tighten all straps. Rearrange cargo for a more compact and even shape.
Difficulty closing zipper	Bag is overfilled or zipper is misaligned.	Remove some items to reduce bulk. Gently realign the zipper teeth.

8. Warranty and Support

For warranty information or technical support, please refer to the contact details provided on the product packaging or visit the official MeeFar website. Keep your purchase receipt for warranty claims.
For additional resources and product information, you may visit theMeeFar Store on Amazon.

© 2024 MeeFar. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B08B3N8M83

More documents and user manuals: **https://manuals.plus/**