

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [BLACK+DECKER](#) /
- › [BLACK+DECKER Portable Air Conditioner User Manual](#)

BLACK+DECKER BPACT14WT, BPACT12WT

BLACK+DECKER Portable Air Conditioner User Manual

Models: BPACT14WT, BPACT12WT

PRODUCT OVERVIEW

The BLACK+DECKER Portable Air Conditioner units (Models BPACT14WT and BPACT12WT) are designed to provide a comfortable indoor climate by offering cooling, dehumidifying, and air circulation functions. These units are equipped with user-friendly electronic controls and come with a remote for convenient operation. They are designed for easy mobility with rolling castors and side carrying handles.



Image: Two BLACK+DECKER Portable Air Conditioners, showcasing their compact design and white finish.

SETUP AND INSTALLATION

Unit Placement

For optimal performance and to minimize noise and vibration, place the air conditioner on a firm, smooth, and level

floor strong enough to support the unit. Ensure adequate space around the unit for proper airflow.

Window Kit Installation

The unit includes a window kit for exhaust ventilation. This kit is compatible with double-hung or sliding windows only. It is not designed for crank casement windows. The exhaust hose is approximately 5 feet long. If your window opening is smaller than the provided panel, the panel can be cut to size using a saw, exercising caution.

Your browser does not support the video tag.

Video: An official BLACK+DECKER video demonstrating the setup and features of the portable air conditioner, including installation of the window kit.

OPERATING INSTRUCTIONS

Controls and Display

The unit features easy-to-use LED electronic controls with a digital display for simple operation. A full-function remote control with touch controls is also included for convenience.

Control Panel



Image: The unit's control panel with LED display, indicating current temperature and mode settings.

Remote Control Included



Image: The remote control for the air conditioner, featuring a digital display and various function buttons.

Modes and Functions

- **Cooling:** Provides powerful cooling for rooms. For optimal cooling, ensure all windows and doors are closed and remove any significant heat sources from the room.
- **Dehumidifying:** Reduces humidity levels in the air.
- **Fan:** Circulates air without cooling.
- **Timer Function:** A 24-hour on/off timer allows you to program when the unit automatically turns on or shuts off.
- **Adjustable Thermostat:** Wide-range, adjustable thermostat control allows you to set the desired temperature.

- **Sleep Function:** Adjusts settings to maintain a comfortable room temperature during sleep.

After a power outage, the unit will restart automatically. Note that a micro-processor control delays the compressor from operating until 3 minutes have passed after startup or restart.

MAINTENANCE

Air Filter Cleaning

The air conditioner is equipped with a removable, washable filter. Regularly cleaning the filter is essential to maintain the unit's efficiency and ensure it outputs fresh, clean air.



Image: Demonstrates the removal of the washable air filter from the side of the unit for cleaning.

TROUBLESHOOTING

If you encounter issues with your BLACK+DECKER Portable Air Conditioner, please refer to the common questions and solutions below:

- **Unit not cooling effectively:** Ensure all windows and doors in the room are closed. Remove any significant heat sources if possible. Remember there is a 3-minute delay before the compressor starts operating after the unit is turned on or restarted.
- **Noise Level:** The unit operates at approximately 75 dB on its high setting. This is the expected sound level for the unit.
- **Window Extender:** An extender for wider windows is not available.

- **Venting Options:** The unit can be vented through a window, or through a wall or door into another room, provided proper ventilation is maintained.
- **Crank Casement Windows:** The window kit is not compatible with crank casement windows; it works only with double-hung or sliding windows.
- **Cutting Window Panel:** Yes, the included window panel can be cut to size if your window opening is smaller. Exercise caution when cutting.

SPECIFICATIONS

Feature	Specification (BPACT14WT)	Specification (BPACT12WT)
Brand	BLACK+DECKER	
Item Model Number	BPACT14WT	BPACT12WT
Cooling Capacity	14,000 BTU	12,000 BTU
Floor Area Coverage	Approx. 22 x 25 ft	Approx. 20 x 25 ft (250-300 sq ft)
Form Factor	Portable	
Voltage	115V / 120 Volts, 60Hz	
Amperage	9 Amps	
Noise Level (High Setting)	75 dB	
Refrigerant	R 410A	
Power Source	Corded Electric	
Color	White	
Power Cord Length	84-3/8 inches	

WARRANTY AND SUPPORT

For detailed warranty information and customer support, please refer to the official user manual provided with your product or visit the BLACK+DECKER website. You can also find a PDF version of the user manual [here](#). If you have further questions or require assistance, please contact BLACK+DECKER customer service.