MeeFar MF-BAG-PP

MeeFar XBEEK 20 Cubic Feet Car Roof Bag Instruction Manual

Model: MF-BAG-PP | Brand: MeeFar

Introduction

This manual provides detailed instructions for the safe and effective use of your MeeFar XBEEK 20 Cubic Feet Car Roof Bag. Designed for universal compatibility with or without roof racks, this waterproof cargo carrier offers significant additional storage for your vehicle. Please read all instructions carefully before installation and use.



Image: The MeeFar XBEEK 20 Cubic Feet Car Roof Bag securely mounted on a vehicle roof.

Package Contents

Verify that all items listed below are included in your package:

- 1x MeeFar XBEEK 20 Cubic Feet Car Roof Bag
- 1x Anti-Slip Mat
- 1x Combination Luggage Lock
- 6x Security Hooks
- 10x Reinforced Straps
- 1x Storage Bag
- 1x Instruction Manual



Image: All components included with the MeeFar XBEEK Car Roof Bag: the bag, anti-slip mat, combination lock, security hooks, straps, and storage bag.

Setup and Installation

The MeeFar XBEEK roof bag is designed for easy installation on vehicles with or without a roof rack. Follow these steps for secure attachment:

1. Prepare the Vehicle Roof

Clean the vehicle roof surface to ensure proper adhesion of the anti-slip mat. Place the provided anti-slip mat on the vehicle roof where the cargo bag will rest. This mat helps prevent the bag from shifting and protects your car's paint.



Image: Close-up of the anti-slip mat on a car roof, showing its textured surface for grip and protection.

2. Position the Cargo Bag

Place the empty MeeFar XBEEK roof bag on top of the anti-slip mat. Ensure it is centered and positioned to allow access to the zipper for loading.

3. Loading the Bag

Open the main zipper of the bag. Load your items, distributing weight evenly. Avoid overfilling to ensure the zipper can close properly and the bag maintains its shape for optimal aerodynamics and security.



Image: The MeeFar XBEEK Car Roof Bag illustrating its 20 cubic feet capacity, capable of holding multiple suitcases and camping gear.

4. Securing the Bag (With Roof Rack)

If your vehicle has a roof rack (side rails or crossbars):

1. Thread the reinforced straps through the buckles on the cargo bag.
2. Wrap the straps around your vehicle's roof rack bars.
3. Tighten the straps securely, ensuring the bag is firmly attached and does not shift.

5. Securing the Bag (Without Roof Rack)

If your vehicle does not have a roof rack:

1. Locate the door frame weather stripping on your vehicle.
2. Carefully pull back the weather stripping to expose the metal door frame.
3. Insert the provided security hooks under the metal door frame.
4. Close the weather stripping over the hooks to secure them.

5. Thread the reinforced straps through the buckles on the cargo bag and attach them to the installed security hooks.
6. Tighten the straps firmly, ensuring the bag is stable and centered.



Image: Step 1: Gently pull back the rubber weather stripping from the door frame.



Image: Step 2: Insert the security hook under the metal door frame.



Image: Step 3: Push the weather stripping back into place, securing the hook.



Image: Step 4: Attach the bag's strap to the secured hook and tighten.

Operating Instructions

Waterproofing and Security

The MeeFar XBEEK roof bag is constructed from 700D PVC tarpaulin with high-frequency voltage technology, ensuring 100% waterproof and tear-proof performance. The main zipper is protected by an extended rain curtain and a zipper flap with Velcro to prevent water ingress.



Image: Detailed view of the 700D waterproof fabric, extended rain curtain, and zipper flap with Velcro, highlighting the bag's waterproof sealing.

For added security, utilize the included combination luggage lock to secure the zipper pulls. This prevents accidental opening and deters unauthorized access to your belongings.



Image: A 4-digit combination lock securing the zipper of the roof bag, enhancing luggage security.

Driving with the Cargo Bag

After installation and loading, double-check all straps and buckles to ensure they are tight and secure. Periodically check the straps during long journeys to maintain tension. Drive cautiously, especially in windy conditions or at high speeds, as the added cargo can affect vehicle handling.

Maintenance

- **Cleaning:** Wipe the bag with a damp cloth and mild soap. Do not use harsh chemicals or abrasive cleaners.
- **Drying:** Ensure the bag is completely dry before folding and storing to prevent mold or mildew.
- **Storage:** When not in use, fold the bag and store it in the provided storage bag in a cool, dry place away from direct sunlight.

Troubleshooting

- **Bag Shifting:** Ensure the anti-slip mat is correctly positioned and all straps are tightened firmly. Re-adjust straps if necessary.
- **Water Leakage:** Verify that the zipper is fully closed and the Velcro flap is properly sealed over the zipper. Check for any tears or punctures in the fabric.
- **Difficulty Closing Zipper:** Avoid overfilling the bag. Distribute contents evenly to reduce strain on the zipper.

Specifications

Brand	MeeFar
Model	MF-BAG-PP
Item Volume	20 Cubic Feet
Product Dimensions	51"L x 40"W x 17"H
Material	700D PVC Tarpaulin
Water Resistance Level	Waterproof
Mounting Type	Roof Mount (Universal Fit)
Item Weight	8.58 pounds (3.9 Kilograms)
Color	Black

Warranty and Support

MeeFar is dedicated to providing high-quality products. For any questions, concerns, or warranty claims, please refer to the warranty card included in your package or visit the official MeeFar store for support.
Warranty Card Information: The product includes a warranty card. Please retain it for future reference.
Online Support: Visit the MeeFar Store on Amazon for additional product information and customer service.

© 2023 MeeFar. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question