Manuals+

Q & A | Deep Search | Upload

FLIR T540-EST

FLIR T540-EST Thermal Screening Camera User Manual

Model: T540-EST with 24-Degree Lens

1. Introduction

The FLIR T540-EST thermal imaging camera is designed for high-precision, non-contact temperature screening, specifically for elevated skin temperature detection in public health scenarios. This manual provides essential information for the proper setup, operation, and maintenance of your device, ensuring accurate and efficient screenings.

Figure 1: The FLIR T540-EST thermal screening camera, showcasing its ergonomic design and integrated lens.

2. Setup

Follow these steps to prepare your FLIR T540-EST for operation:

1. **Unboxing:** Carefully remove all components from the packaging. Verify that all items listed in the packing slip are present.
2. **Battery Installation:** The camera requires two Lithium Ion batteries (included). Insert the batteries into the designated compartment, ensuring correct polarity. Charge batteries fully before first use using the provided charger.
3. **Lens Attachment:** The 24-degree lens is typically pre-attached. If interchanging lenses, align the lens with the camera body's mount and rotate until it clicks securely into place.
4. **Mounting:** For stable and consistent screening, mount the camera on a tripod or a stable surface. Ensure the camera is positioned at an appropriate height for the subjects being screened.
5. **Initial Power-On:** Press and hold the power button until the FLIR logo appears on the screen.

3. Operating Instructions

The FLIR T540-EST is designed for intuitive operation. Familiarize yourself with its key features:

- **Power On/Off:** Press and hold the power button to turn the camera on or off. A short press will put the camera into standby mode.
- **Screen-EST Mode:** Activate the dedicated Screen-EST mode for streamlined temperature screening. This mode provides visual positioning guides, automatically samples to maintain an updated temperature average, and displays graphic pass/fail indicators.
- **Temperature Measurement:** The camera measures temperatures from 15°C to 45°C (59°F to 113°F). Ensure subjects are within the optimal screening distance for accurate readings.
- **Laser-Assisted Autofocus:** Utilize the laser-assisted autofocus feature to ensure sharp focus on the subject's face, which is critical for precise temperature readings.
- **Ergonomic Design:** The 180° rotating optical block allows for comfortable viewing angles during extended screening sessions. The vivid 4-inch capacitive touchscreen provides an interactive interface for settings and viewing.
- **Interpreting Results:** In Screen-EST mode, the camera will provide clear visual cues (e.g., green for pass, red for fail) based on configured temperature thresholds.

Figure 2: The FLIR T540-EST camera set up with an external monitor, displaying a thermal image of a person during a screening process.

Figure 3: A detailed view of the FLIR T540-EST's integrated screen, showing real-time thermal data and a highlighted area for temperature assessment.



Figure 4: An example of a thermal screening station, demonstrating the FLIR T540-EST in a practical application with a subject awaiting screening.

4. Maintenance

Proper maintenance ensures the longevity and accuracy of your FLIR T540-EST:

- **Cleaning the Lens:** Use a soft, lint-free cloth specifically designed for optical lenses. Gently wipe the lens surface to remove dust or smudges. Avoid abrasive materials or harsh chemicals.
- **Cleaning the Screen and Body:** Use a soft, damp cloth with a mild cleaning solution (if necessary) to clean the touchscreen and camera body. Do not spray liquids directly onto the camera.
- **Battery Care:** Always use the FLIR-approved charger. Do not expose batteries to extreme temperatures. If storing the camera for an extended period, ensure batteries are partially charged (around 50%) and remove them from the device.
- **Storage:** Store the camera in its protective case in a cool, dry environment, away from direct sunlight and extreme temperatures.

5. Troubleshooting

Refer to this section for common issues and their solutions:

Problem	Possible Cause	Solution
Camera does not power on	Low or depleted battery; improperly installed battery	Charge batteries fully; ensure batteries are correctly inserted.
Inaccurate temperature readings	Incorrect focus; improper screening distance; environmental factors	Use autofocus; maintain recommended screening distance; ensure stable ambient conditions.
Display is blank or frozen	Software glitch; low battery	Restart the camera; charge batteries. If issue persists, contact support.
Laser autofocus not working	Obstruction; dirty lens	Ensure clear path to subject; clean the lens.

If you encounter issues not listed here or if solutions do not resolve the problem, please contact FLIR customer support.

6. Specifications

Key technical specifications for the FLIR T540-EST camera:

- **Manufacturer:** FLIR Systems, Inc
- **Part Number:** 79302-0302
- **Item Model Number:** T540-EST-24
- **Detector Resolution:** 464 x 348 pixels
- **Lens:** 24-Degree
- **Temperature Measurement Range:** 15°C to 45°C (59°F to 113°F)
- **Product Dimensions:** 9.1 x 9.1 x 9.1 inches
- **Item Weight:** 1 pound
- **Batteries:** 2 Lithium Ion batteries (included)
- **Battery Cell Type:** Lithium Ion

7. Warranty and Support

For detailed warranty information, please refer to the documentation included with your product or visit the official FLIR Systems, Inc. website. For technical support, service, or additional inquiries, please contact FLIR customer service through their official channels.

Related Documents - T540-EST

	FLIR T5xx Series User Manual - Comprehensive Guide Explore the FLIR T5xx Series User Manual for detailed instructions, safety information, and operational guidance on FLIR's advanced thermal imaging cameras. Learn about features, settings, and maintenance.
	FLIR E60 Accessory Kit: Comprehensive List of Thermal Camera Accessories Detailed list of accessories for the FLIR E60 thermal imaging camera, including cases, cables, power supplies, chargers, batteries, memory cards, and documentation from Advanced Test Equipment Corp.
	FLIR ONE Edge Series User Manual Comprehensive user manual for the FLIR ONE Edge series, detailing setup, operation, safety guidelines, and troubleshooting for the mobile thermal camera accessory.
	FLIR ONE Pro User Guide: Thermal Imaging Camera for Smartphones Comprehensive user guide for the FLIR ONE Pro, a thermal imaging camera attachment for Android and iOS devices. Learn about charging, app features, image capture, color palettes, IR scale, gain mode, MSX technology, and more.
	FLIR Kx Series User's Manual Explore the FLIR Kx series thermal imaging cameras with this official user manual. Get detailed insights into operation, safety protocols, technical specifications, and maintenance for the FLIR Kx and K2 models. Ideal for professionals in demanding environments, especially firefighting.



[FLIR ONE Edge Series User Manual]

User manual for the FLIR ONE Edge series thermal camera, covering setup, operation, app usage, safety, and disposal. Includes quick start guide and technical information.

Documents - FLIR – T540-EST

[pdf] Datasheet

ITM Datasheet Template datasheet FLIR T540 EST 42 Thermal Camera with 42° lens 464 x 348 t540 est calcert s cache |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:33 filesize: 286.76 K page_count: 2 document date: 2022-03-29

[pdf] Datasheet

FLIR T5xx EST™ SERIES t540 est 24 datasheet itm s cache

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:32 filesize: 203.63 K page_count: 2 document date: 0000-00-00

[pdf]

DESCARGAR FICHA TÉCNICA FLIR T540 EST Colvin y Cia Ltda— Ltda v 1599677328 cdn shopify s files 1 0255 7509 6354 |||

SOLUCIONES DE DETECCIN TRMICA FLIR ESTTM DE MANO SERIE FLIR T5xx-ESTTM Las cmaras trmicas de mano FLIR **T540-EST**TM y T560-ESTTM son herramientas de deteccin sin contacto que sirven como primera lnea de defensa frente a posibles riesgos para la salud. Estas soluciones de deteccin trmica FLIR ESTTM det...

lang:es score:29 filesize: 560.15 K page_count: 2 document date: 2020-09-04

[pdf] User Manual

Why Go Handheld for Skin Temperature Screening TESTOON As businesses and venues begin to reopen FLIR handheld thermal cameras can be a first Continuous LDM One shot contrast Manual FICHIER LIE A 68394 testoon Fichier line of defense against potential health risks |||

Why Go Handheld for S kin Temperature Screening Mobile, quick to set up, and ready to go in minutes ... d and control Display Power External power Size L W H Weight Tripod mounting E54-EST E86-EST **T540-EST** T560-EST 320 240 pixels 464 348 pixels 464 348 pixels 640 480 pixels 40 mK 30C...

lang:en score:25 filesize: 1.08 M page_count: 2 document date: 2020-07-09

[pdf] User Manual Datasheet

HANDHELD FLIR EST TM THERMAL SCREENING SOLUTIONS T5xx contrast manual Screening mode Temperature range 15°C to 45°C 59°F 113°F accuracy drift ±0 3°C 5°F Image presentation Video out DisplayPort over USB Type C Digital data streaming Simultaneous thermal and visible Command control On camera screen Display 4 in touchscreen LCD 640 × 480 T540 T560 Datasheet mouser cn Docs

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:24 filesize: 555.27 K page_count: 2 document date: 2020-08-12

[pdf] User Manual Datasheet

HANDHELD FLIR EST TM THERMAL SCREENING SOLUTIONS T5xx EST™ SERIES NetX contrast manual Screening mode Temperature range 15°C to 45°C 59°F 113°F accuracy drift ±0 3°C 5°F Image presentation Video out DisplayPort over USB Type C Digital data streaming Simultaneous thermal and visible Command control On camera screen Display 4 in touchscreen LCD 640 × 480 Operate cable free with up hours of battery T540 ESTTM T560 handheld cameras are datasheet Series Datasheet US flir series t5xx est original instrumart assets netx net file asset 30443 attachment grupoacre es sites 3 2020 07

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:23 filesize: 567.38 K page_count: 2 document date: 2020-07-13

[pdf] Datasheet

FLIR T5xx EST Series T560 42 Flir Thermal Imager New valuetronics media vti datasheets |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ... lang:en score:22 filesize: 567.61 K page_count: 2 document date: 2020-06-29

[pdf] Datasheet

FLIR T5xx EST™ SERIESv1mme ae 2022 05 EST Series Datasheet US srsltid AfmBOooCyvYe7jZrCvIuE5NfJctBFgOX FMKWOsHJ2WZ2POmqHHIQEYa SERIESFLIR SERIESv1T5xx USmme FMKWOsHJ2WZ2POmqHHIQEYamme AfmBOorqc8y7PIZqUguq6w0kw sK3P0xwtadrWUcie4s8JyZY1 R Tgq ||| ||| HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR T540-ESTTM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ... lang:en score:22 filesize: 567.38 K page_count: 2 document date: 2020-07-13



[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide T199601 Hand strap and neck Downloads TOPA en US A4 DsDownload Assets |||

Hand strap and neck strap P/N: T199601 Copyright 2020, FLIR Systems, Inc. All rights reserved worl ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4... lang:en score:22 filesize: 91.56 K page_count: 2 document date: 2020-06-30

FLIR Pouch

P/N: T198495

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T198495 Pouch Downloads TOPA en US A4 DsDownload Assets |||

Pouch P/N: T198495 Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Names and mar ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:22 filesize: 71.89 K page_count: 2 document date: 2021-09-09

FLIR Battery charger

P/N: T199610

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199610 Battery charger Downloads TOPA en US A4 DsDownload Assets |||

Battery charger P/N: T199610 Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Nam ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:22 filesize: 506.44 K page_count: 3 document date: 2021-09-09

FLIR T5xx-EST™ SERIES

[pdf] Datasheet

Flir T560 EST Thermal Camera for Screening Elevated Skin Temperature ValueTesters flir t540 t560 est data sheet valuetesters assets images VT |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:22 filesize: 786.92 K page_count: 2 document date: 2020-08-07

FLIR

IR lens, f=10 mm (42°) with case

P/N: T199590

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199590 Specification assets testequity te1 Documents |||

IR lens, f=10 mm 42 with case P/N: T199590 Copyright 2021, FLIR Systems, Inc. All rights reserve ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:22 filesize: 172.78 K page_count: 4 document date: 2021-04-01

FLIR

Hard transport case

P/N: T199347ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199347ACC Hard transport case Downloads TOPA en US A4 DsDownload Assets |||

Hard transport case P/N: T199347ACC Copyright 2021, FLIR Systems, Inc. All rights reserved worldwi ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:22 filesize: 84.46 K page_count: 2 document date: 2021-09-09



FLIR

Calibration target

P/N: T130337ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T130337ACC Calibration target Downloads TOPA en US A4 DsDownload Assets |||

Calibration target P/N: T130337ACC Copyright 2021, FLIR Systems, Inc. All rights reserved worldwid ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:22 filesize: 96.79 K page_count: 3 document date: 2021-09-09



FLIR Screen-EST, Perpetual license

P/N: T300342

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T300342 Screen EST Perpetual license Software TOPA en US A4 DsDownload Assets |||

FLIR Screen-EST, Perpetual license P/N: T300342 Copyright 2022, FLIR Systems, Inc. All rights rese ... 101; FLIR A700-EST 42 90601-0101; FLIR A500-EST 24 90602-0101; FLIR A500-EST 42 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4... lang:en score:22 filesize: 46.85 K page_count: 2 document date: 2022-06-29



Option, No radio

P/N: T300030

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T300030 Option No radio Downloads TOPA en US A4 DsDownload Assets |||

Option, No radio P/N: T300030 Copyright 2022, FLIR Systems, Inc. All rights reserved worldwide. Na ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4... lang:en score:22 filesize: 39.11 K page_count: 2 document date: 2022-06-02

Car adapter 12V

P/N: T911706ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T911706ACC Car adapter 12 V Downloads TOPA en US A4 DsDownload Assets |||

Car adapter 12V P/N: T911706ACC Copyright 2022, FLIR Systems, Inc. All rights reserved worldwide. ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4... lang:en score:21 filesize: 59.06 K page_count: 3 document date: 2022-06-02

FLIR

Hand strap and neck strap

P/N: T199601

Copyright
© 2020, FLIR Systems, Inc.
All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity
Part No.: T199601
Current: 80010
Language: en-US
Modified: 20-06-30
Formatted: 2020-06-30

Website
http://www.flir.com

Customer support
http://support.flir.com

Disclaimer
Specifications subject to change without further notice. Camera models and accessories subject to region & market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description	
Hand strap and tool clip to carry the camera.	
Physical data	
Material	Webbing, Polyester; Leather
Color	Black
Shipping information	
Pack aging type	Carton and box
List of contents	• Hand strap • Neck strap
Pack aging, weight	
Pack aging, size	150 × 90 × 50 mm (5.1 × 2.3 × 2.7 in.)
EAN-13	4742560072988
UPC-12	845188074402
Country of origin	Vietnam

Compatible with the following products:
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79303-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°
- 79305-0201; FLIR T540 24° + 42°
- 79303-0201; FLIR T540 42°
- 79307-0201; FLIR T540 42° + 14°
- 89001-0101; FLIR T560 14°
- 89002-0101; FLIR T560 24°
- 89004-0101; FLIR T560 24° + 14°

1 (2)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide Hand strap and neck RS OnlineHand General description to carry the camera Physical data Material Webbing Polyester A700000007108957docs rs online 6767 A700000007108957 |||

Hand strap and neck strap P/N: T199601 Copyright 2020, FLIR Systems, Inc. All rights reserved worl ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 91.56 K page_count: 2 document date: 2020-06-30

FLIR

Power supply for battery charger

P/N: T911633ACC

Copyright
© 2022, FLIR Systems, Inc.
All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity
Part No.: T911633ACC
Current: 80010
Language: en
Modified: 20-06-30
Formatted: 2022-06-02

Website
http://www.flir.com

Customer support
http://support.flir.com

Disclaimer
Specifications subject to change without further notice. Camera models and accessories subject to region & market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description	
Power supply, with multi plugs	
Power system	
AC operation	100-240 VAC, 50/60 Hz, 12 VDC out
Power	30.00 mA at 12 VDC
Physical data	
Size (L x W x H)	90 × 54 × 38 mm (3.5 × 2.1 × 1.5 in.)
Cable length	1.2 m (3.9 ft.)
Shipping information	
Pack aging type	Carton and box
List of contents	• Power supply including cable • EU plug • UK plug • US plug • AU plug
Pack aging, weight	200 g (0.44 lb.)
Pack aging, size	150 × 70 × 70 mm (5.9 × 2.8 × 2.8 in.)
EAN-13	4742560021194
UPC-12	845188014188
Country of origin	China

Compatible with the following products:
- 85201-0102; FLIR GF77 LR 25°
- 85203-0102; FLIR GF77 HR 25°
- 85203-0102; FLIR GF77 LR 25° + HR 25°
- 85204-0102; FLIR GF77 LR 25° + LR 6°
- 85205-0102; FLIR GF77 HR 25° +HR 6°
- 85206-0102; FLIR GF77 LR 25° + HR 25° +HR 6°
- 85207-0102; FLIR GF77 LR 25° + HR 25° +LR 6°
- 85208-0102; FLIR GF77 LR 25° + HR 25° +LR 6° +HR 6°
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°

1 (3)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T911633ACC Power supply for battery charger Downloads TOPA en US A4 DsDownload Assets |||

Power supply for battery charger P/N: T911633ACC Copyright 2022, FLIR Systems, Inc. All rights res ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 90.55 K page_count: 3 document date: 2022-06-02

FLIR

IR lens, f=10 mm (42°) with case

P/N: T199590

Copyright
© 2021, FLIR Systems, Inc.
All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity
Part No.: T199590
Current: 70244
Language: en
Modified: 2021-01-27
Formatted: 2021-09-09

Website
http://www.flir.com

Customer support
http://support.flir.com

Disclaimer
Specifications subject to change without further notice. Camera models and accessories subject to region & market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

Imaging and optical data	
Field of view (FOV)	42° × 33°
Minimum focus distance	0.17 m (0.6 ft.)
Minimum focus distance with MXX	0.65 m (2.1 ft.)
Focal length	10 mm (0.39 in.)
Spatial resolution (IFOV)	Depends on the IR resolution of the camera: • 320 × 240 pixels: 2.41 mrad/pixel • 384 × 288 pixels: 1.81 mrad/pixel • 640 × 480 pixels: 1.20 mrad/pixel
Lens identification	Yes, AutoCal
F number	1.1
Measurement	
Accuracy	±2°C (±3.6°F) or ±2% of reading, for ambient temperature 15–25°C (59–77°F) and object temperature above 0°C (32°F).
Physical data	
Weight	0.140 kg (0.31 lb.)
Size (L x D)	45 x 72 mm (1.79 x 2.83 in.)
Shipping information	
Pack aging type	Carton and box
List of contents	• Lens • Lens case
Pack aging, weight	0.4 10 kg (0.90 lb.)
Pack aging, size	151 x 125 x 125 mm (5.9 x 4.9 x 4.9 in.)
EAN-13	4742560037119
UPC-12	845188074313
Country of origin	Sweden and/or Estonia

Compatible with the following products:
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°

1 (4)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199590 Lens 42° case Downloads TOPA en US A4 DsDownload Assets |||

IR lens, f=10 mm 42 with case P/N: T199590 Copyright 2021, FLIR Systems, Inc. All rights reserve ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 172.94 K page_count: 4 document date: 2021-09-09

IR lens, f=17 mm (24°) with case

P/N: T199589

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199589 Lens 24° case Downloads TOPA en US A4 DsDownload Assets |||

IR lens, f=17 mm 24 with case P/N: T199589 Copyright 2021, FLIR Systems, Inc. All rights reserve ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 173.34 K page_count: 4 document date: 2021-09-09

Power supply for battery charger

P/N: T911633ACC

[pdf] Specifications Datasheet Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide Datasheet T911633ACCT911633ACC Adaptateur de charge pour caméra thermique EXX GF7x T5xx T8xx RSA700000007099897docs rs online 499c A700000007099897 |||

Power supply for battery charger P/N: T911633ACC Copyright 2020, FLIR Systems, Inc. All rights res ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 89.5 K page_count: 2 document date: 2020-06-30



Power supply, 15 W/3 A

P/N: T911630ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T911630ACC Power supply for camera 15 W 3 A Downloads TOPA en US A4 DsDownload Assets |||

Power supply, 15 W/3 A P/N: T911630ACC Copyright 2022, FLIR Systems, Inc. All rights reserved worl ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 66.63 K page_count: 3 document date: 2022-06-02



FLIR

USB 2.0 A to USB Type-C cable

P/N: T911631ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T911631ACC Commercial Sys РКС Компоненти РАДІОМАГv1static6 arrow aro conversion fda065308ea3f2f8a5047cb7423c5c6968149989 t911631acc en us a4 |||

USB 2.0 A to USB Type-C cable P/N: T911631ACC Copyright 2021, FLIR Systems, Inc. All rights reserv ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 60.27 K page_count: 3 document date: 2024-02-20

FLIR

Car adapter 12V

P/N: T911706ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide Car adapter 12V T911706ACC Specification res cloudinary iwh image upload q auto g center assets 1 26 |||

Car adapter 12V P/N: T911706ACC Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 58.12 K page_count: 2 document date: 2021-04-01

FLIR

Battery charger

P/N: T199610

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide Battery charger Oct 2 2019 · 89001 0101 T560 14° 89002 24° 89004 89006 42° P N A700000007099893 docs rs online 4867 |||

Battery charger P/N: T199610 Copyright 2020, FLIR Systems, Inc. All rights reserved worldwide. Nam ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 506.38 K page_count: 3 document date: 2020-06-30

FLIR

Pouch

P/N: T198495

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T198495 SpecificationTeledyne Pouch Case with Shoulder Strap for T5xx T6xx and T840 Series Nylon Black Techni ToolFLIR Specificationassets testequity te1 Documents Specification |||

Pouch P/N: T198495 Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Names and mar ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 71.76 K page_count: 2 document date: 2021-04-01



FLIR

USB 2.0 A to USB Type-C cable

P/N: T911631ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T911631ACC USB 2 0 A to Type C cable 9 m Downloads TOPA en US A4 DsDownload Assets |||

USB 2.0 A to USB Type-C cable P/N: T911631ACC Copyright 2021, FLIR Systems, Inc. All rights reserv ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 55.44 K page_count: 3 document date: 2021-09-09

FLIR

Remote operation button

P/N: T131171ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T131171ACC en US A4 Bluetooth Fernbedienung für Exx T5xx T8xx TOPA DsDownload Assets |||

Remote operation button P/N: T131171ACC Copyright 2022, FLIR Systems, Inc. All rights reserved wor ... IR T540 42 79307-0201; FLIR T540 42 14 79308-0201; FLIR T540 Dual FOV 14 24 79302-0302; FLIR **T540-EST** 24 1 4 www.flir.com P/N: T131171ACC 2022, FLIR Systems, Inc. #T131171ACC; r. 75780; ...

lang:en score:21 filesize: 171.21 K page_count: 4 document date: 2022-06-22

FLIR

Pouch

P/N: T198495

Copyright

©2021, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Pub. No.: T198495
Current: 80004
Language: en-US
Modified: 2019-10-02
Formatted: 2021-09-09

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description

Pouch, with shoulder strap (to carry and protect the camera, made in durable nylon. The pouch can be used together with the tool belt.

Physical data	
Weight	0.27 kg (9.49 lb.) excluding shoulder strap
Size (L x W x H)	200 x 110 x 180 mm (7.9 x 4.3 x 7.0 in.), excluding shoulder strap
Color	black

Shipping information	
Pack aging, type	Cardboard box
List of contents	• Pouch • Strap
Pack aging, weight	0.425 kg (1.38 lb.)
Pack aging, size	350 x 206 x 128 mm (13.8 x 8.1 x 5.0 in.)
EAN-13	7332558004500
UPC-12	845188004477
Country of origin	Malaysia

Compatible with the following products:

- 85201-0102: FLIR GF77 LR 25°
- 85202-0102: FLIR GF77 HR 25°
- 85203-0102: FLIR GF77 LR 25° + HR 25°
- 85204-0102: FLIR GF77 LR 25° + LR 6°
- 85205-0102: FLIR GF77 HR 25° +HR 6°
- 85206-0102: FLIR GF77 LR 25° + HR 25° +HR 6°
- 85207-0102: FLIR GF77 LR 25° + HR 25° +LR 6°
- 85208-0102: FLIR GF77 LR 25° + HR 25° +LR 6° + HR 6°
- 79301-0101: FLIR T530 14°
- 79302-0101: FLIR T530 24°
- 79304-0101: FLIR T530 24° + 14°
- 79306-0101: FLIR T530 24° + 14° & 42°
- 79305-0101: FLIR T530 24° + 42°
- 79303-0101: FLIR T530 42°
- 79307-0101: FLIR T530 42° + 14°
- 79301-0201: FLIR T540 14°
- 79302-0201: FLIR T540 24°
- 79304-0201: FLIR T540 24° + 14°
- 79306-0201: FLIR T540 24° + 14° & 42°

1 (2)

www.flir.com

[pdf] Specifications Datasheet Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T198495 DatasheetTeledyne Pouch Case with Shoulder Strap for T5xx T6xx and T840 Series Nylon Black Techni Toolflir t198495 datasheetassets testequity te1 Documents datasheet |||

Pouch P/N: T198495 Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Names and mar ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 71.89 K page_count: 2 document date: 2021-09-09

FLIR

Battery charger

P/N: T199610

Copyright

©2021, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Pub. No.: T199610
Current: 80002
Language: en-US
Modified: 2019-10-02
Formatted: 2021-04-01

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description

Stand alone two bay battery charger (P/N T199443) including power supply (P/N T911633).

Power system	
Power	12 VDC input

Physical data	
Weight	0.704 kg (1.55 lb)
Size (L x W x H)	146 x 74 x 96 mm (5.7 x 2.9 x 3.8 in.)

Shipping information	
Pack aging, type	Cardboard box
List of contents	• Stand alone two bay battery charger (P/N T199443) • Power supply for battery charger (P/N T911633)
Pack aging, weight	0.848 kg (1.87 lb)
Pack aging, size	243 x 165 x 82 mm (9.57 x 6.50 x 3.23 in.)
EAN-13	4742583001261
UPC-12	845188014780
Country of origin	China

Compatible with the following products:

- 85201-0102: FLIR GF77 LR 25°
- 85202-0102: FLIR GF77 HR 25°
- 85203-0102: FLIR GF77 LR 25° + HR 25°
- 85204-0102: FLIR GF77 LR 25° + LR 6°
- 85205-0102: FLIR GF77 HR 25° +HR 6°
- 85206-0102: FLIR GF77 LR 25° + HR 25° +HR 6°
- 85207-0102: FLIR GF77 LR 25° + HR 25° +LR 6°
- 85208-0102: FLIR GF77 LR 25° + HR 25° +LR 6° + HR 6°
- 79301-0101: FLIR T530 14°
- 79302-0101: FLIR T530 24°
- 79304-0101: FLIR T530 24° + 14°
- 79306-0101: FLIR T530 24° + 14° & 42°
- 79305-0101: FLIR T530 24° + 42°
- 79303-0101: FLIR T530 42°
- 79307-0101: FLIR T530 42° + 14°
- 79301-0201: FLIR T540 14°
- 79302-0201: FLIR T540 24°
- 79304-0201: FLIR T540 24° + 14°
- 79306-0201: FLIR T540 24° + 14° & 42°

1 (3)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide Battery charger TestEquity Compatible with the following products 85201 0102 GF77 LR 25° 85202 HR 85203 T199610 Specification assets testequity te1 Documents |||

Battery charger P/N: T199610 Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Nam ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 506.31 K page_count: 3 document date: 2021-04-01

FLIR

Power supply for battery charger

P/N: T911633ACC

Copyright

©2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Pub. No.: T911633ACC
Current: 80016
Language: en-US
Modified: 2019-10-02
Formatted: 2023-04-04

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description

Power supply with multi plugs.

Power system	
AC operation	100-240 VAC, 50/60 Hz, 12 VDC out
Power	30.00 max. at 12 VDC

Physical data	
Size (L x W x H)	90 x 54 x 38 mm (3.5 x 2.1 x 1.5 in.)
Cable length	1.2 m (3.9 ft.)

Shipping information	
Pack aging, type	Cardboard box
List of contents	• Power supply including cable • EU plug • UK plug • US plug • AU plug
Pack aging, weight	0.60 kg (0.42 lb.)
Pack aging, size	150 x 70 x 70 mm (5.9 x 2.8 x 2.8 in.)
EAN-13	4742583001194
UPC-12	845188014899
Country of origin	China

Compatible with the following products:

- 10101-0101: FLIR G304 14.5°
- 10101-0102: FLIR G304 24°
- 10201-0101: FLIR G306 14.5°
- 10201-0102: FLIR G306 24°
- 10301-0102: FLIR G615 25°
- 10401-0101: FLIR Gx320 14.5°
- 10401-0102: FLIR Gx320 24°
- 10501-0101: FLIR G620 14.5°
- 10501-0102: FLIR G620 24°
- 10601-0101: FLIR Gx620 14.5°
- 10601-0102: FLIR Gx620 24°
- 10701-0101: FLIR G635 14.5°
- 10701-0102: FLIR G635 24°
- 10801-0101: FLIR G343 14.5°
- 10801-0102: FLIR G343 24°
- 10901-0101: FLIR G346 14.5°
- 10901-0102: FLIR G346 24°

1 (3)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2023 FLIR Systems Inc All rights reserved worldwide Teledyne LLC Spannungsversorgungen Arrow de t911633acc en us a4 static6 arrow aro conversion 526b759b6fc3ea5d3f33e11746d3787862d88bb5 |||

Power supply for battery charger P/N: T911633ACC Copyright 2023, FLIR Systems, Inc. All rights res ... IR T540 42 79307-0201; FLIR T540 42 14 79308-0201; FLIR T540 Dual FOV 14 24 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89001-0101; FLIR T560 14 89002-0101; FLIR T560 24 89004...

lang:en score:21 filesize: 95.95 K page_count: 3 document date: 2023-11-28

Power supply for battery charger

P/N: T911633ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide Cut Sheet Teledyne T911633ACC Power Supply for Battery Charger PLATT ELECTRIC SUPPLY t911633acc i 9979A10F 3E58 445B B36B E5F38CE338CC rexel cdn products |||

Power supply for battery charger P/N: T911633ACC Copyright 2020, FLIR Systems, Inc. All rights res ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 89.5 K page_count: 2 document date: 2020-06-30



USB Type-C to USB Type-C cable (USB 2.0 standard)

P/N: T911705ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2022 FLIR Systems Inc All rights reserved worldwide T911705ACC USB Type C to cable 2 0 standard 1 m Downloads TOPA en US A4 DsDownload Assets |||

USB Type-C to USB Type-C cable USB 2.0 standard P/N: T911705ACC Copyright 2022, FLIR Systems, In ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 54.88 K page_count: 3 document date: 2022-06-02

IR lens, f=10 mm (42°) with case

P/N: T199590

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2023 FLIR Systems Inc All rights reserved worldwide Specification Sheet Teledyne T199590 42° Lens With Case Graybar Store gcewigwrgvsje8zhoniw images salsify image upload s gvBjCpXT |||

IR lens, f=10 mm 42 with case P/N: T199590 Copyright 2023, FLIR Systems, Inc. All rights reserve ... IR T540 42 79307-0201; FLIR T540 42 14 79308-0201; FLIR T540 Dual FOV 14 24 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89001-0101; FLIR T560 14 89002-0101; FLIR T560 24 89004...

lang:en score:21 filesize: 173.04 K page_count: 4 document date: 2023-04-14

FLIR

USB Type-C to HDMI and PD adapter

P/N: T911845ACC

[pdf] Specifications Datasheet Accessories Borchure

Corporate website flir Support support — Training infraredtraining Copyright 2020 FLIR Systems Inc All rights reserved worldwide USB Type C to HDMI and PD adapter P N T911845ACC 4743254003941 Elma PN911845ACC datasheet EN elma instruments se Admin Public DWSDownload aspx File FIles Files Documents ecom Brochures |||

USB Type-C to HDMI and PD adapter P/N: T911845ACC Copyright 2020, FLIR Systems, Inc. All rights re ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 1 2 www.flir.com USB Type-C to HDMI and PD adapter ...

lang:en score:21 filesize: 81.59 K page_count: 2 document date: 2020-06-30

FLIR

USB 2.0 A to USB Type-C with Power supply

P/N: T911846ACC

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide USB 2 0 A to Type C with Power supply P N T911846ACC Specification res cloudinary iwh image upload q auto g center assets 1 26

USB 2.0 A to USB Type-C with Power supply P/N: T911846ACC Copyright 2021, FLIR Systems, Inc. All r ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 85.34 K page_count: 2 document date: 2021-04-01

FLIR

Remote operation button

P/N: T131171ACC

[pdf] Specifications Datasheet Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide Remote operation button TestEquity 78511 1301 E86 14° 78512 24° 78514 78516 42° 78515 Teledyne T131171ACC Datasheet 0125 assets testequity te1 Documents |||

Remote operation button P/N: T131171ACC Copyright 2021, FLIR Systems, Inc. All rights reserved wor ... 171ACC; r. 68279; en-US 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 168.86 K page_count: 3 document date: 2021-04-01

[pdf] Datasheet

T5xx EST Series Datasheet A4 flir netx net file asset 30751 original attachment

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:21 filesize: 555.45 K page_count: 2 document date: 2020-07-13

[pdf] User Manual Datasheet

T5xx EST Series Datasheet DE flir netx net file asset 32284 original attachment

MOBILE FLIR ESTTM WRMEBILDSCREENING-LSUNGEN FLIR T5xx-ESTTM SERIE Die mobilen Wrmebildkameras **T540-EST**TM und T560-ESTTM sind berhrungslose Screening-Instrumente, die sich fr die Erstberprfung auf potenzielle Gesundheitsrisiken eignen. Die FLIR ESTTM Wrmebild-Screening-Lsungen erkennen Wrme und mache...

lang:de score:21 filesize: 159.06 K page_count: 2 document date: 2020-09-04

[pdf]

FLIR T5xx EST™ SERIES DS T540 T560 EST eng scv sa ch 2020 07 |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:21 filesize: 542.31 K page_count: 2 document date: 2020-07-22

[pdf] Datasheet

datasheet FLIR T560 EST 24 Handheld Thermal Camera with 24° lens 640 x 480 t560 est globaltestsupply s cache |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:21 filesize: 192.99 K page_count: 2 document date: 0000-00-00

[pdf] Datasheet

ITM Datasheet Template FLIR T5xx EST™ SERIESt560 est 42 datasheetitm s cache itm t560 datasheet srsltid AfmBOooLiKvxiMBl2eKMG8ibvFHv1EQRpIgvCzndgD2EUwKmEk2WxYIK |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:21 filesize: 279.61 K page_count: 2 document date: 2015-03-23

[pdf] Specifications Accessories

Cut Sheet Teledyne FLIR T199610 Stand Alone Two Bay Battery Charger PLATT ELECTRIC SUPPLY t199610 i 9ECF4881 1DD3 42F9 978B 0B9F9B51F055 rexel cdn products |||

Battery charger P/N: T199610 Copyright 2020, FLIR Systems, Inc. All rights reserved worldwide. Nam ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:21 filesize: 76.32 K page_count: 2 document date: 2022-08-16

[pdf] Datasheet

T5xx EST Series Datasheet SCN flir netx net file asset 31737 original attachment

FLIR ESTTM FLIR T5xx-ESTTM FLIR **T540-EST**TMT560-ESTTM F L I R EST TM T 5 4 0 - E S T T 5 6 0 - E S T Screen-EST / FLIR Screen-ESTTM COVID-19SARS F L I R F D A www.flir.cn/T5xx-EST-Series 4 FLIR Screen-EST FLIR Screen-EST/ F...

lang:i-klingon score:20 filesize: 664.85 K page_count: 2 document date: 2020-08-14

[pdf] Datasheet

ITM Datasheet Template datasheet FLIR T560 EST 24 Handheld Thermal Camera with 24° lens 640 x 480 t560 est itm s cache |||

HANDHELD FLIR ESTTM THERMAL SCREENING SOLUTIONS FLIR T5xx-ESTTM SERIES FLIR **T540-EST**TM and T560-ESTTM handheld thermal cameras are non-contact screening tools that serve as a first line of defense against potential health risks. These FLIR ESTTM thermal screening solutions detect and visualize heat ...

lang:en score:20 filesize: 279.61 K page_count: 2 document date: 2015-03-23

[pdf] User Manual Datasheet

detect and visualize FLIR T560 manual flir t560 Touchboard T540 EST handheld thermal cameras are non contact screening tools that serve as a first line of defense against potential health risks These solutions est datasheet testequipmentdepot |||

...

lang:en score:20 filesize: 514.92 K page_count: 2 document date: 0000-00-00

FLIR

SKIN TEMPERATURE SCREENING SOFTWARE

FLIR Screen-EST™

FLIR Screen-EST desktop software offers an efficient, accurate way to perform elevated skin temperature screenings at points of entry, checkpoints, building entrances, and other high-traffic areas. When connected to a FLIR E-series camera, the software activates as an individual enters the camera's field of view and provides guidance to correctly position them. The software identifies the area for evaluation and takes a skin temperature measurement within seconds. If the measured temperature exceeds a threshold set above the rolling baseline average, Screen-EST will notify the operator and present an alarm on the subject's viewing monitor. The individual can then be directed to a secondary screening with a medical device. This rapid, non-contact measurement system sets up in minutes, and helps organizations reduce the risk of work and production interruptions due to illness.

www.flir.com/Screen-EST

TURNKEY SCREENING SOLUTION

Pair with compatible FLIR thermal cameras for a complete, rapid-deployment system

- Streamline your screening station setup with software you can just download and run
- Connects to FLIR E-, Exx-, or Axxx-Series EST cameras using a single USB-C cable
- Start screening immediately with simplified interface and workflow that require minimal training

INCREASED SPEED AND ACCURACY

Non-contact screening with efficient measurement tools allow for faster traffic through check points

- Ensure accurate measurements with face detection software that guides individuals into optimal position for the presenting thermal sensor
- Achieve high quality, uniform measurement of a hot spot within the measurement box
- Avoid errors due to natural skin fluctuation by comparing skin temperature measurements against a continuously updated rolling average

SIMPLE & COST EFFECTIVE TO USE

Take consistent measurements without the need for added calibration sources

- Simplify training with streamlined user interface that's focused on essential screening features
- Set up a screening station with just a few pieces of equipment—the camera, a tripod, and a computer
- Customize outward-facing screens to guide employees and customers quickly through the screening process

[pdf] Datasheet

Screen EST Datasheet US flir netx net file asset 29508 original attachment

SKIN TEMPERATURE SCREENING SOFTWARE FLIR Screen-ESTTM FLIR Screen-EST desktop software offers an eff ... and 64-bit RAM: minimum 2 GB, 3 GB is recommended Disk space: minimum 100 MB FLIR E54-EST, E86-EST, **T540-EST**, T560-EST, A500-EST, A700-EST *Not all models available at date of release FLIR cameras ar...

lang:en score:20 filesize: 944.91 K page_count: 2 document date: 2021-03-05

FLIR

Battery

P/N: T199300ACC

Copyright:
© 2021, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems, Inc. and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity:
Part No.: T199300ACC
Current: 01/06
Language: en-US
Modified: 20-09-10 04
Formatted: 2021-09-08

Website:
http://www.flir.com

Customer support:
http://support.flir.com

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Fine print and/or typographical errors are not ruled out.

General description	
High quality battery for the IR camera.	
Power system	
Battery type	Rechargeable Li-ion battery
Battery voltage	3.6 V
Battery operating time	4 hours at 25°C (68°F) with typical use
Charging time (using low-loss charger)	3.5 h to 90% capacity
Environmental data	
Physical data	
Weight	180 g (6.4 oz.)
Size (L × W × H)	90 × 55 × 34 mm (3.5 × 2.2 × 1.7 in.)
Shipping information	
Packaging type	Cardboard box
List of contents	• Battery
Packaging weight	
Packaging size	220 × 160 × 70 mm (8.7 × 6.3 × 2.8 in.)
EAN-13	4743254012376
UPC-12	845188014787
Country of origin	Romania

Compatible with the following products:

- 85201-0102; FLIR GF77 LR 25°
- 85203-0102; FLIR GF77 HR 25°
- 85203-0102; FLIR GF77 LR 25° + HR 25°
- 85204-0102; FLIR GF77 LR 25° + LR 6°
- 85205-0102; FLIR GF77 HR 25° +HR 6°
- 85206-0102; FLIR GF77 LR 25° + HR 25° +HR 6°
- 85207-0102; FLIR GF77 LR 25° + HR 25° +LR 6°
- 85208-0102; FLIR GF77 LR 25° + HR 25° +LR 6° +HR 6°
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°

1 (9)

www.flir.com

[pdf] Specifications Accessories

Corporate website flir Support support — Training infraredtraining Copyright 2021 FLIR Systems Inc All rights reserved worldwide T199300ACC Battery Downloads TOPA en US A4 DsDownload Assets ||| Battery P/N: T199300ACC Copyright 2021, FLIR Systems, Inc. All rights reserved worldwide. Names an ... -0101; FLIR T560 24 42 89003-0101; FLIR T560 42 89007-0101; FLIR T560 42 14 79302-0302; FLIR **T540-EST** 24 79303-0302; FLIR **T540-EST** 42 89002-0302; FLIR T560-EST 24 89003-0302; FLIR T560-EST 4...

lang:en score:20 filesize: 606.83 K page_count: 10 document date: 2021-09-09