

Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60

Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60 Kitchen Chimney User Manual

Model: Hood STILUX 3D PLUS MAX T2S2 BK TC 60

1. INTRODUCTION

Thank you for choosing the Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60 Kitchen Chimney. This manual provides essential information for the safe installation, operation, and maintenance of your new appliance. Please read these instructions thoroughly before using the chimney and retain them for future reference.

2. SAFETY INSTRUCTIONS

To ensure safe operation and prevent damage, observe the following safety precautions:

- Ensure the electrical supply matches the voltage specified on the rating label.
- This appliance is intended for domestic use only. Do not use it for commercial purposes.
- Always disconnect the power supply before cleaning or performing maintenance.
- Do not allow children to operate the chimney without supervision.
- Maintain adequate ventilation in the room when the chimney is in use, especially if other fuel-burning appliances are present.
- Do not flambé under the chimney.
- Regularly clean the baffle filters to prevent grease accumulation, which can be a fire hazard.

3. PRODUCT OVERVIEW

The Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60 is a 60 cm box-type kitchen chimney designed for efficient smoke and odor extraction. It features a premium black finish with curved glass and touch controls.

Key Features:

- **Suction Capacity:** 1350 m³/hr, suitable for kitchens larger than 200 sq ft and heavy frying/grilling.
- **Filter Type:** 2 Baffle Filters, designed for Indian kitchens, creating an impenetrable barrier for grease.
- **Control Type:** Intuitive Touch Control for easy operation.

- **Lighting:** 2 x 1.1 Watt LED lamps for illuminating the cooking area.
- **Noise Level:** Maximum 58 dB, ensuring a quieter kitchen environment.
- **Design:** Wall-mounted, box-type with a premium black finish and curved glass.

Product Components:



Figure 1: Overall view of the Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60 Kitchen Chimney.



Figure 2: Close-up view of the baffle filter, designed to capture grease effectively.



Figure 3: Illustration of the 3-way suction capability for enhanced smoke extraction.

4. INSTALLATION

The Faber Hood STILUX 3D PLUS MAX T2S2 BK TC 60 is a wall-mounted chimney. Professional installation is highly recommended to ensure proper functioning and safety.

Installation Steps (Overview):

1. **Site Preparation:** Ensure the wall is strong enough to support the chimney's weight (approximately 10 kg). The installation height above the cooking surface should be as per local regulations and manufacturer recommendations (typically 65-75 cm).
2. **Mounting:** Securely mount the chimney bracket to the wall using appropriate fasteners.
3. **Ducting:** Connect the exhaust pipe to the chimney outlet and route it to an external vent. Ensure the ducting is free from sharp bends to maintain optimal suction. This model supports ducted/vented ventilation.
4. **Electrical Connection:** Connect the chimney to a suitable power outlet. Ensure the connection is grounded.
5. **Final Checks:** Verify all connections are secure and the chimney is level.

For detailed installation instructions, please refer to the separate installation guide provided with the product or contact Faber customer service.

5. OPERATION

Your Faber chimney is equipped with a user-friendly touch control panel.



Figure 4: Touch control panel for operating the chimney functions.

Operating the Chimney:

- **Power On/Off:** Touch the power symbol to turn the chimney on or off.
- **Speed Selection:** The chimney offers 3 speed settings. Touch the speed control buttons to adjust the suction power according to your cooking needs. Use higher speeds for heavy frying or grilling.
- **Light Control:** Touch the light symbol to turn the LED lamps on or off, illuminating your cooking area.
- **Auto Clean (if applicable):** If your model includes an auto-clean function, refer to the specific instructions for its activation.

It is recommended to turn on the chimney a few minutes before you start cooking and let it run for a few minutes after you finish to ensure complete removal of smoke and odors.

6. MAINTENANCE AND CLEANING

Regular maintenance ensures optimal performance and extends the lifespan of your chimney.

Baffle Filter Cleaning:



Figure 5: Baffle filter, requiring regular cleaning.

- The baffle filters should be cleaned every 6 months, or more frequently depending on cooking habits.
- To remove, locate the release latches on the filters and gently pull them down.
- Clean the filters with warm water and a degreasing detergent. You can also use a dishwasher for cleaning.

- Ensure the filters are completely dry before re-installing them.

Exterior Cleaning:

- Wipe the exterior surfaces with a soft cloth dampened with mild soap and water.
- Do not use abrasive cleaners, scouring pads, or harsh chemicals, as these can damage the finish.
- For stainless steel parts, use a non-abrasive stainless steel cleaner.

7. TROUBLESHOOTING

If you encounter issues with your chimney, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Chimney does not turn on	No power supply; loose connection; faulty switch	Check power cord and circuit breaker; ensure connections are secure; contact service if switch is faulty.
Low suction power	Clogged filters; obstructed ducting; incorrect installation height	Clean baffle filters; check ducting for blockages; verify installation height.
Excessive noise	Loose parts; motor issue; improper installation	Check for loose screws or components; ensure proper installation; contact service for motor issues.
Lights not working	Faulty LED lamp; loose connection	Check connections; replace LED lamp if faulty (contact service).

If the problem persists after attempting these solutions, please contact Faber customer support.

8. SPECIFICATIONS

Feature	Specification
Model Number	Hood STILUX 3D PLUS MAX T2S2 BK TC 60
Brand	Faber
Colour	Black
Mounting Type	Wall Mount
Air Flow Capacity	1350 m³/hr
Filter Type	Baffle
Controls Type	Touch Control
Number Of Speeds	3
Noise Level	58 Decibels

Feature	Specification
Light Source	LED (2x1.1 watts)
Voltage	220 Volts
Material Type	Alloy Steel
Item Weight	10000 Grams
Included Components	1 Chimney, 1 User Manual

9. WARRANTY AND SUPPORT

Warranty Information:

- **Product Warranty:** 1 year on the product.
- **Motor Warranty:** 10 years on the motor.

The warranty covers manufacturing defects under normal use. Please retain your purchase receipt for warranty claims.

Customer Support:

For any queries, service requests, or technical assistance, please contact Faber customer support:

- **Manufacturer Contact:** 1800 209 3484
- **Importer Contact:** Faber
- **Official Website:** www.faberindia.com (Please check for the most current contact information on the official website)