

[Manuals.plus](#) /

> [Amerimax](#) /

> Amerimax 37084 2x3 Flex Elbow Installation and Maintenance Guide

## Amerimax 37084

# Amerimax 37084 2x3 Flex Elbow Instruction Manual

Model: 37084

## INTRODUCTION

---

This manual provides comprehensive instructions for the proper installation, function, maintenance, and troubleshooting of the Amerimax 37084 2x3 Flex Elbow. Please read this guide thoroughly before beginning any installation or maintenance procedures to ensure safe and effective use of the product.

## PRODUCT OVERVIEW

---

The Amerimax 37084 2x3 Flex Elbow is a versatile component designed for gutter downspout systems. Made from durable plastic, this flexible elbow allows for adjustable angles to effectively direct rainwater away from your home's foundation. Its 2x3 inch dimension ensures compatibility with standard downspout sizes, providing a secure and leak-resistant connection. This product is supplied as a three-pack, offering convenience for multiple downspout installations or replacements.



Image: A white Amerimax 2x3 Flex Elbow, showcasing its flexible design and standard dimensions. This image illustrates the product's appearance and general form.

## SAFETY INFORMATION

---

- Always wear appropriate personal protective equipment (PPE), including gloves and eye protection, when handling tools and materials.
- Exercise caution when working at heights, such as on ladders or roofs. Ensure ladders are stable and properly secured.
- Be aware of overhead power lines and other obstructions when positioning ladders or handling long downspout sections.
- Keep children and pets away from the work area during installation.

## PACKAGE CONTENTS

---

Verify that all components are present and undamaged before beginning installation.

- Three (3) Amerimax 37084 2x3 Flex Elbows (White, Plastic)

## SETUP AND INSTALLATION

---

The Amerimax 2x3 Flex Elbow is designed for straightforward installation into existing or new downspout systems. Ensure all connecting downspout sections are clean and free of debris.

### Tools and Materials Required:

- Tape Measure
- Tin Snips or Hacksaw (if cutting downspout sections)
- Drill with appropriate bit (for screws)
- Sheet Metal Screws or Rivets
- Gutter Sealant (optional, for enhanced leak prevention)
- Ladder (ensure stability)

### Installation Steps:

1. **Measure and Plan:** Determine the desired angle and length for your downspout extension. The flex elbow allows for adjustments, but pre-planning helps ensure optimal water diversion.
2. **Prepare Downspout Sections:** If necessary, cut the connecting downspout sections to the appropriate length using tin snips or a hacksaw. Ensure clean, burr-free edges.
3. **Connect to Upper Downspout:** Slide the wider end of the flex elbow over the end of the upper downspout section. Ensure a snug fit.
4. **Adjust Angle:** Flex the elbow to achieve the desired angle for water discharge. The flexible design allows for various configurations to direct water away from the foundation.
5. **Connect to Lower Downspout/Extension:** Slide the narrower end of the flex elbow into the next downspout section or an extension piece.
6. **Secure Connections:** Use sheet metal screws or rivets to secure the flex elbow to both the upper and lower downspout sections. Typically, two screws per connection point are sufficient. Pre-drilling pilot holes may be necessary.
7. **Apply Sealant (Optional):** For added leak protection, apply a bead of gutter sealant around the seams where the flex elbow connects to the downspout sections.

8. **Test System:** After installation, test the gutter system with water (e.g., from a hose or during rainfall) to ensure proper flow and check for any leaks.

## FUNCTION AND USAGE

---

The Amerimax 2x3 Flex Elbow serves a critical role in a functional gutter system by providing a flexible connection point that allows for directional changes in downspout runs. Its primary function is to:

- **Direct Water Flow:** Effectively guides rainwater from the downspout away from the building's foundation, preventing water damage, erosion, and basement flooding.
- **Accommodate Angles:** Its flexible design allows for easy adjustment to various angles, making it suitable for complex installations or when precise water direction is needed.
- **Connect Components:** Provides a secure and adaptable connection between different sections of a downspout system, including extensions or other elbows.

Once installed, the flex elbow operates passively, channeling water as designed. Regular checks ensure its continued effectiveness.

## MAINTENANCE

---

Regular maintenance ensures the longevity and optimal performance of your Amerimax 2x3 Flex Elbow and the entire gutter system.

- **Seasonal Inspection:** Inspect the flex elbow and surrounding downspout sections at least twice a year, typically in spring and fall, or after heavy storms.
- **Check for Clogs:** Ensure the elbow is free from leaves, twigs, and other debris that can accumulate and impede water flow. Clear any blockages promptly.
- **Examine for Damage:** Look for cracks, punctures, or signs of wear on the plastic material. While durable, extreme weather or physical impact can cause damage.
- **Verify Connections:** Confirm that the elbow remains securely attached to the downspout sections. Tighten or replace screws/rivets if connections appear loose.
- **Clean Exterior:** If desired, clean the exterior of the elbow with mild soap and water to maintain its appearance. Avoid abrasive cleaners.

## TROUBLESHOOTING

---

Address common issues with your Amerimax 2x3 Flex Elbow using the following guide:

Problem	Possible Cause	Solution
Water leaking from connections	Loose screws/rivets; insufficient sealant; damaged elbow.	Tighten or replace fasteners. Apply gutter sealant to seams. Inspect elbow for damage and replace if necessary.
Water not flowing freely through elbow	Clog (leaves, debris); improper angle.	Clear any debris from inside the elbow and downspout. Adjust the elbow's angle to ensure a clear, downward path for water.

Problem	Possible Cause	Solution
Elbow appears cracked or broken	Physical impact; extreme temperature fluctuations; material fatigue.	Replace the damaged flex elbow with a new one.

## SPECIFICATIONS

---

- **Model:** 37084
- **Size:** 2x3 inches (compatible with standard downspouts)
- **Material:** Plastic
- **Color:** White
- **Quantity:** Three (3) per pack
- **Manufacturer:** AMERIMAX HOME PRODUCTS
- **ASIN:** B08KQL9ZPS

## WARRANTY AND SUPPORT

---

For specific warranty information or technical support regarding your Amerimax 37084 2x3 Flex Elbow, please refer to the product packaging or contact Amerimax Home Products directly through their official website or customer service channels. Keep your proof of purchase for any warranty claims.