

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [Laurey](#) /
- › [Laurey Tribeca Modern Cabinet Hardware Pull User Manual](#)

Laurey 87803

Laurey Tribeca Modern Cabinet Hardware Pull User Manual

Model: 87803

PRODUCT OVERVIEW

The Laurey Tribeca Modern Cabinet Hardware Pull (Model 87803) is designed to enhance the aesthetic and functionality of your cabinets and drawers. Crafted from solid alloy steel with a satin nickel finish, this pull offers a sleek and clean design, providing a comfortable feel and a modern, timeless appeal. It is suitable for various applications including kitchen, bathroom, and furniture cabinets.



Image: Laurey Tribeca Modern Cabinet Hardware Pull, 7.5 inch center-to-center, in satin nickel finish.

SPECIFICATIONS

Brand	Laurey
Model Number	87803
Material	Alloy Steel, Metal
Finish	Satin Nickel (Brushed)
Center-to-Center Spacing	7.5 Inches (192mm)
Included Components	(1) Cabinet Hardware Pull, (2) 1 Inch Mounting Screws, (2) 1.5 Inch Mounting Screws
Item Weight	11.5 Ounces
Product Dimensions (Approx.)	5"L x 5"W (Note: This refers to package dimensions, actual pull length is approximately 7.5 inches center-to-center)
UPC	722233878033

SETUP AND INSTALLATION

This section provides instructions for the proper installation of your Laurey Tribeca Cabinet Hardware Pull. Ensure you have the necessary tools before beginning.

Tools Required:

- Drill with appropriate drill bit (typically 3/16" or 5mm for cabinet hardware screws)
- Measuring tape or ruler
- Pencil or marker
- Screwdriver (Phillips head recommended)
- Optional: Cabinet hardware jig for precise hole placement

Installation Steps:

1. **Measure and Mark:** Determine the desired location for your pull on the cabinet door or drawer. Using a measuring tape and pencil, mark two points that are 7.5 inches (192mm) apart, corresponding to the center-to-center spacing of the pull. Ensure these marks are level and centered as desired.
2. **Drill Pilot Holes:** Carefully drill pilot holes at the marked points. Use a drill bit slightly smaller than the screw diameter to prevent wood splitting. Drill straight through the cabinet material.
3. **Attach the Pull:** Align the pull with the drilled holes. Insert the included mounting screws (choose between 1-inch or 1.5-inch screws based on your cabinet thickness) from the inside of the cabinet door or drawer through the pilot holes and into the threaded posts of the pull.
4. **Tighten Screws:** Using a screwdriver, carefully tighten the screws until the pull is secure. Do not overtighten, as this can strip the threads or damage the cabinet material.
5. **Verify Alignment:** After installation, check that the pull is firmly attached and properly aligned.

Note: If your cabinet material is thicker than 1.5 inches, you may need to acquire longer mounting screws separately.

Always ensure the screws are appropriate for your specific cabinet thickness.

OPERATING INSTRUCTIONS

The Laurey Tribeca Cabinet Hardware Pull is designed for straightforward operation. Simply grasp the pull firmly to open or close your cabinet doors and drawers.

- **Opening:** Apply gentle, even pressure to the pull and pull it towards you to open the cabinet or drawer.
- **Closing:** Push the cabinet or drawer back into its closed position.

Avoid excessive force or twisting motions, as this can put undue stress on the pull and its mounting points.

MAINTENANCE

Proper maintenance will ensure the longevity and appearance of your Laurey Tribeca Cabinet Hardware Pulls.

- **Cleaning:** Clean the pull regularly with a soft, damp cloth. For stubborn marks, a mild soap solution can be used. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the satin nickel finish.
- **Drying:** After cleaning, dry the pull immediately with a clean, soft cloth to prevent water spots.
- **Periodic Inspection:** Periodically check the mounting screws for tightness. If a pull feels loose, gently tighten the screws with a screwdriver. Do not overtighten.
- **Avoid Impact:** Protect the pulls from direct impact with hard objects, which can cause dents or scratches.

TROUBLESHOOTING

This section addresses common issues you might encounter with your cabinet hardware pulls.

Problem	Possible Cause	Solution
Pull feels loose or wobbly.	Mounting screws are loose.	Gently tighten the mounting screws from the inside of the cabinet door/drawer using a Phillips head screwdriver. Do not overtighten.
Pull is scratched or discolored.	Abrasive cleaning agents, harsh chemicals, or physical impact.	Damage from abrasive cleaning or impact is typically permanent. For discoloration, try cleaning with a soft, damp cloth and mild soap. Prevent future damage by following maintenance guidelines.
Screws do not fit or are too short.	Cabinet thickness is not standard, or incorrect screw length was chosen.	Ensure you are using the correct screw length (1-inch or 1.5-inch provided). If both are too short, you will need to purchase longer M4 or 8/32 thread screws suitable for your cabinet thickness.

WARRANTY INFORMATION

Laurey provides a **Full Lifetime Warranty** for this product. This warranty covers defects in material and workmanship under normal use and service. For specific details regarding warranty claims and coverage, please refer to the official Laurey warranty policy or contact Laurey customer support.

SUPPORT AND CONTACT

For further assistance, technical support, or inquiries regarding your Laurey Tribeca Cabinet Hardware Pull, please contact Laurey customer service.

- **Manufacturer:** Laurey
- **Website:** [Visit the Laurey Store on Amazon](#)
- For direct support contact information, please refer to the product packaging or the official Laurey website.