

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [YUNDOOM](#) /

› [YUNDOOM Waterfall Bathroom Faucet \(Model bath02\) - Instruction Manual](#)

YUNDOOM bath02

YUNDOOM Waterfall Bathroom Faucet (Model bath02) - Instruction Manual

Model: bath02 | Brand: YUNDOOM



1. INTRODUCTION

This manual provides detailed instructions for the installation, operation, maintenance, and troubleshooting of your YUNDOOM Waterfall Bathroom Faucet, Model bath02. Please read this manual thoroughly before installation and retain it for future reference.

2. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- Waterfall Bathroom Faucet (Matte Black)
- Pop-Up Drain Assembly
- Deck Plate (for 3-hole installation)
- Hot and Cold Water Supply Hoses (3/8" standard)
- Mounting Hardware (nuts, washers, wrench)



Figure 2.1: Main components of the YUNDOOM Waterfall Bathroom Faucet. This image displays the matte black faucet, the included pop-up drain, and the hot and cold water supply hoses.

DETAILS DECIDE THE QUALITY

Healthy, lead-free, rust-free, stable and thick
Every part is carefully selected



Figure 2.2: Exploded view of faucet components including the main body, deck plate, supply hoses, and mounting tools. This image shows the individual parts required for installation, highlighting the quality materials.

3. INSTALLATION INSTRUCTIONS

3.1 Tools Required

- Adjustable Wrench
- Phillips Head Screwdriver
- Plumber's Putty or Silicone Sealant
- Safety Glasses
- Flashlight

3.2 Pre-Installation Steps

1. Turn off the main water supply to the bathroom.
2. Remove the old faucet and clean the sink surface thoroughly.

3. Ensure the mounting hole(s) on your sink or countertop are clean and free of debris.

3.3 Faucet Installation

1. If your sink has three holes, place the deck plate over the holes. For single-hole sinks, the deck plate is optional.
2. Insert the faucet body through the hole(s) in the sink/deck plate. Ensure the faucet is properly oriented.
3. From underneath the sink, secure the faucet using the provided rubber washer, metal washer, and mounting nut. Tighten firmly but do not overtighten.
4. Connect the hot and cold water supply hoses to the corresponding inlets on the faucet body. Hand-tighten, then use a wrench for a quarter turn.
5. Connect the other ends of the supply hoses to your hot and cold water supply valves. Ensure a tight seal.

PAINTED SURFACE

Paint layer

Chrome plating process

Nickel-plated layer

Refined copper body



Figure 3.1: Faucet dimensions for proper fit. This diagram illustrates the height and reach of the faucet, aiding in planning the installation.



Figure 3.2: Installation for a single-hole sink. This image demonstrates how the faucet is mounted through a single opening on the countertop.



Figure 3.3: Installation for a three-hole sink using the deck plate. This diagram shows the deck plate covering unused holes and providing a stable base for the faucet.



Video 3.1: YUNDOOM Bathroom Faucet Installation Guide. This video provides a visual step-by-step demonstration of how to install the YUNDOOM bathroom faucet, including securing the faucet and connecting water lines.

3.4 Pop-Up Drain Installation

1. Apply plumber's putty or silicone sealant around the underside of the drain flange.
2. Insert the drain body into the sink drain hole from above.
3. From underneath the sink, install the rubber washer, friction washer, and mounting nut onto the drain body. Tighten securely.
4. Connect the drain tailpiece to your P-trap assembly.



Figure 3.4: Diagram of the pop-up drain with overflow feature. This image illustrates the components of the drain assembly and how it integrates with a sink that has an overflow hole.

4. OPERATING INSTRUCTIONS

The YUNDOOM Waterfall Bathroom Faucet features a single handle for controlling both water flow and temperature.

- **To Turn On/Off:** Lift the handle upwards to start water flow. Push the handle downwards to stop water flow.
- **To Adjust Water Temperature:** Move the handle to the left for hot water and to the right for cold water. The further left or right, the hotter or colder the water will be.
- **To Adjust Water Flow:** The height to which you lift the handle controls the volume of water. Lift higher for more flow, lower for less.



Figure 4.1: Faucet handle indicating hot and cold water positions. This image highlights the intuitive control for adjusting water temperature.

5. MAINTENANCE AND CARE

Proper care will ensure the longevity and appearance of your faucet.

- **Cleaning:** Clean the faucet regularly with a soft cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the matte black finish.
- **Water Spots:** To prevent water spots, wipe the faucet dry after each use.
- **Aerator/Filter:** The waterfall spout has a built-in filter. Periodically check and clean any debris from the filter to maintain optimal water flow.
- **Ceramic Disc Cartridge:** The faucet features a durable ceramic disc cartridge designed for drip-free performance. If

leaks occur from the handle, the cartridge may need inspection or replacement.



Figure 5.1: Internal structure and finish layers of the faucet. This image details the refined copper body, nickel-plated layer, chrome plating process, and paint layer, illustrating the faucet's construction.

6. TROUBLESHOOTING GUIDE

Problem	Possible Cause	Solution
Low Water Flow	Clogged filter in spout Partially closed shut-off valves Debris in supply lines	Clean the filter in the waterfall spout. Ensure hot and cold water supply valves are fully open. Flush supply lines by disconnecting them from the faucet and running water into a bucket.
Leaking from Faucet Base	Loose mounting nut Improperly seated gasket	Tighten the mounting nut underneath the sink. Re-install the faucet ensuring gaskets are correctly positioned.

Problem	Possible Cause	Solution
Leaking from Handle	Worn ceramic disc cartridge	Contact customer support for a replacement ceramic disc cartridge.
Water Leaking from Drain	Loose drain nut Improperly applied plumber's putty/sealant	Tighten the drain nut underneath the sink. Re-apply plumber's putty or silicone sealant around the drain flange.

7. SPECIFICATIONS

Feature	Detail
Brand	YUNDOOM
Model Name	YUNDOOM bath02
Mounting Type	Deck Mount
Finish Type	Matte Black
Material	Brass (Main Body), Zinc (Handle)
Number of Handles	1
Hole Count	1 (or 3 with deck plate)
Spout Design	Waterfall
Spout Height	100 Millimeters (approx. 3.94 inches)
Spout Reach	5.68 Inches
Item Weight	3.16 pounds
Product Dimensions	5.91 x 1.97 x 4.72 inches
UPC	738629976115

8. WARRANTY AND SUPPORT

YUNDOOM provides a three-year replacement warranty for this product. If you encounter any issues with your faucet, please contact YUNDOOM customer support for assistance or replacement parts.

Your complete satisfaction is important to us. For support, please refer to the contact information provided with your purchase or visit the official YUNDOOM website.