

Manuals.plus /

> DUB /

> DUB S258 G.O.A.T. 26X10 Chrome Wheel Instruction Manual

DUB S258 G.O.A.T.

DUB S258 G.O.A.T. 26X10 Chrome Wheel Instruction Manual

Model: S258 G.O.A.T. | Brand: DUB

1. INTRODUCTION

This manual provides essential information for the proper installation, maintenance, and care of your DUB S258 G.O.A.T. 26X10 Chrome Wheel. Adhering to these guidelines will help ensure the longevity and optimal performance of your wheel. Please read this manual thoroughly before installation and use.

2. PRODUCT OVERVIEW

The DUB S258 G.O.A.T. wheel is a 26x10 inch chrome-finished automotive wheel designed for passenger cars, SUVs, and trucks. It features a 5x5.0 inch (5x127 mm) bolt pattern and a 10mm offset. Manufactured by MHT, this wheel is constructed using cast methods, ensuring durability and a distinctive appearance.



Figure 2.1: Angled view of the DUB S258 G.O.A.T. 26x10 Chrome Wheel, showcasing its multi-spoke design and polished finish.

3. SAFETY INFORMATION

- Always ensure your vehicle is securely supported on jack stands before removing or installing wheels.
- Wear appropriate personal protective equipment, including gloves and eye protection, during installation.
- Never exceed the maximum load index of 2500 lbs per wheel.
- Ensure proper tire mounting and balancing by a qualified professional.
- Incorrect installation can lead to serious injury or vehicle damage. If unsure, seek professional assistance.

4. SETUP AND INSTALLATION

4.1 Pre-Installation Checks

- Verify that the wheel specifications (size, bolt pattern, offset) match your vehicle's requirements.

- Inspect the wheel for any shipping damage or manufacturing defects before mounting tires.
- Ensure all necessary hardware (lug nuts, hub rings if required) is present and correct for your vehicle.

4.2 Installation Steps

1. Park the vehicle on a level surface and engage the parking brake.
2. Loosen the lug nuts on the wheel you intend to replace.
3. Safely lift the vehicle using a jack and secure it with jack stands.
4. Remove the old wheel and clean the hub mounting surface thoroughly.
5. Mount the new DUB wheel onto the hub, ensuring it sits flush against the mounting surface.
6. Install lug nuts by hand, ensuring they are properly seated.
7. Lower the vehicle until the tire just touches the ground.
8. Tighten the lug nuts in a star pattern to the vehicle manufacturer's specified torque. Refer to your vehicle's owner's manual for exact torque specifications.
9. Fully lower the vehicle and remove jack stands.
10. Re-check lug nut torque after 50-100 miles of driving.



Figure 4.1: Front view of the DUB S258 G.O.A.T. wheel, highlighting the 5-lug bolt pattern and center cap.



Figure 4.2: The DUB S258 G.O.A.T. wheel installed on a vehicle, demonstrating its fitment and aesthetic integration.

5. OPERATING GUIDELINES

Once installed, proper operation involves ensuring the wheels and tires are maintained correctly.

- **Tire Selection:** Always use tires that are compatible with the wheel size (26 inches diameter, 10 inches width) and your vehicle's specifications.
- **Tire Pressure:** Maintain correct tire pressure as recommended by your vehicle manufacturer. Incorrect pressure can affect handling, tire wear, and wheel integrity.
- **Balancing:** Ensure tires are properly balanced on the wheels to prevent vibrations and uneven wear. Re-balance if vibrations occur.
- **Driving Practices:** Avoid impacts with potholes, curbs, or road debris that could damage the wheel.

6. MAINTENANCE

Regular maintenance will preserve the appearance and structural integrity of your DUB chrome wheels.

6.1 Cleaning Chrome Wheels

- Use only mild soap and water with a soft cloth or sponge.
- Avoid abrasive cleaners, harsh chemicals, or stiff brushes, as these can scratch or damage the chrome finish.
- Rinse thoroughly with clean water and dry immediately with a soft, clean towel to prevent water spots.
- For stubborn grime, use a chrome-specific cleaner designed for automotive wheels, following the product's instructions carefully.

6.2 Regular Inspection

- Periodically inspect wheels for any signs of damage, such as cracks, bends, or corrosion.
- Check lug nuts for proper tightness regularly, especially after tire rotations or service.
- Monitor tire wear and replace tires as needed to maintain optimal performance and safety.



Figure 6.1: Side view of the DUB S258 G.O.A.T. wheel, illustrating the depth and profile of the rim.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Vehicle vibration	Unbalanced wheels, bent wheel, loose lug nuts, improper tire pressure.	Have wheels re-balanced. Inspect wheels for damage. Check and re-torque lug nuts. Adjust tire pressure.

Problem	Possible Cause	Solution
Unusual noises from wheels	Loose lug nuts, brake component interference, bearing issues.	Check and re-torque lug nuts. Inspect brake components for clearance. Consult a mechanic for bearing inspection.
Air loss from tire/wheel	Puncture, damaged tire bead, bent rim, faulty valve stem.	Inspect tire for punctures. Check wheel for damage. Have tire re-seated or valve stem replaced by a professional.

8. SPECIFICATIONS

Feature	Specification
Brand	DUB
Model	S258 G.O.A.T. (26X10 5X5.0 Chrome 10Mm)
Wheel Size	26 Inches
Rim Width	10 Inches
Bolt Pattern (PCD)	5x5.0 Inches (5x127 Millimeters)
Offset	10 Millimeters
Color	Chrome
Construction	Cast
Item Weight	63.9 Pounds
Load Index	2500
Vehicle Service Type	Passenger Car, SUV, Truck
UPC	194933071845

9. WARRANTY AND SUPPORT

DUB wheels are manufactured to high standards. For specific warranty information, please refer to the warranty documentation provided with your purchase or contact DUB customer support directly. Keep your proof of purchase for any warranty claims.

For technical support or inquiries, please contact your authorized DUB dealer or the manufacturer's customer service channels.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question

and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B08S2W7XJN>

More documents and user manuals: **<https://manuals.plus/>**