

Inalsa Zylo 60BKMAC

INALSA Zylo60BKMAC Kitchen Chimney User Manual

Model: Zylo 60BKMAC | Brand: Inalsa

1. INTRODUCTION

This manual provides essential information for the safe and efficient operation, installation, and maintenance of your INALSA Zylo60BKMAC Kitchen Chimney. Please read these instructions carefully before using the appliance and retain them for future reference.

2. SAFETY INSTRUCTIONS

- Ensure the power supply voltage matches the rating label on the chimney.
- Installation must be performed by a qualified technician to prevent electrical hazards or damage.
- Do not operate the chimney without the oil collector properly installed.
- Maintain adequate ventilation in the room when the chimney is in use, especially if other fuel-burning appliances are present.
- Clean the chimney and oil collector regularly to prevent grease buildup, which can be a fire hazard.
- Do not flambé under the chimney.
- Keep children away from the appliance during operation and cleaning.
- Disconnect the power supply before any cleaning or maintenance.

3. PACKAGE CONTENTS

Verify that all components are present in the package:

- Main Unit with Bee Filter
- Oil Collector
- Hood
- Expandable Pipe
- Wall Mounting Bracket
- Mounting Screws
- Screws for chimney cover

- Wall mounting plastic plugs
- Screws for flexible pipe
- Drill hole stencil
- Instruction cum Warranty Card

4. SETUP & INSTALLATION

Proper installation is crucial for the chimney's performance and safety. It is recommended to have the chimney installed by an authorized service technician.

4.1 Wall Dimensions for Installation

Ensure your kitchen wall space meets the required dimensions for proper fitting and operation. A minimum gap of 75 cm between the cooking surface and the chimney is recommended. Leave 1-2 cm space on each side for perfect fitting.



Figure 1: Wall Dimensions for Installation

4.2 Product Dimensions

The chimney measures 60 cm in width, 46 cm in depth, and 51.2 cm in height (excluding the duct cover). The duct cover adds to the overall height.

Quick Installation within 48 Hours



Figure 2: Detailed Product Dimensions

4.3 Installation Process

The chimney is designed for wall-mount installation. Use the provided wall mounting bracket, screws, and plastic plugs. A drill hole stencil is included to assist with accurate placement.



Figure 3: Chimney Installation

Important: Installation done by a third party will void the product warranty. Ensure installation is performed by authorized INALSA service personnel.

5. OPERATING INSTRUCTIONS

The INALSA Zyl60BKMAC chimney features both touch control and motion sensor operation for convenience.

5.1 Power On/Off and Speed Control

The chimney has 3 speed settings to adjust suction power based on cooking requirements. Use the touch panel controls to select the desired speed.

5.2 Motion Sensor Control

Wave your hand in front of the motion sensor to control the chimney's functions, such as turning it on/off or adjusting fan speed, without touching the panel.



Figure 4: Motion Sensor Operation

5.3 LED Lighting

The integrated LED light illuminates your cooking area, providing clear visibility and energy-efficient lighting.



Figure 5: LED Light in Operation

5.4 Thermal Auto Clean Function

Activate the thermal auto-clean function to melt and collect oil and grease particles into the oil collector, reducing manual cleaning effort.

5.5 Delay Power Off

The delay power-off feature allows the chimney to continue operating for a short period after cooking, ensuring all smoke and odors are cleared from the kitchen.



Figure 6: Creating a Healthy Cooking Environment

6. CLEANING & MAINTENANCE

Regular cleaning and maintenance ensure optimal performance and longevity of your chimney.

6.1 Oil Collector Cleaning

The oil collector should be cleaned regularly. It can be easily removed without tools for thorough cleaning.

- Easily remove the oil collector.
- Clean the oil collector thoroughly with warm soapy water.
- Slide it back into the chimney slot once dry.



Figure 7: Easy Oil Collector Cleaning

6.2 Exterior Cleaning

Wipe the exterior surfaces of the chimney with a soft cloth and mild detergent. Avoid abrasive cleaners or harsh chemicals that could damage the finish.

6.3 Filterless Design

This chimney features a filterless design, reducing the need for filter replacement and simplifying maintenance.

7. TROUBLESHOOTING

If you encounter issues with your chimney, refer to the following common problems and solutions:

| Problem | Possible Cause | Solution |
|------------------------|--|--|
| Chimney not turning on | No power supply; loose connection | Check power plug and circuit breaker. Ensure connections are secure. |
| Low suction power | Oil collector full; obstruction in ducting | Clean the oil collector. Check for blockages in the exhaust duct. |

| Problem | Possible Cause | Solution |
|-----------------------|---|---|
| Excessive noise | Loose parts; improper installation; motor issue | Ensure all parts are securely fastened. Verify correct installation. If noise persists, contact customer service. |
| LED light not working | Faulty LED; electrical issue | Check power supply. If the issue persists, contact customer service. |

For problems not listed here or if solutions do not resolve the issue, please contact INALSA customer support.

8. SPECIFICATIONS

Key technical specifications for the INALSA Zylo60BKMAC Kitchen Chimney:

- **Brand:** Inalsa
- **Model Number:** Zylo 60BKMAC
- **Product Dimensions:** 46D x 60W x 51.2H Centimeters
- **Colour:** Black
- **Special Features:** Auto Clean, Filterless Chimney, Motion Sensor, Oil Collector
- **Finish Type:** Powder Coated
- **Air Flow Capacity:** 1250 Cubic Meters Per Hour
- **Noise Level:** 65 Decibels
- **Mounting Type:** Wall Mount
- **Controls Type:** Motion Sensor, Touch
- **Voltage:** 230.0 V
- **Number Of Speeds:** 3
- **Light Source:** LED
- **Filter Type:** Filterless
- **Ventilation Type:** Ductless
- **Item Weight:** 9500 Grams
- **Material Type:** Glass

The graphic is a comparison between two kitchen chimneys. On the left, an INALSA chimney is shown with a control panel featuring a Wi-Fi icon, a power button, and several indicator lights. Below it, the text reads 'INALSA' in large teal letters, followed by a teal icon of a cyclone and '1250m³/h SUCTION'. Below this, it says 'More Suction Prevent the cooking fumes from spreading*'. On the right, a smaller, simpler chimney is shown. Below it, the text reads 'OTHER CHIMNEY' in white, followed by '<1150m³/h SUCTION' and a white icon of a cyclone. Below this, it says 'The fumes are dispersed during extraction*'. A central teal circle with 'VS' in white is positioned between the two chimneys. A teal diagonal line separates the two sides. At the bottom right, a small teal box contains the text '*AS PER INTERNAL INALSA TESTING DATA 2022'.

Figure 8: High Suction Power

9. WARRANTY & SUPPORT

Your INALSA Zyl60BKMAC Kitchen Chimney comes with a comprehensive warranty and dedicated support.

9.1 Warranty Information

- **Product Warranty:** 2 Years from the date of purchase.
- **Motor Warranty:** 7 Years from the date of purchase.

The warranty is provided by the brand INALSA. Please ensure you register your product to activate the warranty.

9.2 Warranty Registration

To activate your warranty, please register your product on the official INALSA website:

<https://www.inalsaappliances.com/product-registration>

Note: Warranty is valid only after registration. Installation by a third party will void the warranty.

9.3 Customer Support

For any queries, service requests, or technical assistance, please contact Tuareg Marketing Pvt Ltd., the manufacturer and importer of INALSA products.