



[Manuals.plus](#) /

› [Generation Lighting](#) /

› Generation Lighting Perryton Four-Light Pendant Fixture Instruction Manual

Generation Lighting 5115004-112

Instruction Manual

Generation Lighting Perryton Four-Light Pendant Fixture

1. INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your **Generation Lighting Perryton Four-Light Pendant Fixture**, Model **5115004-112**. This fixture is designed to provide abundant light and add style to your home, inspired by stately carriage lanterns with an updated open frame design.

Key features include:

- Featured in the decorative Perryton collection.
- Requires 4 Torpedo Candelabra 60-watt light bulbs.
- Supplied with adjustable 10-feet of wire for preferred length.
- Additional extension rods included for a do-it-yourself project and customized look.
- Mounting hardware included for use on flat, slope, vaulted, or cathedral ceilings.



Figure 1: Generation Lighting Perryton Four-Light Pendant Fixture. This image shows the complete fixture with its black metal frame and four candelabra-style light sockets.



Figure 2: Two Perryton Pendant Fixtures installed above a kitchen island. This image demonstrates the fixture's appearance in a typical home setting, highlighting its design and lighting effect.

2. SETUP AND INSTALLATION

This fixture is designed for semi-flush mount installation and includes all necessary mounting hardware. While the main fixture is pre-assembled, professional installation is recommended to ensure safety and proper functionality. Always turn off power at the circuit breaker before beginning any electrical work.

2.1 Components Checklist

- Fixture body with 4 light sockets
- Canopy and mounting bracket
- (3) 12" Stems
- (1) 6" Stem
- Wire nuts and screws

2.2 Installation Steps

1. **Safety First:** Ensure power is disconnected at the main circuit breaker before installation.
2. **Prepare Mounting:** Attach the mounting bracket to the junction box in the ceiling.
3. **Adjust Height:** Determine the desired hanging height. The fixture comes with adjustable stems (three 12-inch and one 6-inch) and a 10-foot adjustable wire to customize the length. Connect the appropriate stems to the fixture and the canopy.
4. **Wire Connections:** Connect the fixture's electrical wires to the corresponding household wires (black to black, white to white, ground to ground) using wire nuts.
5. **Secure Canopy:** Carefully push the canopy up to the ceiling, ensuring all wires are tucked inside the junction box, and secure it with the provided screws.
6. **Install Bulbs:** Insert four E12 candelabra base bulbs (up to 60 watts each) into the sockets.
7. **Restore Power:** Turn power back on at the circuit breaker.



Figure 3: Dimensions of the Perryton Four-Light Pendant Fixture. The image illustrates the fixture's height of 18.5 inches and width of 12.25 inches.

3. OPERATING INSTRUCTIONS

The Perryton Four-Light Pendant Fixture operates on a standard 120-volt electrical system. It is designed for use with four incandescent E12 candelabra base bulbs, each up to 60 watts. The fixture is dimmable, allowing you to adjust the light intensity when connected to a compatible dimmer switch (sold separately).

3.1 Powering On/Off

Control the fixture using a standard wall switch. If connected to a compatible touch control system, follow the instructions provided with your touch control device.

3.2 Dimmable Functionality

To utilize the dimmable feature, ensure you are using dimmable E12 incandescent bulbs and that the fixture is wired to a compatible dimmer switch. Adjust the dimmer switch to achieve your desired light level.

4. MAINTENANCE

Regular maintenance will help preserve the appearance and functionality of your lighting fixture.

- **Cleaning:** Before cleaning, ensure the power to the fixture is turned off. Allow the fixture to cool. Use a soft, dry cloth to wipe down the metal frame. For glass components, a mild glass cleaner can be applied to a cloth (not directly to the fixture) and then wiped clean. Avoid abrasive cleaners or solvents as they may damage the finish.
- **Bulb Replacement:** Always turn off power before replacing bulbs. Allow bulbs to cool completely before handling. Replace with E12 candelabra base bulbs, not exceeding 60 watts per bulb.
- **Inspection:** Periodically check all connections and mounting hardware to ensure they remain secure.

5. TROUBLESHOOTING

If your fixture is not operating correctly, refer to the following common issues and solutions:

Problem	Possible Cause	Solution
Light does not turn on.	No power to the fixture; Loose wiring connection; Faulty bulb.	Check circuit breaker. Ensure all wire connections are secure. Replace bulb.
Light flickers.	Loose bulb; Incompatible dimmer switch; Loose wiring.	Tighten bulb. Ensure dimmer switch is compatible with incandescent bulbs. Check wiring connections.
Fixture hums.	Incompatible dimmer switch; Loose wiring.	Replace dimmer with a high-quality, compatible model. Check wiring connections.

If the problem persists after attempting these solutions, contact a qualified electrician or Generation Lighting customer support.

6. SPECIFICATIONS

Attribute	Detail
Brand	Generation Lighting
Model Name	Perryton
Model Number	5115004-112

Attribute	Detail
Product Dimensions	12.25"L x 12.25"W x 18.5"H
Item Weight	6.7 Pounds
Color	Midnight Black
Material	Alloy Steel (Frame), Glass (Shade)
Light Source Type	Incandescent
Number of Light Sources	4
Bulb Base	E12
Max Wattage per Bulb	60 watts
Voltage	120 Volts
Special Feature	Dimmable
Installation Type	Semi Flush Mount
Indoor/Outdoor Usage	Indoor (Damp rated, also ideal for covered patio or porch)
Included Components	(3) 12" Stems, (1) 6" Stem, Mounting Hardware

7. WARRANTY AND SUPPORT

This Generation Lighting fixture comes with a **1-year manufacturer's warranty** from the date of purchase. This warranty covers defects in materials and workmanship under normal use.

For warranty claims, technical assistance, or any questions regarding your product, please contact Generation Lighting customer support. Keep your proof of purchase for warranty validation.

Please note: This product is subject to local laws and regulations. Ensure compliance before installation and use.

