

GROHE 39663000

GROHE 39663000 Eurocube Two-Piece Elongated Toilet User Manual

Brand: GROHE | Model: 39663000

1. INTRODUCTION

This manual provides detailed instructions for the installation, operation, maintenance, and troubleshooting of your GROHE 39663000 Eurocube Two-Piece Elongated Toilet. Please read these instructions carefully before beginning installation or use to ensure proper function and longevity of your product.

The GROHE Eurocube toilet features a powerful flushing system designed for efficient clearing and cleaning of the bowl. Its skirted sides contribute to a contemporary aesthetic and facilitate easy cleaning. This model operates with an ultra-low consumption of 1.28 gallons of water per flush, promoting eco-friendly water usage.

2. PRODUCT FEATURES

- **InfinaBright Coating:** A specialized coating that reduces dirt and bacteria buildup, helping to maintain a lasting shine and simplify cleaning.
- **DreamClean Technology:** Features a powerful rush of water from the rim to thoroughly scrub the bowl with every flush.
- **Ultra-Low Water Consumption:** Uses only 1.28 gallons per flush (GPF), which is 20% less water than conventional toilets, without compromising performance.
- **Clog-Free Siphon Flushing Action:** Engineered to clear the bowl completely on the first flush, minimizing clogs.
- **Soft-Close Seat and Cover:** Designed for quiet operation, preventing slamming.
- **Quick-Release Seat:** Allows for easy removal and reattachment of the seat for convenient cleaning.



DreamClean
Scrubs the bowl with pressurized water from the rim during each flush



InfinaBright
Double coating inhibits the growth of stain and odor-causing bacteria, mold and mildew



Soft-Close Seat & Cover
Slow, gentle motion to eliminate noise and slamming



Quick-Release Seat
Easily remove and replace seat for quick and easy cleaning



ADA Compliant
Americans With Disabilities Act 2010 compliant

Image: Overview of the GROHE Eurocube toilet highlighting its key features like InfinaBright, DreamClean, Soft-Close Seat, and Quick-Release Seat.



InfinaBright Durable coating reduces dirt and bacteria build-up ensuring the surface shines longer so you scrub less.



Powerful Flush Forceful, clog-free siphon flushing action clears the bowl completely on the first flush.



DreamClean Innovative rim design releases powerful rush of water, scrubs the bowl top-to-bottom with every flush.



Quick-Release, Soft-Close Seat & Cover Remove the seat with push-button ease plus slow, gentle motion to eliminate slamming.

Image: Detailed view of the toilet bowl during flushing, demonstrating the DreamClean and Powerful Flush features. Also shows the quick-release mechanism for the soft-close seat.

3. SETUP AND INSTALLATION

The GROHE 39663000 is a two-piece toilet, meaning the tank and bowl are separate components that are assembled during installation. Professional installation is recommended.

3.1 Pre-Installation Checks

- Verify all components are present and undamaged.
- Ensure the rough-in dimensions of your plumbing match the toilet specifications.
- Turn off the water supply to the toilet area.

3.2 Installation Steps (Summary)

1. Prepare the flange and wax ring.
2. Set the bowl onto the flange, ensuring proper alignment.
3. Secure the bowl to the floor using the provided bolts.
4. Install the tank onto the bowl, connecting the tank-to-bowl bolts and gasket.

5. Connect the water supply line to the tank fill valve.
6. Install the right-hand trip lever.
7. Install the soft-close, quick-release seat.
8. Turn on the water supply and check for leaks.

Note on Flange Bolt Access: Some users have reported that the side holes behind the side covers could be larger to allow easier access to the flange bolts during installation. Careful alignment and patience are advised during this step.



Image: Technical drawing showing the dimensions of the GROHE Eurocube toilet, including height, width, depth, and rough-in measurements. This is crucial for proper installation planning.

4. OPERATING INSTRUCTIONS

The GROHE 39663000 Eurocube toilet is designed for simple and efficient operation.

4.1 Flushing the Toilet

- To flush, simply press down on the right-hand trip lever located on the side of the tank.
- The toilet will initiate a powerful siphon flush using 1.28 gallons of water to clear the bowl.
- Release the lever once the flush cycle begins.



Image: This image illustrates both a right-hand trip lever and a top-mounted dual flush button. For model 39663000, operation is primarily via the right-hand trip lever, providing a single 1.28 GPF flush.

5. MAINTENANCE

Regular cleaning and maintenance will ensure your GROHE Eurocube toilet remains in optimal condition and appearance.

5.1 Cleaning the Bowl and Exterior

- Utilize the InfinaBright coating and DreamClean features by regularly flushing and cleaning the bowl with a soft brush and mild toilet cleaner.
- For the exterior, use a soft cloth and a non-abrasive, mild bathroom cleaner. Avoid harsh chemicals, abrasive pads, or strong acids, as these can damage the finish and coating.
- The skirted design of the toilet simplifies exterior cleaning.

5.2 Seat Removal for Cleaning

- The soft-close seat features a quick-release button for easy removal. Locate the buttons near the hinges at the back of the seat.
- Press the quick-release buttons and lift the seat straight up to detach it from the bowl.
- Clean the seat and the area around the hinges thoroughly.
- To reattach, align the seat posts with the hinge pins and press down until they click into place.

6. TROUBLESHOOTING

This section addresses common issues you might encounter with your toilet.

6.1 Toilet Not Flushing or Weak Flush

- **Check Water Supply:** Ensure the water supply valve behind the toilet is fully open.
- **Inspect Trip Lever:** Verify the right-hand trip lever is properly connected to the flapper chain inside the tank. Adjust the chain if it's too loose or too tight.
- **Examine Flapper:** Check if the flapper is sealing correctly at the bottom of the tank. Mineral buildup or wear can prevent a good seal.
- **Water Level:** Ensure the water level in the tank is at the recommended fill line. Adjust the fill valve if

necessary.

6.2 Loose Toilet Seat

- If the seat becomes loose, gently remove the quick-release seat.
- Tighten the mounting bolts that secure the seat hinges to the toilet bowl. Do not overtighten.
- Reattach the quick-release seat.

6.3 Leaks

- **Base Leaks:** Check the wax ring and flange bolts. If leaking from the base, the wax ring may need replacement or the bolts may need tightening.
- **Tank-to-Bowl Leaks:** Ensure the tank-to-bowl bolts are tight and the gasket is properly seated.
- **Supply Line Leaks:** Check the connection of the water supply line to the fill valve and the wall. Tighten connections if necessary.

7. SPECIFICATIONS

Attribute	Detail
Model Number	39663000
Brand	GROHE
Color	Alpine White
Material	Vitreous China (Toilet), Plastic (Seat)
Item Weight	136 Pounds
Product Dimensions	29.19 x 14.94 x 30.88 inches (Depth x Width x Height)
Installation Type	Floor Mounted
Shape	Elongated (Oblong)
Flush Type	Single Flush, Right-Hand Trip Lever
Water Consumption	1.28 Gallons Per Flush (GPF)
Included Components	Toilet, trip lever, slow-close telescoping seat, color-matched bolt hole covers

8. WARRANTY AND SUPPORT

8.1 Product Warranty

This GROHE product is covered by a LIMITED warranty. For specific details regarding the terms and conditions of your warranty, please refer to the warranty documentation included with your purchase or visit the official GROHE website.

8.2 Customer Support

For technical assistance, replacement parts, or any questions not covered in this manual, please contact GROHE customer service. Contact information can typically be found on the GROHE website or on your product packaging.

Optional protection plans, such as a 4-Year Protection Plan or a Complete Protect monthly plan, may be available for purchase separately to extend coverage beyond the standard manufacturer's warranty.