

I2W-DC226

DC 2-26 Electrical Mechanical Multi-use Lubricant

Instruction Manual

PRODUCT OVERVIEW

The DC 2-26 Multi-use Lubricant is a versatile solution designed for various applications, including electrical and mechanical systems. This product is formulated to penetrate and lubricate components, displace and seal out moisture, release rusted mechanisms, prevent corrosion, and effectively clean surfaces.

It serves as a comprehensive multi-use lubricant, offering multiple benefits in a single application.



Figure 1: DC 2-26 Electrical Mechanical Multi-use Lubricant spray can.

This image displays the DC 2-26 Electrical Mechanical Multi-use Lubricant in its spray can packaging. The can features a green and blue design with the product name "DC 2-26" prominently displayed. The label highlights its multi-use capabilities, including penetration, lubrication, moisture displacement, rust release, corrosion prevention, and cleaning properties.

SETUP AND PREPARATION

Before using the DC 2-26 lubricant, ensure proper preparation of the work area and the product itself.

- Ventilation:** Use in a well-ventilated area to avoid inhalation of fumes. If working indoors, ensure windows are open or use an exhaust fan.
- Surface Preparation:** For best results, clean the target surface of loose dirt, grease, or debris before application.
- Shake Can:** Shake the spray can thoroughly for at least 30 seconds before use to ensure the contents are well mixed.

4. **Test Application:** For sensitive materials or painted surfaces, test the product on an inconspicuous area first to check for compatibility.
5. **Protective Gear:** Consider wearing gloves and eye protection to prevent skin and eye contact.

OPERATING INSTRUCTIONS

Follow these instructions for effective application of the DC 2-26 Multi-use Lubricant:

- **General Lubrication and Penetration:**

Spray directly onto the moving parts, hinges, or seized components. Allow a few minutes for the product to penetrate. For heavily rusted or seized parts, reapply and allow more time.

- **Electrical Contact Cleaning:**

For electrical contacts, ensure power is off before application. Spray a light coat onto the contacts. The product displaces moisture and helps improve conductivity. Allow to dry completely before restoring power.

- **Rust Removal and Prevention:**

Apply generously to rusted areas. The penetrating action helps loosen rust. For severe rust, use a wire brush after application. A thin film left behind will help prevent future corrosion.

- **Degreasing and Cleaning:**

Spray onto greasy or dirty surfaces. Allow the product to work for a few moments, then wipe clean with a cloth. For stubborn grime, a second application may be necessary.

- **Bike Chain Cleaning and Lube:**

Apply to the bike chain while rotating the pedals slowly. This will clean and lubricate the chain simultaneously. Wipe off excess product to prevent dirt accumulation.

- **Chimney Cleaning:**

While not a primary chimney cleaner, it can assist in loosening minor creosote or soot buildup on metal components within the chimney system. Apply to affected metal parts and allow to penetrate before cleaning. Consult a professional for major chimney cleaning.

MAINTENANCE AND STORAGE

Proper maintenance and storage ensure the longevity and effectiveness of the product.

- **Storage:** Store the can upright in a cool, dry place away from direct sunlight and heat sources. Do not expose to temperatures exceeding 50°C (122°F).
- **Cap Replacement:** Always replace the cap after use to prevent accidental discharge and maintain product integrity.
- **Disposal:** Dispose of empty cans according to local regulations. Do not puncture or incinerate.

TROUBLESHOOTING

If you encounter issues while using the DC 2-26 lubricant, consider the following:

- **Clogged Nozzle:** If the spray nozzle is clogged, remove it and rinse with warm water. If persistent, replace the nozzle.
- **Insufficient Effect:** Ensure the surface was properly cleaned before application. For stubborn issues (e.g., heavy rust), allow more penetration time or reapply.

- **Product Leakage:** Ensure the cap is securely fastened when not in use. Store upright.

SPECIFICATIONS

Attribute	Detail
Brand	Generic
Manufacturer	Denmat Chemicals Pvt. Ltd.
Model Number	I2W-DC226
Item Weight	350 g
ASIN	B097LGD8DB
Date First Available	20 June 2021

WARRANTY AND SUPPORT

Information regarding product warranty and customer support is not explicitly provided in the available product details. For any inquiries or support needs, please refer to the contact information provided on the product packaging or reach out to the manufacturer, Denmat Chemicals Pvt. Ltd., directly.

© 2023 Generic. All rights reserved.

This manual is for informational purposes only. Always follow safety guidelines and product label instructions.