

[Manuals.plus](#) /

› [Shop-Vac](#) /

› Shop-Vac 5 Gallon 2.0 Peak HP Wet/Dry Vacuum User Manual

Shop-Vac 2035000

Shop-Vac 5 Gallon 2.0 Peak HP Wet/Dry Vacuum User Manual

Model: 2035000

Brand: Shop-Vac

INTRODUCTION

This manual provides essential information for the safe and efficient operation, maintenance, and troubleshooting of your Shop-Vac 5 Gallon 2.0 Peak HP Wet/Dry Vacuum. Please read this manual thoroughly before using the product and retain it for future reference.

IMPORTANT SAFETY INFORMATION

Always follow basic safety precautions when using electrical appliances to reduce the risk of fire, electric shock, or injury.

- Do not leave the appliance unattended when plugged in. Unplug from outlet when not in use and before servicing.
- Do not use with damaged cord or plug. If appliance is not working as it should, has been dropped, damaged, left outdoors, or dropped into water, return it to a service center.
- Do not pull or carry by cord, use cord as a handle, close a door on cord, or pull cord around sharp edges or corners. Do not run appliance over cord. Keep cord away from heated surfaces.
- Do not unplug by pulling on cord. To unplug, grasp the plug, not the cord.
- Do not handle plug or appliance with wet hands.
- Do not use to pick up flammable or combustible liquids, such as gasoline, or use in areas where they may be present.
- Do not pick up anything that is burning or smoking, such as cigarettes, matches, or hot ashes.
- Use extra care when cleaning on stairs.
- Do not use without filters in place.
- Connect to a properly grounded outlet only. See grounding instructions.

PRODUCT COMPONENTS

Familiarize yourself with the main components of your Shop-Vac Wet/Dry Vacuum.



Figure 1: Overview of the Shop-Vac 5 Gallon Wet/Dry Vacuum components, including the carry handle, ON/OFF switch, 2 HP motor, latches, blower port, vacuum port, collection tank, and casters.

WHAT'S IN THE BOX

Verify that all components are present before assembly.

WHAT'S IN THE BOX?



Figure 2: Contents of the Shop-Vac package, including the main unit, 10-inch wet/dry nozzle, foam sleeve, filter ring, three extension wands, three reusable dry filters, and a 7-foot LockOn hose.

- Shop-Vac 5 Gallon 2.0 Peak HP Wet/Dry Vacuum Unit
- 7 ft. x 1-1/4 in. Secure Fit Hose
- (3) Extension Wands
- (1) 10 In Wet/Dry Nozzle
- (3) Type S Disc Filter (Reusable Dry Filter)
- (1) Foam Sleeve
- (1) Filter Ring

SETUP AND ASSEMBLY

Follow these steps to assemble your Shop-Vac Wet/Dry Vacuum.

1. **Unpack Components:** Carefully remove all items from the packaging.
2. **Attach Casters:** Insert the casters into the designated slots on the bottom of the collection tank until they click

securely into place.

3. Install Filter for Dry Pickup:

- Ensure the foam sleeve is removed if previously installed for wet pickup.
- Place a reusable dry filter over the filter cage, ensuring it covers the entire cage.
- Secure the filter with the filter ring, pressing it firmly into place.

4. Install Foam Sleeve for Wet Pickup:

- Remove any dry filters and filter rings.
- Slide the foam sleeve over the filter cage until it is fully seated.

5. **Attach Hose:** Insert the secure fit hose into the vacuum port on the front of the unit. Twist to lock if applicable.

6. **Attach Accessories:** Connect the desired extension wands and the 10-inch wet/dry nozzle to the end of the hose.

OPERATING INSTRUCTIONS

Your Shop-Vac Wet/Dry Vacuum is designed for versatile cleaning tasks.



Figure 3: The Shop-Vac's three primary functions: dry cleaning for debris, wet cleaning for liquids, and blow cleaning for clearing areas.

Dry Cleaning

For dry debris pickup, ensure the reusable dry filter and filter ring are properly installed. Do not use the foam sleeve for dry pickup.

1. Ensure the dry filter is clean and correctly installed.
2. Plug the power cord into a grounded electrical outlet.
3. Turn the ON/OFF switch to the "ON" position.
4. Begin vacuuming dry debris.
5. When finished, turn the switch to "OFF" and unplug the unit.

Wet Cleaning

For wet liquid pickup, the foam sleeve must be installed, and the dry filter removed. Do not use the dry filter for wet pickup.

1. Remove the dry filter and filter ring. Install the foam sleeve over the filter cage.
2. Plug the power cord into a grounded electrical outlet.
3. Turn the ON/OFF switch to the "ON" position.
4. Begin vacuuming liquids. The vacuum will stop suction when the tank is full.
5. When finished, turn the switch to "OFF" and unplug the unit. Empty the collection tank immediately after wet pickup.

Blowing Function

The vacuum can be converted into a powerful blower.

1. Ensure the unit is unplugged.
2. Remove the hose from the vacuum port.
3. Insert the hose into the blower port located on the back of the motor housing.
4. Plug the power cord into a grounded electrical outlet.
5. Turn the ON/OFF switch to the "ON" position to use as a blower.
6. When finished, turn the switch to "OFF" and unplug the unit.

EASY TRANSPORTATION



Top Handle Design

Non-marring Wheels

Figure 4: The compact design, top collapsible handle, and caster system allow for easy transportation of the Shop-Vac.

MAINTENANCE

Regular maintenance ensures optimal performance and extends the life of your vacuum.

Emptying the Collection Tank

For both wet and dry pickup, empty the tank when it is full or when suction power decreases significantly.

1. Unplug the vacuum from the power outlet.
2. Release the latches on the sides of the unit and lift off the motor housing.
3. Carefully pour out liquids or dispose of dry debris from the collection tank.
4. Clean the inside of the tank with water and mild soap if necessary, then dry thoroughly.
5. Replace the motor housing and secure the latches.

Filter Maintenance

Clean or replace filters as needed to maintain suction power.

- **Reusable Dry Filter:** Tap off loose dirt. If heavily soiled, rinse with water and allow to air dry completely before reinstallation. Do not use a wet filter for dry pickup.
- **Foam Sleeve:** Rinse with water and mild soap. Allow to air dry completely before reinstallation.

TROUBLESHOOTING

Refer to this section for common issues and their solutions.

Problem	Possible Cause	Solution
Vacuum will not operate.	No power to outlet; Power cord not plugged in; ON/OFF switch in "OFF" position.	Check power supply; Plug in power cord; Turn switch to "ON".
Reduced suction power.	Clogged hose/nozzle; Full collection tank; Clogged or wet filter; Loose hose connection.	Clear obstruction; Empty tank; Clean/dry/replace filter; Secure hose connection.
Water coming from exhaust.	Tank is full during wet pickup; Foam sleeve not installed or damaged.	Empty tank; Install/replace foam sleeve.

SPECIFICATIONS

Key technical specifications for the Shop-Vac 5 Gallon 2.0 Peak HP Wet/Dry Vacuum.



Figure 5: Visual representation of the Shop-Vac's capacity, power, hose diameter, hose length, power cord length, and airflow (CFM).

- **Model:** 2035000
- **Capacity:** 5 Gallons
- **Peak Horsepower:** 2.0 HP
- **Item Weight:** 5.4 Kilograms
- **Form Factor:** Cannister
- **Hose Diameter:** 1-1/4 inches
- **Hose Length:** 7 feet
- **Power Cord Length:** 6 feet
- **Voltage:** 120 Volts
- **Filter Type:** Foam (for wet), Disc (for dry)
- **Special Features:** Wet/Dry capability, Wheels, Collapsible Handle
- **Included Components:** Vacuum unit, 7' x 1-1/4" secure fit hose, three extension wands, foam sleeve, reusable disc filter with ring, 10 in wet/dry nozzle.

WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the warranty card included with your product or visit the official Shop-Vac website. Keep your purchase receipt as proof of purchase.

For further assistance, you may contact Shop-Vac customer service through their official channels.

© 2024 Shop-Vac Corporation. All rights reserved.

This manual is for informational purposes only. Specifications are subject to change without notice.