

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [Moen](#) /

› [Moen Cia Widespread 2-Handle High-Arc Bathroom Faucet \(Model T6222BG\) Instruction Manual](#)

Moen T6222BG

Moen Cia Widespread 2-Handle High-Arc Bathroom Faucet

Model T6222BG Instruction Manual for 3-Hole Bath Sinks

PRODUCT OVERVIEW

The Moen Cia Widespread 2-Handle High-Arc Bathroom Faucet, model T6222BG, is designed for 3-hole bath sink installations. It features a brushed gold finish and two lever handles for precise control of water temperature and flow. This faucet is WaterSense certified, promoting water conservation without compromising performance.

Key Features

- **Temperature Control:** Two-handle lever handles allow for easy adjustment of water temperature.
- **Brushed Gold Finish:** Features a mix of classic gold tones and modern brushed texture.
- **Flexible Design:** Can be installed with a widespread configuration between 8 to 16 inches.
- **Certified Safe:** Complies with Federal Safe Drinking Water Act and NSF 61 standards.
- **WaterSense Certified:** Meets EPA WaterSense criteria for water conservation.
- **Coordinating Collection:** Designed to complement other faucets and accessories in the Cia Collection.

IMPORTANT PRE-INSTALLATION INFORMATION

Before beginning installation, ensure you have all necessary components and tools. A Moen valve 9000 is required for complete installation and is sold separately. Verify that your sink has a 3-hole configuration suitable for a widespread faucet.



REQUIRED VALVE SOLD SEPARATELY

This image illustrates the valve assembly (Moen valve 9000) that is essential for the proper function and installation of the faucet. This component must be acquired separately.

Recommended Tools and Materials

- Adjustable wrench
- Phillips and flathead screwdrivers
- Plumber's putty or silicone sealant
- Safety glasses
- Flashlight
- Towels
- Moen valve 9000 (sold separately)

INSTALLATION INSTRUCTIONS

Step 1: Prepare the Sink Area

1. Turn off the main water supply to the sink.
2. Clear the area under the sink for access.
3. Remove any existing faucet and thoroughly clean the mounting surface.

Step 2: Install the Valve Body

Refer to the detailed installation instructions provided with your Moen valve 9000 for proper installation of the valve body. Ensure all connections are secure and watertight before proceeding.

Step 3: Install the Faucet Spout and Handles

4. Position the faucet spout and handle assemblies into the pre-drilled 3-holes on your sink or countertop. The widespread design allows for flexible spacing between 8 to 16 inches.
5. Secure the faucet components from underneath the sink using the provided mounting hardware. Ensure they are tightened evenly to prevent wobbling.
6. Connect the hot and cold water supply lines to the corresponding inlets on the valve body. Use an adjustable wrench to tighten connections firmly, but avoid overtightening.
7. Install the drain assembly according to its specific instructions, ensuring a watertight seal.

Step 4: Test for Leaks

8. Slowly turn on the main water supply.
9. Carefully check all connections for any signs of leaks. Tighten any leaking connections as needed.
10. Operate the faucet handles to ensure proper water flow and temperature control from both hot and cold lines.

OPERATING INSTRUCTIONS

The Moen Cia faucet features two lever handles for precise control over water flow and temperature.

- To turn on the water, lift the lever handles.
- To adjust water temperature, move the left handle for hot water and the right handle for cold water.
- To increase or decrease water flow, adjust the height of the lever handles.
- To turn off the water, push the lever handles down.



This image shows the Moen Cia faucet with water flowing, demonstrating its high-arc design and ease of use.

MAINTENANCE AND CARE

To maintain the brushed gold finish and ensure long-lasting performance of your Moen Cia faucet, follow these care guidelines:

- **Cleaning:** Clean regularly with a soft, damp cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Drying:** Always dry the faucet after use to prevent water spots and mineral buildup, especially in hard water areas.
- **Avoid Polishes:** Do not use polishes or waxes unless specifically designed for brushed gold finishes.



This image highlights the brushed gold finish, emphasizing the importance of proper care to preserve its appearance.

TROUBLESHOOTING

Common Issues and Solutions

Problem	Possible Cause	Solution
Low Water Flow	Aerator clogged with debris	Remove and clean the aerator.

Problem	Possible Cause	Solution
Leaking from Spout	Worn out O-rings or cartridges	Replace O-rings or cartridges. (Consult Moen support or a qualified plumber).
Leaking at Base	Loose mounting nuts or improper sealant	Tighten mounting nuts and/or reapply plumber's putty/silicone sealant.
Difficulty Adjusting Temperature	Faulty cartridge or mineral buildup	Clean or replace the cartridge. (Consult Moen support).

SPECIFICATIONS

Feature	Detail
Brand	Moen
Model Number	T6222BG
Color	Brushed Gold
Material	Metal
Number of Handles	2
Mounting Type	Deck Mount
Hole Count	3
Installation Type	Widespread (8" to 16" spread)
Spout Design	High Arc
Spout Height	6.4 Inches
Spout Reach	5.5 Inches
Maximum Flow Rate	1.2 Gallons Per Minute
Included Components	Bathroom Faucet trim kit, Drain, Instruction Manual
Item Weight	4.18 Pounds
Product Dimensions	5.5 x 13.75 x 9 inches
Certifications	WaterSense Certified, Federal Safe Drinking Water Act, NSF 61 standards

WARRANTY AND SUPPORT

Limited Lifetime Warranty

Moen offers a Limited Lifetime Warranty on this faucet to the original consumer purchaser against leaks, drips, and finish defects during normal residential use. For commercial installations, a 5-year limited warranty applies.

For detailed warranty information, product support, or to order replacement parts, please visit the official Moen website or contact Moen customer service.

Manufacturer: Moen Incorporated

UPC: 026508336212

© 2024 Moen Incorporated. All rights reserved.