Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

OasisCraft B099DGF8TK

OasisCraft Folding Teak Shower Bench Seat

Model: B099DGF8TK

Introduction

Thank you for choosing the OasisCraft Folding Teak Shower Bench Seat. This manual provides essential information for the safe and proper installation, operation, and maintenance of your new shower bench. Please read these instructions carefully before installation and retain them for future reference.

Safety Information

- **Maximum Weight Capacity:** This shower bench is designed to support a maximum weight of 400 pounds (181 kg). Do not exceed this limit.
- **Proper Installation is Crucial:** The bench **must** be installed into solid wood studs or a reinforced wall structure capable of supporting the weight of the bench and user. **Do not install into drywall with molly bolts or similar anchors alone.** Improper installation can lead to serious injury.
- Ensure all mounting hardware is securely tightened before initial use and periodically check for any loosening.
- Always ensure the bench is fully extended and locked into position before sitting.
- Exercise caution when folding and unfolding the bench to avoid pinching fingers.

Package Contents

Verify that all components are present before beginning installation:

- Folding Teak Shower Bench Seat (1)
- Wall Brackets (2)
- ABS Plating Plastic Bracket Covers (2)
- Stainless Steel Mounting Pins (2)
- Stainless Steel Screws (8)



Image: The OasisCraft Folding Teak Shower Bench Seat with all its components, including the teak seat, two wall brackets, two plastic bracket covers, two mounting pins, and eight stainless steel screws.

Specifications

Feature	Detail
Brand	OasisCraft
Model	B099DGF8TK
Material	Teak Wood, Aluminum, ABS Plastic
Color	Brown
Product Dimensions (D x W x H)	13.4" x 20" x 1.18"

Seat Depth	13.4 inches
Seat Width	20 inches
Maximum Weight Capacity	400 pounds

Setup and Installation

Tools Required: Drill, drill bits, stud finder, level, pencil, screwdriver, silicone sealant (recommended).

1. **Identify Mounting Location:** Use a stud finder to locate two solid wood studs in your desired installation area. The distance between the studs should align with the mounting points on the shower bench brackets. Mark the drilling points with a pencil.
2. **Drill Pilot Holes:** Using an appropriate drill bit for your screws, drill pilot holes at the marked locations. Ensure the holes are level.
3. **Mount Wall Brackets:** Position the aluminum wall brackets over the pilot holes. Secure them firmly to the wall using the provided stainless steel screws. It is highly recommended to apply silicone sealant around the edges of the brackets to prevent moisture intrusion and corrosion.
4. **Attach Seat to Brackets:** Align the teak shower seat with the mounted brackets. Insert the stainless steel mounting pins through the seat's frame and into the brackets. Ensure the pins are fully engaged and secure.
5. **Install Bracket Covers:** Snap the ABS plating plastic bracket covers over the aluminum wall brackets. These covers provide a finished look and additional protection against water.
6. **Test Stability:** Before use, gently apply pressure to the installed bench to confirm it is securely mounted and stable.



Image: The OasisCraft Folding Teak Shower Bench Seat securely installed in a shower, ready for use.



Image: An illustration demonstrating the 400 lbs weight capacity of the shower bench, emphasizing its robust design.

Operating Instructions

The OasisCraft Folding Teak Shower Bench Seat features a convenient fold-down design for space-saving and ease of use.

- **To Unfold:** Gently pull the seat downwards until it locks into the horizontal position. Ensure it is fully extended and stable before sitting.
- **To Fold:** Lift the seat upwards until it rests flush against the wall. This minimizes its profile, making it ideal for smaller spaces or when not in use.



Image: A visual guide demonstrating the shower bench in its folded position against the wall and its open, ready-to-use position.

This versatile bench can be used in various locations beyond the shower, such as a hallway for putting on shoes or any area where temporary seating is beneficial.



Image: The shower bench installed in a hallway, shown in the open position, illustrating its versatility for use outside the shower.



Image: The shower bench installed in a hallway, shown in the folded position, demonstrating its space-saving design.

Maintenance

To ensure the longevity and appearance of your OasisCraft Folding Teak Shower Bench Seat, follow these maintenance guidelines:

- **Cleaning:** The teak wood features a clear, waterproof coating, making it easy to clean. Simply rinse with water and wipe dry with a soft cloth after each use. Avoid abrasive cleaners or harsh chemicals that could damage the finish.
- **Teak Oil Application:** For enhanced protection and to maintain the wood's natural luster, periodic application of teak oil is recommended. Follow the instructions on your chosen teak oil product.
- **Hardware Inspection:** Regularly inspect the stainless steel mounting pins, screws, and aluminum brackets for any signs of corrosion or loosening. Tighten screws as necessary.
- **Bracket Covers:** Ensure the plastic bracket covers remain securely in place to protect the underlying aluminum brackets from direct water exposure.



Image: A close-up view of the teak wood surface, showing water droplets beading on its waterproof finish, highlighting its durability and ease of maintenance.

Troubleshooting

- **Bench feels unstable:**
  - Ensure the bench is fully extended and the mounting pins are correctly seated in the brackets.
  - Verify that all mounting screws are securely tightened.
  - Re-check that the bench was installed into solid wood studs or a properly reinforced wall. If installed into drywall without adequate backing, it must be reinstalled correctly.
- **Difficulty folding/unfolding:**
  - Check for any obstructions around the hinge mechanism.
  - Ensure the mounting pins are not bent or damaged.

- **Signs of corrosion on brackets:**
  - While the brackets are aluminum and the pins/screws are stainless steel, prolonged exposure to moisture without proper sealing can lead to issues. Ensure bracket covers are in place and consider applying silicone sealant around the edges of the covers if not already done.

Warranty and Support

OasisCraft offers a **1-year after-sale warranty** for this folding teak shower seat. If you encounter any issues or have questions regarding your product, please do not hesitate to contact our customer support team.
Our customer service team is available to assist you within 24 hours.
Contact Information: Please refer to the contact details provided on your purchase receipt or the OasisCraft official website for the most current support options.

© 2023 OasisCraft. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B099DGF8TK

More documents and user manuals: **https://manuals.plus/**