

Petra PM-2210

PetraMax Mulch Glue Max Concentrate (32oz) Instruction Manual

This manual provides detailed instructions for the proper use and maintenance of your PetraMax Mulch Glue Max Concentrate.

1. PRODUCT OVERVIEW

PetraMax Mulch Glue Max Concentrate is a professional-grade, non-toxic, water-permeable binder designed to securely hold various landscaping materials in place. It is suitable for garden mulch, wood chips, shells, sand, pine straw, small pebbles, hay, straw, small gravel, and leaf piles. This concentrated formula helps prevent wash-outs from rain and displacement by wind or leaf blowers, reducing the need for constant landscape upkeep.

Key Features

- Holds various landscaping materials (mulch, pebbles, etc.)
- Concentrated formula for maximum value (makes 3x ready-to-use)
- Non-toxic, water-permeable, safe for pets and plants
- Long-lasting coverage (12-24 months)
- Effective on light and heavy materials like gravel and pebbles
- American Family-Owned Company & USA Support

2. SAFETY INFORMATION

Always wear protective gear such as gloves, safety glasses, and protective clothing when handling this product. Use in a well-ventilated area to avoid inhaling fumes. Do not swallow. Avoid direct contact with skin and eyes.

First Aid

- **Skin Contact:** If in contact with skin, remove contaminated clothing and thoroughly rinse the

skin with soap and water.

- **Eye Contact:** Separate the eyelids and rinse with flowing water or physiological saline.
- **Ingestion:** If swallowed, rinse your mouth and do not induce vomiting. If you feel any discomfort, seek medical attention immediately.

KEEP AWAY FROM CHILDREN. KEEP OUT OF REACH OF CHILDREN.

3. PREPARATION AND MIXING

Proper preparation ensures optimal performance and longevity of the mulch glue.

Required Materials

- PetraMax Mulch Glue Max Concentrate
- Water
- Sprayer (PetraTools sprayer recommended for best results)
- Measuring cup/container
- Stirring tool (if mixing in a separate container)
- Protective gear (gloves, safety glasses)

Mixing Instructions

The PetraMax Mulch Glue is a concentrate and must be diluted with water before application.

- For spraying, mix 1 part mulch glue with 1/2 part water.
- For pouring, mix 1 part mulch glue with 1/5 part water.
- Shake well before use to ensure uniformity and prevent nozzle clogging.

Example Coverage (for spraying 1 quart glue + 1/2 quart water): Covers approximately 50 sq. ft. per coat.



MIX & SPRAY

3 EASY STEPS

- 1  | Mix in sprayer
- 2  | Spray
- 3  | Turn & coat again*



*2-3 coats recommended. Must let mulch dry between coats.

A person is shown pouring the concentrated PetraMax Mulch Glue into a sprayer, demonstrating the mixing process before application.

4. APPLICATION GUIDELINES

For best results, apply the mulch glue in completely dry, warm conditions (above 50°F / 10°C) with humidity below 70%. Avoid rain for 48 hours after applying.

Step-by-Step Application

1. **Prepare the Area:** Ensure the base mulch/stones are clean, dry, and free of dust, mud, or oil. Remove any weeds.
2. **Rake/Turn Mulch:** Rake or turn the mulch to ensure it is completely dry before applying. This also helps expose untreated mulch for subsequent coats.
3. **Apply First Coat:** Spray an even, thin coat over the mulch without oversaturating.
4. **Drying Time:** Allow the first coat to dry for at least 24 hours before applying additional coats.
5. **Apply Additional Coats:** For maximum strength and hold, apply 2-3 thin coats. Rake/turn mulch between coats to ensure even coverage. A thick layer may result in white/blue residue.
6. **Final Drying:** Let the treated area dry undisturbed for 48+ hours after the final application.



- 1 **Apply** in completely dry, warm conditions (above 50°F).
- 2 **Rake/turn** mulch and let it dry in sun before applying.
- 3 **Rake/turn** mulch between coats.
- 4 Mulch must be **COMPLETELY** dry before applying.
- 5 Dry conditions for 48+ hours after applying.



5 TIPS FOR SUCCESS

An infographic detailing five key tips for successful application: apply in dry, warm conditions (above 50°F), rake/turn mulch before applying, rake/turn mulch between coats, mulch must be completely dry, and ensure dry conditions for 48+ hours after application.

Coverage

The entire 32oz bottle covers approximately 50 sq. ft. when applied in three coats. Large mulch/bark will require more coats and may have less coverage area.



**50 sq ft
COVERAGE**



**200 sq ft
COVERAGE**

100% SAFE* FOR
PET AND KIDS



*When used as directed



Visual representation of product coverage, indicating that 32oz of PetraMax Mulch Glue can cover 50 sq. ft. for small gravel and 200 sq. ft. for mulch, depending on the material and number of coats.

Video Demonstration

Your browser does not support the video tag.

Official product video demonstrating the application of PetraTools Max Mulch Glue, showing how it binds mulch and prevents displacement.

5. MAINTENANCE AND STORAGE

Tool Cleaning

Rinse tools with flowing water immediately after use to prevent nozzle blockage and residue buildup.

Product Storage

Store in a sealed container, away from heat. Do not allow the product to freeze.

6. TROUBLESHOOTING

Common Issues and Solutions

- **Mulch Not Holding / Moves Easily:**
 - Ensure the mulch was completely dry before application.
 - Apply 2-3 thin coats for maximum strength, allowing 24 hours drying time between coats.
 - Ensure sufficient product was used for the material type (e.g., heavier materials like gravel may require more product).
- **White/Blue Residue After Drying:**
 - This can occur if a thick layer is applied. Apply thin, even coats.
 - Ensure proper dilution ratio.
- **Nozzle Clogging:**
 - Shake the product well before use.
 - Rinse tools immediately after use.
 - Ensure proper dilution to prevent the concentrate from being too thick.

For best results, please contact us for guidance before starting the project if you have any questions.

7. SPECIFICATIONS

Feature	Detail
Brand	Petra
Material	Resin
Item Form	Liquid
Special Feature	Pet Friendly
Color	Clear Drying
Item Volume	32 Fluid Ounces
Viscosity	Medium
Full Cure Time	12 Months
Water Resistance Level	Water Resistant
UPC	850029123170
Model Number	PM-2210

Feature	Detail
Item Weight	2.48 pounds
Package Dimensions	8.74 x 5.55 x 3.07 inches

8. WARRANTY AND SUPPORT




PetraTools is an American family-owned company based in Carlisle, Pennsylvania. All PetraTools products come with a 100% satisfaction guarantee.




Customer Service

For any questions or concerns, contact the friendly USA customer service team.

- **Phone:** (800) 613-6889 (Mon - Fri | 9am - 6pm EST)
- **Website:** Visit the [Petra Store](#) for more information.

Related Documents - PM-2210

 <p>Owners Manual Installation - Operation - Maintenance</p> <p>PizzaMaster ELECTRIC MODULAR OVENS</p> <p>Models: 700, 800, 900</p> <p>CE CB</p>	<p>PizzaMaster Electric Modular Ovens: Owners Manual & Warranty Information</p> <p>Comprehensive owners manual and manufacturer warranty statement for PizzaMaster electric modular ovens, covering installation, operation, maintenance, troubleshooting, and technical specifications for models 700, 800, and 900 series.</p>
 <p>2146 ROLLER STAND ROLLENSTANDER SERVANTE À ROULEAU</p> <p>JET CE UK</p>	<p>JET 2146 Roller Stand - Parts Manual</p> <p>Official manual for the JET 2146 Roller Stand, detailing parts and assembly. Includes multilingual support information and product specifications.</p>
 <p>trend</p> <p>AIRPRO MAX USER INSTRUCTIONS</p> <p>FOR MODEL 40000</p>	<p>Trend AirPro Max Powered Air Purifying Respirator User Manual</p> <p>Comprehensive user guide for the Trend AirPro Max PAPR system, detailing setup, operation, maintenance, safety precautions, troubleshooting, and technical specifications.</p>

	<p>Hanshow Polaris Pro-Q Series Product Manual - Features, Specifications, and Usage</p> <p>Comprehensive product manual for Hanshow Polaris Pro-Q and Polaris Max series Electronic Shelf Labels (ESLs), detailing features, specifications, application scenarios, precautions, and regulatory compliance.</p>
	<p>Olympus Photomicrography Group: Advanced Camera Systems and Accessories</p> <p>Explore the comprehensive range of Olympus photomicrography equipment, including manual and automatic exposure bodies, adapters, filters, eyepieces, and accessories for professional photographic applications.</p>
	<p>Petermann Sliding Mats: User Manual and Technical Specifications</p> <p>Comprehensive guide to Petermann Sliding Mats, covering general information, safety, application, cleaning, technical data, warranty, and disposal. Designed to reduce strain for caregivers and improve patient comfort during transfers.</p>