



[Manuals.plus](#) /

› [PelIKing](#) /

› PelIKing Quick Release Base Tripod Adapter Mount User Manual

PelIKing 709226438450

PelIKing Quick Release Base Tripod Adapter Mount User Manual

MODEL: 709226438450

Introduction

The PelIKing Quick Release Base Tripod Adapter Mount is designed to provide a fast and secure way to attach your action camera to various accessories. Made from durable aluminum, this adapter ensures stability and quick transitions between different mounting setups, enhancing your filming experience. It is compatible with a wide range of sports cameras including GoPro Hero series, Insta360 One R, DJI Osmo Action, and Akaso Sports Cameras.



Image: The PellKing Quick Release Base Tripod Adapter Mount, showcasing the aluminum base, plastic quick release buckle, and a thumb screw.

Package Contents

Please verify that all items listed below are included in your package:

- 1 × Aluminum Quick Release Adapter Base
- 1 × Quick Release Buckle (plastic)
- 1 × Thumb Screw

Package List



1 × Aluminum quick release base

1 × Quick release buckle

1 × Thumbscrews

Image: A clear display of the three components included in the package: the aluminum quick release base, the plastic quick release buckle, and the thumb screw.

Setup

Follow these steps to properly set up your Peliking Quick Release Base Tripod Adapter Mount:

1. Attach the quick release buckle to your camera's mounting fingers using the provided thumb screw. Ensure it is tightened securely.
2. Align one side of the quick release buckle with the corresponding slot on the aluminum quick release adapter base.
3. Snap the first side into place, then rotate the quick release buckle to snap the other side into the base. This ensures a tight and stable connection.
4. Once the buckle is fully seated, the camera is securely attached to the adapter base.
5. Attach the aluminum quick release adapter base to your desired accessory (e.g., tripod, selfie stick) using its standard mounting point.

Installation Tips

This quick release base is stuck especially tight, even when used on a motorcycle will not shake, so you need to install the correct way



1: First snap into the base of a foot

2: Rotate the base to snap into the other foot

Image: An illustrative diagram demonstrating the two-step process for attaching the quick release buckle to the aluminum base: first snapping in one foot, then rotating to secure the second foot.

Installation Video Guide

Video: This video demonstrates the quick release adapter's functionality, showing how to attach and detach a GoPro camera from a selfie stick using the quick release mechanism. It highlights the ease of switching between accessories.

Operating the Quick Release System

The quick release system allows for rapid attachment and detachment of your camera from various mounts. To detach, simply press the release tabs on the quick release buckle and slide the camera off the adapter base. To reattach, align the buckle with the base and snap it firmly into place until you hear a click, ensuring a secure connection.

Compatibility

This quick release base is designed for broad compatibility with action camera accessories that utilize the standard GoPro-style mounting fingers.

Tripod compatible



Image: The quick release base mounted on a mini tripod, demonstrating tripod compatibility.

Selfie Stick Compatible



Image: The quick release base mounted on a selfie stick, demonstrating selfie stick compatibility.

Compatible with GoPro original base



Image: The quick release base shown alongside a GoPro original base, highlighting their compatibility.



Image: A GoPro Hero 9 camera securely attached to a tripod via the Pelikn Quick Release Base, ready for use.



Image: A DJI Osmo Action camera attached to a selfie stick using the PellKing Quick Release Base, demonstrating its versatility.

Maintenance

To ensure the longevity and optimal performance of your PellKing Quick Release Base, follow these simple maintenance guidelines:

- **Cleaning:** Wipe the aluminum base and plastic buckle with a soft, damp cloth to remove dirt or debris. Avoid using harsh chemicals or abrasive materials.
- **Storage:** Store the mount in a dry, cool place away from direct sunlight when not in use.
- **Inspection:** Periodically inspect the quick release mechanism and thumb screw for any signs of wear or damage. Ensure the screw threads are clean and free of obstructions.

Troubleshooting

If you encounter any issues with your quick release base, refer to the following common problems and solutions:

- Issue:** The quick release buckle feels too tight when attaching to the base.
Solution: The aluminum base is designed for a very secure fit, especially for high-vibration environments like motorcycles. Ensure you are snapping in one side first and then rotating the other side into place as shown in the setup instructions. If it remains excessively tight, a small amount of lubrication (e.g., silicone grease) on the plastic buckle's feet might help, or gently filing the edges of the plastic buckle (not the aluminum base) if necessary, though this is rarely required.
- Issue:** The camera feels loose or wobbly after attachment.
Solution: Ensure the quick release buckle is fully seated and clicked into the aluminum base. Also, check that the thumb screw attaching the buckle to your camera is tightened securely.
- Issue:** Difficulty detaching the camera.
Solution: Firmly press both release tabs on the quick release buckle simultaneously while sliding the camera off the base. Avoid forcing the detachment.

Specifications

Feature	Detail
Product Dimensions	1.77 x 0.79 x 1.1 inches
Item Weight	0.705 ounces
Material	CNC Aluminum Alloy (Base), Plastic (Buckle)
Color	Black
Special Features	Quick Release Mechanism
Compatible Devices	GoPro Hero 13/12/11/10/9/8/7/6/5/4 Session Max, Insta360 One R, DJI Osmo Action 5/4/3/2, Akaso Sports Camera, and more.
Mounting Type	Tripod (GoPro-style mount)

Quick Release Base

Material: CNC aluminum alloy

Weight: 18G

Size: 45*35*28mm



Image: A detailed view of the quick release base, indicating its material (CNC aluminum alloy), weight (18G), and size (45*35*28mm).

Warranty and Support

For warranty information and customer support, please refer to the documentation included with your product or visit the official PellKing website. You can also visit the [PellKing Store on Amazon](#) for additional product information and assistance.