

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

MOREL Maximo 6 MKII

Morel Maximo 6 MK II Maximo Series 6-1/2" Component Speaker System User Manual

Model: Maximo 6 MKII | Brand: MOREL

1. INTRODUCTION AND OVERVIEW

The Morel Maximo 6 MK II is a high-quality 6-1/2" component speaker system designed to deliver superior audio performance in automotive applications. This system is engineered to provide detailed sound clarity and robust output, making it an excellent choice for audio enthusiasts seeking an enhanced in-car listening experience. Its design focuses on efficiency and sound fidelity, ensuring compatibility with a wide range of audio setups.



Figure 1.1: Complete Morel Maximo 6 MK II Component Speaker System, showing two woofers and two tweeters.

What's Included

Your Morel Maximo 6 MK II Component Speaker System package includes the following components:

- Two (2) 6-1/2" Woofers
- Two (2) Tweeters
- One (1) Warranty Card
- Integrated Crossovers (part of the system design)

2. SETUP AND INSTALLATION

Proper installation is crucial for optimal performance of your Morel Maximo 6 MK II speaker system. It is highly recommended that installation be performed by a qualified car audio professional. Incorrect wiring or mounting can lead to damage to the speakers or your vehicle's electrical system.

2.1 Woofer Installation

The 6-1/2" woofers are designed for flush mounting in standard speaker locations within your vehicle's doors or kick panels. Ensure the mounting surface is rigid and free from obstructions. Use appropriate mounting hardware to secure the woofers firmly.



Figure 2.1: Detailed view of the Morel Maximo 6 MK II woofer, showing its robust construction.

2.2 Tweeter Installation

The tweeters can be installed in various locations to optimize sound staging, such as dashboard corners, A-pillars, or door panels. Consider the listening position and vehicle acoustics when choosing the mounting location. The system includes tweeters designed for flexible mounting options.



Figure 2.2: The Morel Maximo 6 MK II tweeter, designed for clear high-frequency reproduction.

2.3 Wiring and Crossover Integration

Connect the woofers and tweeters to your amplifier or head unit according to the wiring diagram provided with your amplifier. The Maximo 6 MK II features integrated crossovers, simplifying the wiring process by directing appropriate frequencies to each speaker component. Ensure all connections are secure and properly insulated to prevent short circuits and signal loss. Pay attention to speaker polarity (+/-) for correct phase alignment.

The system is designed for a 4 Ohm impedance. Ensure your amplifier is stable at this impedance. The speakers can handle up to 90 W RMS (180 W Peak) power. Match your amplifier's output to these specifications for optimal performance and longevity.

3. OPERATING YOUR SPEAKER SYSTEM

Once installed, your Morel Maximo 6 MK II speaker system is ready for operation. The system's high sensitivity (92 dB) allows it to produce significant volume even with modest power sources, such as a factory head unit. For the best audio experience, consider pairing these speakers with a dedicated amplifier that can deliver clean power within the recommended range.

3.1 Initial Power-Up and Sound Adjustment

1. Ensure all connections are secure and the vehicle's audio system is off.
2. Turn on your head unit or amplifier at a low volume level.
3. Gradually increase the volume, listening for clear, balanced sound from all speakers.
4. Adjust the bass, treble, and balance settings on your head unit or amplifier to suit your personal preference. Avoid excessive bass or treble boost, which can lead to distortion or speaker damage.
5. If using an external amplifier, refer to its manual for gain setting and crossover frequency adjustments.

3.2 Recommended Usage

To ensure the longevity and optimal performance of your speakers:

- Avoid playing music at excessively high volumes for prolonged periods, especially if distortion is audible.
- Ensure your amplifier is not clipping (sending a distorted signal), as this is a common cause of speaker damage.
- Protect speakers from direct sunlight and extreme temperatures, which can degrade materials over time.

4. MAINTENANCE

The Morel Maximo 6 MK II speaker system requires minimal maintenance to ensure long-term performance.

- **Cleaning:** Use a soft, dry cloth to gently wipe dust from the speaker cones and surrounds. Avoid using harsh chemicals or abrasive cleaners, which can damage the speaker materials.
- **Inspection:** Periodically check speaker mounts and wiring connections to ensure they remain secure. Loose connections can lead to intermittent sound or reduced performance.
- **Environmental Protection:** While designed for automotive use, extreme moisture or direct water exposure should be avoided. The speakers are not waterproof.

5. TROUBLESHOOTING

If you experience issues with your Morel Maximo 6 MK II speaker system, refer to the following common troubleshooting steps:

Problem	Possible Cause	Solution
No sound from one or more speakers	Loose or disconnected wiring Incorrect amplifier settings Damaged speaker or amplifier	Check all speaker wire connections at both the speaker and amplifier/head unit. Verify amplifier is powered on and settings (gain, mute) are correct. Test with another known-good speaker or amplifier if possible.
Distorted or unclear sound	Amplifier clipping (overdriving) Incorrect gain settings Loose speaker mounting Damaged speaker cone/surround	Reduce volume or amplifier gain. Ensure gain is set correctly, not too high. Check speaker mounting screws for tightness. Visually inspect speaker for physical damage.

Problem	Possible Cause	Solution
Weak or no bass	Incorrect wiring polarity Insufficient amplifier power Poor speaker enclosure/mounting	Verify correct speaker polarity (+ to + and - to -). Ensure amplifier provides adequate power for the woofers. Confirm woofers are securely mounted in a sealed environment (e.g., car door).

If these steps do not resolve the issue, contact a professional car audio technician or Morel customer support for further assistance.

6. SPECIFICATIONS

The following are the technical specifications for the Morel Maximo 6 MK II Component Speaker System:

- **Configuration:** 2-way Split system
- **Driver Size:** 165mm (Woofer), 69mm (Tweeter)
- **Frequency Response:** 60 Hz - 22,000 Hz
- **Crossover:** Integrated
- **Power Handling:** 90 W RMS / 180 W Peak
- **Sensitivity:** 92 dB
- **Impedance:** 4 Ohm
- **Mounting Type:** Flush Mount
- **Material:** ABS
- **Product Dimensions:** 40D x 22W x 9H Centimeters (approximate overall package dimensions)
- **Item Weight:** 2 Kilograms
- **Included Components:** 2 Speakers, 2 Tweeter, 1 Warranty Card


7. WARRANTY AND SUPPORT

The Morel Maximo 6 MK II Component Speaker System comes with a Limited Warranty. Please refer to the included Warranty Card for specific terms, conditions, and duration of the warranty coverage.

For technical support, warranty claims, or any product-related inquiries, please contact Morel customer service or your authorized Morel dealer. Keep your proof of purchase for warranty validation.

For more information, you may visit the official Morel website or contact their support channels as listed on the warranty card or product packaging.

© 2023 MOREL. All rights reserved. Specifications are subject to change without notice.



[\[pdf\]](#) User Manual

Maximo 6 MKII user manual A5 RUS indd fubiz Руководство пользователя 24 mar 2023 — Благодарим за выбор продукции Morel! Установка автомобильной акустической системы требует наличия у установщика известного опыта работы с механическими 1679584130444 maximo mkii a5 rus mms store ru attachments prod file3510 |||

6 MKII 2- Morel , , , , Morel . . . , . - X2 X2 X2 - X2 X4 X2 X2 X2 X1 X8 X8 , , RMS , , , - , Maximo 6 MKII 94 4 90 180 60-22000 25 25 4000 ...

lang:it score:37 filesize: 1.8 M page_count: 6 document date: 2023-03-23



[\[pdf\]](#) User Manual

Maximo Coax 6 user manual A5 RUS indd fubiz Инструкция пользователя MOREL MAXIMO COAX MKII Купить 1679583742932 maximo coax a5 rus mms store ru attachments prod file3511 |||

6 coax MKII Morel , , , , Morel , , , . : 8 495 788-17-01 -: mms-store.ru : Morel Maximo 6 MKII -: : 3 : 17 , , 70400, : 127220, , , . 1 ...

lang:it score:30 filesize: 1.68 M page_count: 4 document date: 2023-03-23