

TIMCO 434777

TIMCO Flush Hinges (105) Steel Silver - 75 x 51 Instruction Manual

PRODUCT OVERVIEW

The TIMCO Flush Hinges (105) are designed for the quick and easy installation of light internal doors or cabinets. Constructed from steel with a silver finish, these hinges eliminate the need for cutting into the door or frame, making installation straightforward. Their design ensures the hinge knuckle is flush with the back of the hinge leaf, making them an ideal choice for lay-over doors.

- Ideal for cabinets and wardrobes.
- Quick fitting with no mortising required.
- Suitable for lay-over doors.

PACKAGE CONTENTS

Each package contains one TIMCO Flush Hinge (105) Steel Silver - 75 x 51. Please ensure all components are present and undamaged upon opening.



This image displays a single TIMCO Flush Hinge, model 105, constructed from steel with a silver finish. The hinge is designed for surface mounting, eliminating the need for mortising. It features multiple pre-drilled holes for screw attachment to a door or cabinet and its frame. The hinge knuckle is visible, indicating its pivot point.

SETUP AND INSTALLATION

Follow these steps for proper installation of your TIMCO Flush Hinges. No specialized tools are required beyond a screwdriver and appropriate fasteners (not included).

1. **Prepare the Surface:** Ensure the surfaces of the door/cabinet and the frame where the hinge will be mounted are clean, dry, and free from obstructions.
2. **Position the Hinge:** Place the hinge in the desired position on the edge of the door or cabinet. The 'flush' design means the hinge will sit directly on the surface without requiring a cut-out. Ensure the hinge is aligned correctly for smooth operation.
3. **Mark Screw Holes:** Using a pencil or a small awl, mark the positions of the screw holes through the pre-drilled holes on the hinge leaf onto the door/cabinet.
4. **Attach to Door/Cabinet:** Secure one leaf of the hinge to the door or cabinet using appropriate screws. Do not overtighten.
5. **Align and Attach to Frame:** Position the door/cabinet against the frame, ensuring proper alignment and spacing. Mark the screw holes for the second hinge leaf onto the frame.
6. **Final Attachment:** Secure the second hinge leaf to the frame using appropriate screws. Test the door/cabinet for smooth opening and closing. Adjust screw tightness if necessary.

OPERATION

Once installed, the TIMCO Flush Hinges allow for the smooth pivoting of doors or cabinet fronts. The hinge is designed for standard opening and closing motions. Avoid forcing the door or cabinet beyond its natural range of motion to prevent damage to the hinge or mounting surface.

MAINTENANCE

To ensure the longevity and smooth operation of your TIMCO Flush Hinges, consider the following maintenance tips:

- **Cleaning:** Wipe the hinges periodically with a soft, dry cloth to remove dust and debris. For stubborn dirt, a slightly damp cloth can be used, followed by immediate drying. Avoid abrasive cleaners or harsh chemicals.
- **Lubrication:** If the hinges begin to squeak or feel stiff, apply a small amount of silicone-based lubricant to the hinge pin. Wipe away any excess lubricant.
- **Tighten Screws:** Periodically check and tighten any loose mounting screws to maintain stability and prevent sagging. Do not overtighten.

TROUBLESHOOTING

Here are solutions to common issues you might encounter:

- **Hinge Squeaks:** Apply a small amount of lubricant (e.g., silicone spray) to the hinge pin. Open and close the door/cabinet several times to distribute the lubricant.
- **Door/Cabinet Sags or is Loose:** Check all mounting screws. If they are loose, tighten them carefully. If the screw holes are stripped, consider using longer screws or wood filler to secure them.
- **Door/Cabinet Does Not Close Properly:** Verify that the hinges are aligned correctly and that no debris is obstructing the closing path. Ensure all screws are tightened appropriately.





SPECIFICATIONS

Manufacturer	TIMCO
Part Number	434777
Item Model Number	434777
Product Dimensions	6.69 x 3.62 x 0.39 inches
Item Weight	3.52 ounces
Material	Steel
Finish Type	Silver
Color	Black (Note: Product is Silver, 'Color' specification might refer to packaging or a variant)
Mounting Type	Door Mount
Item Package Quantity	1
Batteries Required?	No

SUPPORT INFORMATION

For further assistance or inquiries regarding your TIMCO Flush Hinges, please refer to the retailer where the product was purchased. Keep your purchase receipt and product model number (434777) handy for any support requests.

Related Documents - 434777

	<p>Timco Ball Joint Separator Tool Set - User Guide</p> <p>A user guide for the Timco ball joint separator tool set, including instructions for use, safety precautions, and product specifications. The set includes forged carbon steel forks for manual and air hammer operation.</p>
	<p>Timco Ball Joint Separator Tool Set - User Guide</p> <p>A user guide for the Timco ball joint separator tool set, including instructions for use, safety precautions, and product specifications. The set includes forged carbon steel forks for manual and air hammer operation.</p>
	<p>Timco Ball Joint Separator Set - User Guide and Specifications</p> <p>Comprehensive guide to the Timco ball joint separator set, detailing its intended use, safety instructions, and specifications for various automotive applications. Includes information for Ford, Volkswagen, Mercedes, Audi, Skoda, Citroen, Peugeot, Renault, Fiat, Mazda, and Toyota vehicles.</p>
	<p>Timco S-85A Petrooil Heater: Käyttöohje ja Turvallisuusopas</p> <p>Kattava käyttöohje Timco S-85A 2,4kW petroolilämmittimelle. Opi turvallinen käyttö, sytytys, liekin säätö ja huolto varmistaaksesi tehokkaan ja turvallisen lämmityksen. Sisältää tärkeät turvallisuusvaroitukset ja tekniset tiedot.</p>



[pdf] Accessories Borchure

Brochure Key Safe key safe b059904 1 checkout mkm content products 25924 |||

SECURITY IRONMONGERY New New Hinges - Page 199 - Intumescent Door Seals

- Page 207 - New Inte ... sheltered areas Zinc CR 2 Product L x W Code mm 434451

38 x 28 434056 50 x 38.5 434900 63 x 37 **434777** 75 x 51 TYPE - IDH Pack Carton

Qty Qty 1 Pair 50 1 Pair 50 1 Pair 30 1 Pair 30 SUB TYPE - ID...

lang:en score:8 filesize: 2.53 M page_count: 20 document date: 2020-07-27