

[Manuals.plus](#) /

› [Pro Chaser](#) /

› Pro Chaser Tune-Up Kit Instruction Manual for Craftsman Lawn Tractors (YT3000, LT2000, T2200, YS4500, YTS3000, T1400)

Pro Chaser Tune Up Kit

Pro Chaser Tune-Up Kit Instruction Manual

For Craftsman Lawn Tractors: YT3000, LT2000, T2200, YS4500, YTS3000, T1400 (42" & 46" Decks)

1. PRODUCT OVERVIEW

This Pro Chaser Tune-Up Kit is designed to provide essential replacement components for maintaining the performance of your Craftsman lawn tractor. Regular replacement of these parts ensures optimal engine efficiency and longevity.

1.1 Compatibility

This kit is compatible with the following Craftsman lawn tractor models, typically equipped with 19.5hp, 20hp, or 21hp engines and 42" or 46" cutting decks:

- Craftsman YT3000
- Craftsman LT2000
- Craftsman YS4500
- Craftsman YTS3000
- Craftsman T1400
- Craftsman T2200

1.2 Package Contents

The Pro Chaser Tune-Up Kit includes the following components:

- 1 x Air Filter (125mm / 5")
- 1 x Pre-filter
- 1 x Oil Filter
- 1 x Fuel Filter
- 2 x Clamp
- 2 x Spark Plug



Figure 1: Complete contents of the Pro Chaser Tune-Up Kit.

2. INSTALLATION GUIDE

Before beginning any installation, ensure your lawn tractor is turned off, the engine is cool, and the spark plug wire is disconnected to prevent accidental starting. Refer to your tractor's owner's manual for specific component locations and safety precautions.

2.1 Air Filter Installation

1. Locate the air filter housing on your engine.
2. Open the housing and carefully remove the old air filter and pre-filter.
3. Clean any debris from inside the air filter housing.
4. Install the new pre-filter over the new air filter.
5. Insert the assembled air filter and pre-filter into the housing, ensuring a snug fit.
6. Close and secure the air filter housing.



Figure 2: Air filter dimensions (125mm height, 74mm diameter).



Figure 3: Top view of the air filter.



Figure 4: Side view of the air filter with pre-filter.



Figure 5: Comparison of air filter sizes. Ensure your original filter matches the 125mm height.

2.2 Oil Filter Installation

1. Place a drain pan under the oil filter.
2. Remove the old oil filter using an oil filter wrench.
3. Apply a thin film of new engine oil to the gasket of the new oil filter.
4. Screw on the new oil filter by hand until the gasket makes contact with the engine.
5. Tighten the filter an additional 1/2 to 3/4 turn as specified by your tractor's manual. Do not overtighten.
6. Check for leaks after running the engine for a few minutes.

Distinguish between similar air filters

Please check the measurements of your original air filter before ordering

We are selling
You are buying

Listed in **another** page
Scroll down for buying link



Figure 6: Oil filter dimensions (51mm height, 78mm diameter).



Figure 7: Side view of the oil filter.

2.3 Fuel Filter Installation

1. Locate the fuel filter in the fuel line.
2. Use the provided clamps to secure the fuel line on both sides of the old filter to prevent fuel leakage.
3. Remove the old fuel filter and replace it with the new one, ensuring the flow direction arrow (if present) points towards the engine.

4. Secure the fuel lines with the new clamps.
5. Check for leaks after starting the engine.



Figure 8: Fuel filter dimensions.

2.4 Spark Plug Installation

1. Remove the spark plug wire from the old spark plug.
2. Use a spark plug wrench to remove the old spark plug.
3. Inspect the new spark plug for proper gap (refer to your engine manual for specifications).
4. Thread the new spark plug into the engine by hand to prevent cross-threading.
5. Tighten the spark plug with a wrench, typically 1/4 to 1/2 turn after finger-tight, or to the torque specified in your engine manual.
6. Reconnect the spark plug wire.

3. OPERATING CONSIDERATIONS

After completing the tune-up, ensure all components are securely installed and all fluids (oil, fuel) are at appropriate levels. Start the engine and allow it to run for a few minutes, checking for any unusual noises, leaks, or warning lights. A properly tuned engine will run smoother and more efficiently.

4. MAINTENANCE

Regular maintenance is crucial for the longevity and performance of your lawn tractor. The components in this kit are designed for periodic replacement.

- **Air Filter:** Inspect the air filter and pre-filter regularly (e.g., every 25 hours of operation or annually). Replace if dirty or damaged. Operating with a clogged air filter can reduce engine power and increase fuel consumption.
- **Oil Filter:** Replace the oil filter every time you change the engine oil, typically every 50 hours of operation or annually, whichever comes first.
- **Fuel Filter:** Replace the fuel filter annually or if you notice fuel delivery issues or contamination.
- **Spark Plugs:** Inspect spark plugs annually. Replace if electrodes are worn, fouled, or if engine performance is degraded.

5. TROUBLESHOOTING

If you encounter issues after installing the tune-up kit, consider the following common troubleshooting steps:

- **Engine not starting or running rough:**
 - Check spark plug connections and ensure they are properly tightened.
 - Verify fuel filter orientation and ensure no air bubbles are in the fuel line.
 - Ensure the air filter housing is sealed correctly.

- **Oil leaks:**
 - Confirm the oil filter is tightened correctly (not overtightened or undertightened).
 - Ensure the oil filter gasket is properly seated and not damaged.
- **Reduced engine power:**
 - A clogged air filter can restrict airflow; ensure it is clean and properly installed.
 - A faulty spark plug can lead to misfires and reduced power.

If problems persist, consult your Craftsman lawn tractor's owner's manual or seek assistance from a qualified service technician.

6. PRODUCT VIDEO


Video 1: Overview of the Pro Chaser Tune-Up Kit components.

7. SPECIFICATIONS

Feature	Detail
Brand	Pro Chaser
Product Grade	Tuning
Vehicle Service Type	Tractor
Material	Steel, Paper/Synthetic Fibers
Air Filter Dimensions	125mm (4.92") Height, 74mm (2.94") Diameter
Oil Filter Dimensions	51mm (2.04") Height, 78mm (3.09") Diameter, M14x1.5 Thread Size
Item Weight (Kit)	0.38 Kilograms (approx. 13.4 ounces)
Manufacturer Part Number	Filter (Generic for kit)
UPC	709345780409

Pro Chaser © 2026. All rights reserved.

For further assistance, please contact Pro Chaser customer support.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question