DIYElectronic EPM3064ATC44-10N

User Manual

EPM3064ATC44-10N EPM3064ATC44 QFP44

Model: EPM3064ATC44-10N | Brand: DIYElectronic

1. Introduction

This manual provides essential information for the proper use, installation, and handling of the **DIYElectronic EPM3064ATC44-10N EPM3064ATC44 QFP44** integrated circuit. Please read this manual thoroughly before attempting to use or integrate this component into any electronic system.

The EPM3064ATC44-10N is a high-performance, low-cost, high-density programmable logic device (PLD) from the MAX 3000A family, designed for general-purpose logic integration. Its QFP44 package makes it suitable for surface-mount applications.

2. Safety Information

Always observe the following safety precautions when working with electronic components:

- **Electrostatic Discharge (ESD) Precautions:** This device is sensitive to ESD. Always handle the component in an ESD-safe environment, using grounding straps, ESD mats, and proper tools.
- **Power Supply:** Ensure the power supply voltage and current ratings are within the specified limits for the EPM3064ATC44-10N to prevent damage. Refer to the device datasheet for detailed electrical characteristics.
- **Soldering:** When soldering, use appropriate ventilation and follow safety guidelines for soldering fumes. Avoid excessive heat that could damage the component.
- **Professional Use:** This component is intended for use by qualified electronics professionals or hobbyists with sufficient knowledge of electronic circuit design and assembly.
- **Disposal:** Dispose of electronic components responsibly according to local regulations.

3. Package Contents

Your package should contain the following item:

- 1 x EPM3064ATC44-10N EPM3064ATC44 QFP44 Integrated Circuit




Figure 1: Top and bottom view of the EPM3064ATC44-10N QFP44 integrated circuit. The top view shows the flat black package with pins extending from all four sides. The bottom view reveals the exposed thermal pad in the center and the array of pins.

4. Setup and Installation

The EPM3064ATC44-10N is a surface-mount component (QFP44 package) and requires careful handling and soldering for proper installation.

1. **Prepare the PCB:** Ensure your Printed Circuit Board (PCB) is clean and has the correct footprint for a QFP44 package.
2. **ESD Protection:** Before handling the IC, ensure you are properly grounded to prevent ESD damage.
3. **Component Placement:** Carefully align the IC with the pads on the PCB. Pay attention to the pin 1 indicator (usually a dot or notch on the package) to ensure correct orientation.
4. **Soldering:**
    - Use appropriate soldering techniques for QFP packages, such as reflow soldering or drag soldering.

    - Ensure proper temperature profiles for reflow soldering to avoid overheating the component.
    - For manual soldering, use a fine-tip soldering iron and flux to ensure good solder joints without bridging pins.
5. **Inspection:** After soldering, visually inspect all pins for proper solder joints, ensuring no shorts or open circuits.

5. Operating Principles and Programming

The EPM3064ATC44-10N is a programmable logic device. Its operation is defined by the logic design programmed into it.

- **Design Software:** Use Altera's Quartus II software (or compatible design tools) to create and compile your logic design.
- **Programming:** The device is typically programmed via a JTAG (Joint Test Action Group) interface. Connect a compatible JTAG programmer (e.g., USB Blaster) to the JTAG pins on your PCB.
- **Power-Up Sequence:** Refer to the official Altera (now Intel FPGA) datasheet for the recommended power-up sequence to ensure stable operation and prevent latch-up.
- **Input/Output (I/O) Configuration:** Configure the I/O pins according to your design requirements, respecting voltage levels and current limits.
- **Clocking:** Provide a stable and clean clock signal as required by your logic design.

Note: Detailed programming and design guidelines are beyond the scope of this basic manual. Please consult the official Altera MAX 3000A device handbook and datasheets for comprehensive technical information.

6. Maintenance and Care

The EPM3064ATC44-10N is a robust electronic component, but proper care ensures its longevity and reliable performance.

- **Storage:** Store unused components in their original ESD-safe packaging in a dry, temperature-controlled environment.
- **Cleaning:** If cleaning is necessary, use isopropyl alcohol and a soft brush or lint-free cloth. Avoid harsh chemicals or abrasive materials.
- **Physical Damage:** Avoid bending pins or subjecting the component to physical shock.
- **Thermal Management:** Ensure adequate heat dissipation in your circuit design, especially if the device is operating at higher frequencies or driving significant loads.

7. Troubleshooting

If you encounter issues with the EPM3064ATC44-10N, consider the following common troubleshooting steps:

Problem	Possible Cause	Solution
Device not recognized by programmer	Incorrect JTAG connection; Power supply issue; Damaged device.	Verify JTAG pin connections and cable. Check power supply voltage. Inspect device for physical damage.
Logic not functioning as expected	Incorrect programming; Design error; I/O configuration issue.	Re-verify your logic design and programming file. Check I/O pin assignments and voltage levels. Use a logic analyzer for debugging.

Problem	Possible Cause	Solution
Device overheating	Excessive current draw; Inadequate heat dissipation.	Check power supply and current consumption. Ensure proper thermal management (e.g., heatsink if necessary, adequate airflow).
Intermittent operation	Poor solder joints; Noise on power lines; ESD damage.	Inspect solder joints. Add decoupling capacitors near the device. Ensure proper ESD handling.

8. Specifications

Feature	Detail
Model Number	EPM3064ATC44-10N
Package Type	QFP44 (Quad Flat Package, 44 pins)
Brand	DIYElectronic
ASIN	B09LQ64T75
Manufacturer	DIYElectronic
Date First Available	November 12, 2021
Device Family	MAX 3000A (CPLD)
Logic Elements	64 (refer to datasheet for exact configuration)
Operating Voltage	Refer to official datasheet for specific voltage ranges (typically 3.3V or 5V compatible)

9. Warranty and Support

As an electronic component, the EPM3064ATC44-10N is typically covered by the standard warranty provided by the reseller or manufacturer at the time of purchase. Please retain your proof of purchase for any warranty claims.
For technical support, detailed datasheets, application notes, and programming guides, please refer to the official documentation provided by the original manufacturer (Altera, now Intel FPGA) or contact your component supplier.
For general inquiries regarding your purchase, please contact the seller:Obelia~s.

© 2023 DIYElectronic. All rights reserved.
This manual is for informational purposes only. Specifications are subject to change without notice.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question