Manuals+
Q & A | Deep Search | Upload

Vente-unique ADELMO

EXPERTLAND ADELMO Galvanized Steel Garden Shed, Wood Effect Grey, 10.98 m² User Manual

Brand: Vente-unique | Model: ADELMO

1. Introduction

This manual provides essential information for the safe and efficient assembly, operation, and maintenance of your Vente-unique EXPERTLAND ADELMO Galvanized Steel Garden Shed. Please read these instructions thoroughly before beginning assembly or use. Retain this manual for future reference.

2. Safety Information

General Safety Warnings:

- Always wear appropriate personal protective equipment (PPE) during assembly, including gloves and eye protection.
- Ensure the assembly area is clear of obstructions and children.
- Do not attempt to assemble the shed in strong winds or adverse weather conditions.
- Verify all parts are present and undamaged before starting assembly. Contact customer support immediately if any parts are missing or damaged.
- Securely anchor the shed to a level, stable foundation to prevent tipping or movement.
- Keep all sharp edges and small parts away from children.
- Do not store flammable liquids or hazardous materials inside the shed without proper ventilation and safety precautions.

3. Product Features

The EXPERTLAND ADELMO garden shed is designed for outdoor storage, offering durability and functionality. Key features include:

- **Material:** Galvanized steel with a wood-effect finish for enhanced durability and aesthetic appeal.
- **Doors:** Double sliding doors for convenient access and space-saving operation.
- **Ventilation:** Integrated ventilation grilles to ensure air circulation and reduce condensation, keeping stored items dry.
- **Window:** A PVC window (48 x 35 cm) provides natural light inside the shed.
- **Resistance:** Water-resistant construction.

Figure 3.1: Exterior view of the EXPERTLAND ADELMO garden shed.

Figure 3.2: Side view showing the integrated PVC window and wood-effect panels.

4. Specifications

Attribute	Value
Model	ADELMO
Exterior Dimensions (L x D x H)	340 cm x 323 cm x 226 cm (10.98 m^2)
Ground Dimensions (L x D)	330 cm x 309 cm (10.19 m^2)
Door Dimensions (L x H)	138 cm x 181 cm
Steel Thickness	0.25 mm
Material	Galvanized Steel, Wood Effect
Window Material	PVC (48 x 35 cm)
Weight	120 kg
Water Resistance	Waterproof



Figure 4.1: Dimensional diagram of the garden shed.

5. Setup and Assembly

Assembly of the EXPERTLAND ADELMO garden shed requires careful attention to detail. It is recommended that two or more people perform the assembly.

5.1 Site Preparation

- Choose a level and stable site for the shed. A concrete slab or a well-compacted gravel base is ideal.
- Ensure adequate clearance around the shed for assembly and future access.
- Clear the area of any debris, rocks, or vegetation.

5.2 Assembly Steps (General Guidelines)

1. **Unpack and Identify Parts:** Carefully unpack all components and verify against the parts list provided in the separate assembly guide.
2. **Base Frame Assembly:** Assemble the base frame on your prepared site, ensuring it is square and level.
3. **Wall Panel Installation:** Attach the wall panels to the base frame, following the numerical or alphabetical order indicated in the assembly guide. Secure panels using the provided fasteners.
4. **Roof Frame and Panels:** Construct the roof frame and then attach the roof panels. Ensure all roof sections overlap correctly for water resistance.
5. **Door Installation:** Install the double sliding doors into their tracks. Adjust as necessary for smooth operation.
6. **Window and Ventilation:** Install the PVC window and ensure ventilation grilles are clear.
7. **Anchoring:** Securely anchor the shed to the ground using appropriate anchoring hardware (not always included, may need to be purchased separately based on foundation type).

Note: Refer to the detailed graphical assembly instructions included with your product for specific step-by-step guidance and fastener details.

6. Operating Instructions

6.1 Sliding Doors

The shed features double sliding doors for easy access. To open, gently slide one or both doors along their tracks. To close, slide them back until they meet in the center. Ensure the doors are fully closed to protect contents from weather.

Figure 6.1: Double sliding doors in the open position.

Figure 6.2: Double sliding doors in the closed position.

6.2 Ventilation

The integrated ventilation grilles are designed to provide continuous airflow. Do not block these grilles, as proper ventilation helps prevent moisture buildup and maintains the condition of stored items.

7. Maintenance

Regular maintenance will extend the lifespan of your garden shed.

- **Cleaning:** Clean the shed exterior periodically with water and a mild detergent. Avoid abrasive cleaners or harsh chemicals that could damage the galvanized finish.
- **Door Tracks:** Keep the sliding door tracks clear of dirt, leaves, and debris to ensure smooth operation. Lubricate tracks with a silicone-based spray if movement becomes stiff.
- **Fasteners:** Periodically check all screws and bolts for tightness, especially after strong winds. Tighten any loose fasteners.
- **Ventilation Grilles:** Ensure ventilation grilles remain unobstructed to allow for proper airflow.
- **Foundation:** Inspect the shed's foundation and anchoring points annually to ensure stability.

8. Troubleshooting

This section addresses common issues you might encounter with your garden shed.

Problem	Possible Cause	Solution
Doors stick or are difficult to slide.	Debris in tracks, bent track, lack of lubrication.	Clean tracks thoroughly. Check for bent sections and straighten if possible. Apply silicone lubricant to tracks.

Problem	Possible Cause	Solution
Water leakage inside the shed.	Improperly sealed panels, damaged roof, unlevel foundation.	Inspect all panel seams and roof overlaps. Apply silicone sealant if necessary. Ensure the shed is on a level foundation.
Shed feels unstable or wobbly.	Loose anchoring, unlevel ground, loose fasteners.	Verify all anchoring points are secure. Re-level the foundation if needed. Tighten all assembly fasteners.
Condensation inside the shed.	Blocked ventilation, high humidity.	Ensure ventilation grilles are clear. Consider adding a dehumidifier if humidity is consistently high.

9. Warranty and Support

For warranty information or technical support, please contact Vente-unique customer service. Details regarding specific warranty periods and conditions are typically provided with your purchase documentation.

Contact Information: Refer to your purchase receipt or the Vente-unique website for the most current customer support contact details.

Online Resources: Visit the official Vente-unique website for additional product information, FAQs, and support resources:Vente-unique Store

© 2024 Vente-unique. All rights reserved.