

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [TENGA](#) /

› [TENGA FLIP Zero Gravity TFZ-005 Instruction Manual](#)

## TENGA TFZ-005

# TENGA FLIP Zero Gravity TFZ-005 Instruction Manual

Model: TFZ-005 | Brand: TENGA

## 1. PRODUCT OVERVIEW

The TENGA FLIP Zero Gravity TFZ-005 is a reusable male masturbator sleeve designed for intense pleasure and easy maintenance. It features an innovative flip-open design and a unique internal structure for varied sensations. This manual provides detailed instructions for its proper use and care.

- **Intense Pleasure:** Features an easy-to-handle squeezable pressure pad designed to provide focused sensation and create an internal vacuum. The bold elastomer provides vigorous stimulation with its internal design.
- **Seamless Insertion:** Features an “integrated pivot” that houses the flip-open hinge inside the product body, allowing for seamless insertion, improved usability, and easier cleaning.
- **Ergonomically Designed:** Engineered with less dead-space and denser internal details, the lower elevation of materials allows for faster stroking movements.
- **Easy-To-Use Design:** Features a flip-open design that allows for easy cleaning, hygienic storage, and accommodates air drying.
- **Made in Japan:** Designed, engineered, and proudly created in Japan.





Figure 1: TENGA FLIP Zero Gravity TFZ-005 in its closed state.

## 2. SETUP AND FIRST USE

---

Prepare your TENGA FLIP Zero Gravity for optimal performance by following these steps.

### 2.1 Unpacking

- Carefully remove the product from its packaging.
- Ensure all components are present: the main unit and the slide arms.

## 2.2 Initial Preparation

1. Remove the slide arms from the product.
2. Squeeze the rails of the product until it clicks open. This reveals the internal textures.
3. Apply a generous amount of water-based lubricant to the internal textures.
4. Close the product using the slide arms until it clicks securely.





Figure 2: The TENGA FLIP Zero Gravity TFZ-005 in its open position, ready for lubrication.

Video 1: Official TENGA Gravity video demonstrating the product's features, including opening, lubrication, and closing. This video also shows the internal textures and how to use the product.

### 3. OPERATION

---

The TENGA FLIP Zero Gravity is designed for a unique and customizable experience.

#### 3.1 Insertion

1. Apply lubricant to the insertion point for smooth entry.
2. Gently insert. The integrated pivot allows for seamless entry.

#### 3.2 Customizing Sensation

Once inserted, you can adjust the sensation by squeezing the pressure pads on the sides of the unit.

- Squeezing the pads allows air to escape through an internal one-way valve, creating a vacuum sensation.
- The intensity of the vacuum and internal stimulation can be controlled by varying the pressure applied to the pads.



Figure 3: Demonstrating the use of pressure pads for adjustable vacuum sensation.

## 4. CLEANING AND STORAGE

---

Proper cleaning and storage are essential for hygiene and product longevity.

### 4.1 Cleaning After Use

1. After each use, open the product by squeezing the rails until it clicks open.
2. Rinse the internal textures thoroughly under running water. Use mild soap if desired, then rinse completely to remove all residue.

### 4.2 Drying

1. Use the slide arms as a stand to allow the product to air dry completely. Ensure it is fully open for proper ventilation.
2. Avoid direct sunlight or excessive heat during drying, as this can damage the material.



Figure 4: The product positioned on its stand for air drying.

#### 4.3 Storage

Once dry, close the product and store it in its provided case in a clean, dry place, away from dust and direct sunlight.



Figure 5: The product stored in its hygienic case.

## 5. TROUBLESHOOTING

If you encounter any issues with your TENGA FLIP Zero Gravity, please refer to the following common solutions.

### 5.1 Reduced Suction

If the vacuum sensation is weaker than expected:

- Ensure the product is properly closed and sealed.
- Verify that the pressure pads are being squeezed correctly to allow air release.
- Check for any debris or damage around the one-way valve that might impede its function.

### 5.2 Lubricant Leakage

While the design minimizes leakage, if it occurs:

- Ensure sufficient lubricant is applied internally, but avoid overfilling.
- Confirm the product is fully closed before use.

## 5.3 Material Durability

The product is made from durable Thermoplastic Elastomer (TPE). To maximize lifespan:

- Follow cleaning instructions carefully.
- Avoid using oil-based lubricants, which can degrade TPE. Use only water-based lubricants.
- Store away from sharp objects or extreme temperatures.

## 6. PRODUCT SPECIFICATIONS

---

Feature	Detail
Product Dimensions	2.76 x 3.15 x 7.1 inches
Item Model Number	TFZ-005
Weight	1.07 Pounds
Manufacturer	TENGA
Material	Thermoplastic Elastomer (TPE)
Color	Black
Style	FLIP ZERO Gravity Black

## 7. WARRANTY AND SUPPORT

---

### 7.1 Warranty Information

This product comes with a manufacturer's warranty against defects in materials and workmanship. Please retain your proof of purchase. For specific warranty terms and conditions, refer to the product packaging or the official TENGA website.

### 7.2 Customer Support

For further assistance, questions, or support regarding your TENGA FLIP Zero Gravity TFZ-005, please visit the official TENGA website or contact their customer service department.

You can also find more information and products by visiting the [TENGA Store on Amazon](#).

