



[Manuals.plus](#) /

› [Waterstone](#) /

› Waterstone 1455C-MB Industrial Cold Only Filtration Faucet User Manual

Waterstone 1455C-MB

Waterstone 1455C-MB Industrial Cold Only Filtration Faucet User Manual

Model: 1455C-MB

INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your Waterstone 1455C-MB Industrial 2 Bend U-Spout Cold Only Filtration Faucet. Please read these instructions carefully before installation and retain them for future reference. This faucet is designed for cold water filtration systems, providing filtered cold water on demand.

SAFETY INFORMATION

- Always turn off the main water supply before beginning any installation or maintenance.
- Ensure all local plumbing and building codes are followed.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Do not overtighten connections, as this may damage the faucet or plumbing.

PACKAGE CONTENTS

Verify that all components are present before beginning installation.

- Waterstone 1455C-MB Faucet Assembly
- Mounting Hardware
- Connection Hoses
- Installation Guide (this document)



Image 1: Exploded view of Waterstone 1455C-MB faucet components. This image illustrates the various parts included in the package, such as the faucet body, handle, spout, and mounting hardware, to assist with identification during installation.

SPECIFICATIONS

Feature	Detail
Model Number	1455C-MB
Finish Type	Matte Black
Material	Brass
Mounting Type	Embedded
Number of Handles	1
Hole Count	1
Flow Rate	1.1 gpm maximum
Valve Type	1/4 turn ceramic disk cartridge
Special Feature	Rust Resistant, Resistant to reverse osmosis water
Spout Reach	6 inches (2 bend U-spout)
Spout Swivel	360 degrees
Item Weight	8 Pounds

SETUP AND INSTALLATION

Tools Required:

- Adjustable Wrench
- Plumber's Putty or Silicone Sealant

- Phillips Head Screwdriver
- Flashlight (optional)

Installation Steps:

1. **Turn off Water Supply:** Locate and turn off the main cold water supply valve.
2. **Prepare Mounting Surface:** Ensure the mounting hole on your sink or countertop is clean and free of debris. The faucet requires a single hole for installation.
3. **Install Faucet Body:**
 - Apply a thin bead of plumber's putty or silicone sealant around the base of the faucet body.
 - Insert the faucet body into the mounting hole.
 - From underneath the sink, secure the faucet using the provided mounting washer and nut. Hand-tighten first, then use an adjustable wrench to snug it securely. Do not overtighten.
4. **Connect Water Line:**
 - Connect the cold water supply line from your filtration system to the inlet on the bottom of the faucet. Ensure a watertight seal using a wrench.
5. **Check for Leaks:**
 - Slowly turn on the main cold water supply.
 - Inspect all connections for leaks. If leaks are present, gently tighten the connections until they stop.

OPERATING INSTRUCTIONS

The Waterstone 1455C-MB faucet features a single lever handle for simple operation.

- **To Turn On:** Lift the lever handle upwards. The further you lift, the greater the water flow.
- **To Turn Off:** Push the lever handle downwards to its original position.
- **Spout Swivel:** The U-spout can swivel 360 degrees for convenience.

MAINTENANCE AND CARE

Cleaning:

- Clean the faucet regularly with a soft cloth and mild soap.
- Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the Matte Black finish.
- Rinse thoroughly after cleaning and dry with a soft cloth to prevent water spots.

Aerator Maintenance:

- If water flow decreases, the aerator may be clogged. Unscrew the aerator from the tip of the spout.
- Rinse any debris from the aerator screen under running water.
- Reattach the aerator, ensuring it is securely tightened.

TROUBLESHOOTING

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed water supply valve; issue with filtration system.	Clean the aerator (see Maintenance); ensure water supply valve is fully open; check your filtration system's manual.
Leaks at Faucet Base	Loose mounting nut; insufficient sealant.	Gently tighten the mounting nut; if leak persists, remove faucet, reapply plumber's putty/sealant, and reinstall.
Leaks from Spout	Worn ceramic disk cartridge.	Contact Waterstone customer support for a replacement ceramic disk cartridge.

WARRANTY AND SUPPORT

Waterstone offers a **Lifetime Functional Warranty** on this product. For warranty claims, technical support, or replacement parts, please contact Waterstone customer service directly.

Refer to the official Waterstone website or your purchase documentation for the most current contact information and detailed warranty terms.

