

[manuals.plus](#) /› [WoldoClean](#) /› [WoldoClean Super Glue Metal 25g Instruction Manual](#)

WoldoClean 9776

WoldoClean Super Glue Metal 25g Instruction Manual

Model: 9776

1. INTRODUCTION

The WoldoClean Super Glue Metal 25g is an extra-strong cyanoacrylate adhesive designed for fast and durable bonding of various materials, with a primary focus on metal surfaces such as stainless steel and aluminum. It dries clear and provides an instant hold, making it suitable for a wide range of repair and crafting applications. This manual provides essential information for safe and effective use of the product.



Image 1.1: The WoldoClean Super Glue Metal 25g bottle, showcasing its design and labeling.

2. SAFETY INFORMATION

WARNING: Bonds skin and eyes instantly. Irritant. Read cautions on label.

- **Keep out of reach of children.**
- Avoid contact with skin and eyes. In case of skin contact, do not pull apart. Soak in warm soapy water or use a solvent like acetone. Seek medical attention if irritation persists.
- In case of eye contact, flush immediately with plenty of water for at least 15 minutes and seek immediate medical attention.
- Use in a well-ventilated area. Avoid breathing vapors.
- Wear appropriate personal protective equipment, such as gloves and eye protection.
- Do not ingest. If swallowed, do not induce vomiting. Seek medical attention immediately.

3. PREPARATION AND SETUP

3.1 Surface Preparation

- Ensure all surfaces to be bonded are clean, dry, and free from dust, grease, oil, or other contaminants.
- For best results, lightly abrade smooth surfaces with fine sandpaper to create a better bonding profile.
- Test the glue on an inconspicuous area first, especially with plastics, to ensure compatibility and desired finish.

3.2 Product Preparation

- Twist the cap to break the seal. Do not squeeze the bottle while opening.
- Ensure the precision tip is clear and ready for application.

4. OPERATING INSTRUCTIONS (APPLICATION)

The WoldoClean Super Glue Metal is designed for instant bonding on various materials, including metal, rubber, plastic, wood, and ceramics. Its precision tip allows for clean application on vertical, rough, or uneven surfaces without dripping or clogging.



Image 4.1: Examples of metal components on a car, illustrating potential application areas for the super glue in automotive repairs.

1. **Apply Sparingly:** Apply a small amount of glue to one of the surfaces to be bonded. A single drop is often sufficient for a square inch. Over-application can hinder bonding and curing.

2. **Join Surfaces:** Immediately press the two surfaces together firmly. Hold them in place for at least 10-30 seconds to allow initial bonding.
3. **Curing Time:** The glue achieves handling strength within seconds. Full cure typically occurs within 24 hours, depending on humidity and material.
4. **Clean Excess:** If any excess glue is visible, wipe it away immediately with a cloth dampened with acetone (nail polish remover) before it cures. Once cured, removal is more difficult.

Specific Uses: This adhesive is suitable for fixing broken car grill pieces, repairing metal candle holders, reattaching motorcycle mirrors, securing loose metal parts of rings, and repairing loose metal hinges.



Image 4.2: The WoldoClean Super Glue Metal bottle positioned in a modern home environment, surrounded by common household metal items like a lamp base, hairdryer, and metal mug, demonstrating its versatility for everyday repairs.

5. MAINTENANCE AND STORAGE

Proper storage ensures the longevity and effectiveness of your WoldoClean Super Glue Metal.

- **Anti-Clog Cap:** The product features an anti-clog cap designed to keep the adhesive fresh after each use, preventing waste and drying out. Always replace the cap securely after use.
- **Storage Conditions:** Store upright in a cool, dry place, ideally below 41°F (5°C). Refrigeration can extend shelf life but ensure the glue is brought to room temperature before use to prevent condensation.

- **Shelf Life:** The product has a long shelf life of up to 1-2 years when stored correctly.



Image 5.1: The WoldoClean Super Glue Metal bottle highlighting its anti-clog cap, which helps prevent the glue from drying out and ensures a longer product life.



Image 5.2: Information graphic detailing the recommended shelf life (1-2 years) and storage conditions (store upright, cooled, dry, above 41°F), along with the product dimensions (110x35x25 mm).

6. TROUBLESHOOTING

- **Glue not bonding:** Ensure surfaces are clean, dry, and free of contaminants. Apply a thin, even layer. Ensure sufficient pressure and holding time.
- **Glue drying too slowly:** Cyanoacrylate glues cure faster in the presence of moisture. If the environment is very dry, a slight mist of water can accelerate curing, but use sparingly.
- **Cap stuck:** If the cap becomes stuck, try soaking it in warm water or using pliers to gently twist it open. Always clean the nozzle after use to prevent this.
- **Skin bonded:** Do not pull apart. Soak the affected area in warm soapy water or use acetone (nail polish remover). Gently peel apart. Seek medical attention if necessary.

7. SPECIFICATIONS

Feature	Detail

Feature	Detail
Product Name	WoldoClean Super Glue Metal
Item Model Number	9776
Net Weight	25g (0.88 oz.)
Product Dimensions	4.33 x 1.38 x 0.91 inches; 0.71 ounces
Item Form	Liquid
Material Compatibility	Metal, Plastic, Wall, Rubber, Wood, Concrete, PVC
Temperature Resistance	-49°F to 239°F (-45°C to 115°C)
Special Features	Highly Durable in Extreme Conditions, Instant Bonding on Metal Surfaces, Long-Lasting Formula with Anti-Clog Cap, Multi-Surface Compatibility, No Dripping, Clean Application
Manufacturer	WoldoClean
Contents	1x Cyanoacrylate Super Glue

TEMPERATURE RESISTANT

239°F TO -49°F



WATER
RESISTANT



CHEMICAL
RESISTANT



UV
RESISTANT



Image 7.1: Graphic illustrating the temperature resistance range (239°F to -49°F) and other resistances of WoldoClean Super Glue Metal, including water, chemical, and UV resistance.



INDUSTRY QUALITY

- ✓ Ultra Strong
- ✓ Transparent
- ✓ Sandable
- ✓ Paintable



Image 7.2: Graphic highlighting the industry quality features of WoldoClean Super Glue Metal: Ultra Strong, Transparent, Sandable, and Paintable.

8. DISPOSAL INFORMATION

Dispose of cured adhesive and empty containers according to local regulations. Do not dispose of liquid adhesive down drains or into waterways. Contact your local waste management authority for proper disposal guidelines for chemical products.

9. ADDITIONAL RESOURCES AND SUPPORT

For further detailed instructions and support, please refer to the official Instructions for Use (IFU) document. You can access it via the link below or by scanning the QR code found on the product packaging.

Official Instructions for Use (PDF): [Download PDF](#)



Image 9.1: The WoldoClean Super Glue Metal bottle alongside a printed instruction sheet featuring a QR code, indicating where users can find detailed usage guidelines.

For product inquiries or technical assistance, please visit the [WoldoClean Store on Amazon](#).

Warranty Information: While specific warranty details are not provided in this manual, WoldoClean products are manufactured to high-quality standards. For any concerns regarding product defects or performance, please contact WoldoClean customer support through their official channels or the Amazon store page.