

[Manuals.plus](#) /

> [Qagea](#) /

> Qagea DC97-07618A Dryer Drum Felt Seal Instruction Manual for Samsung Dryers

Qagea DC97-07618A

Qagea DC97-07618A Dryer Drum Felt Seal Instruction Manual for Samsung Dryers

Model: DC97-07618A

INTRODUCTION

This instruction manual provides essential information for the proper installation and maintenance of the Qagea DC97-07618A dryer drum felt seal. This part is designed as a replacement for specific Samsung dryer models. Please read all instructions carefully before proceeding with installation.

COMPATIBILITY

The Qagea DC97-07618A dryer drum felt seal is compatible with various Samsung dryer models. It replaces OEM part numbers including DC97-07618A, AP4453798, PD00025731, PS4218879, and 3998155.

Known Compatible Samsung Dryer Models:

- DV42H5200EW
- DV42H5000EW
- DV45K6500EV
- DV48H7400EW
- DV45H7000EW
- DV45H6300GG/A3
- DV5471AEW
- DV50K8600EV/A3
- DV50K7500E
- DV52J8700EP/A2
- DVE50R5400V/A3
- DV50K7500EV/A3
- MDG9700AWW
- DV45H6300EW/A3
- DV45H7000GW/A2

- DV45K6500GV/A3
- DVE50M7450W
- DV48J7770EP/A2
- DVE50R5200W
- DVE52M8650W/A3
- DV48J7700E(G)
- DV410AEW/XAA
- DV361EWBEWR/A3
- DV50K7500GV/A3
- DV448AEW/XAA
- DV210AEW/XAA
- DVE52M7750V/A3
- DV45K6200GW/A3
- DV218AEB/XAA
- DV52J8700E(G)
- DV52J8060E(G)
- DV45H7000GW/A2-02
- DV48J7700EW/A2
- DV42H5000EW/A3 04
- DV45K6200EZ/A3
- DV448AGP/XAA
- DV42H5200EP/A3-0003
- DV48H7400GW/A2
- DV40J3000EW/A2
- DV218AGW/XAA
- DV5451AEW XAA 01
- DVE50M7450W/A3
- DV42H5200EW/A3
- DV42H5200EP/A3
- DV42H5200GP/A3
- DV45H5600
- DV45K6200EW/A3-02
- DV50F9A6GVW/A2
- DV48H7400EW/A2-00
- DV45K6500GV/A3
- DV45K6200GWA3
- DVE52M8650V/A3
- DV50F9A6EVW/A2
- DV52J8700EW/A2
- DV10K6500EV
- DV203AES, DV203AEW, DV203AGS, DV203AGW
- DV206AES, DV206AGS, DV206LEW
- DV209AEW, DV209AGW

- DV210AES, DV210AEW, DV210AGW
- DV218AEB, DV218AES, DV218AEW, DV218AGB, DV218AGW
- DV219AEB, DV219AEW, DV219AGB, DV219AGW
- DV220AEW, DV220AGW
- DV221AEG, DV221AES
- DV229AEG
- DV231AEW, DV231AGW
- DV2C6BEW, DV2C6BGW
- DV306BEW, DV306LEW, DV306LGW
- DV316BEC, DV316BEW, DV316BGC, DV316BGW, DV316HEC, DV316LES, DV316LEW, DV316LGS, DV316LGW
- DV317AEG, DV317AES, DV317AEW, DV317AGG, DV317AGS, DV317AGW
- DV328AEG, DV328AER, DV328AEW, DV328AGG, DV328AGR, DV328AGW
- DV330AEB, DV330AEW, DV330AGB, DV330AGW
- DV331AER, DV331AEW, DV331AGR

To confirm compatibility, locate your dryer's model number and compare it with the list above. If your model is not listed, please contact Qagea customer support for assistance.

PARTS INCLUDED

- 1x Qagea DC97-07618A Dryer Drum Felt Seal
- 1x Adhesive (30ml tube)



INSTALLATION INSTRUCTIONS

Replacing a dryer drum felt seal requires disassembling the dryer. It is recommended that this procedure be performed by individuals with mechanical aptitude. Always prioritize safety by disconnecting power to the appliance before beginning any repair work.

Required Tools (Not Included):

- Screwdrivers (Phillips and flathead)
- Nut drivers or socket set
- Pliers
- Work gloves
- Cleaning supplies (e.g., rubbing alcohol, cloth)
- Clamps or clothes pins (to hold felt during drying)

General Installation Steps:

1. **Disconnect Power:** Unplug the dryer from the electrical outlet or turn off the circuit breaker to ensure no power is supplied to the unit.
2. **Access the Drum:** Carefully disassemble the dryer cabinet to gain access to the dryer drum. This typically involves removing the top panel, control panel, front panel, and potentially the drum itself. Refer to your specific dryer model's service manual or online repair guides for detailed disassembly instructions.
3. **Remove Old Felt Seal:** Locate the worn or damaged felt seal on the drum. Carefully peel off the old seal and thoroughly clean the drum's rim where the new seal will be applied. Remove all old adhesive residue, lint, and debris. Use rubbing alcohol to ensure the surface is clean and dry.
4. **Apply New Felt Seal:** Apply a thin, even bead of the provided adhesive to the clean rim of the dryer drum. Carefully position the new Qagea DC97-07618A felt seal onto the adhesive, ensuring it is properly aligned.
5. **Secure and Dry:** Use clamps or clothes pins to hold the felt seal firmly in place around the drum's rim while the adhesive dries. Allow ample drying time, typically several hours or overnight, as recommended by the adhesive instructions. Insufficient drying time can lead to the seal detaching prematurely.
6. **Reassemble Dryer:** Once the adhesive is fully cured, remove any clamps. Reassemble the dryer by reversing the disassembly steps. Ensure all connections are secure and panels are properly fastened.
7. **Test Operation:** Plug the dryer back into the electrical outlet or restore power. Run a short cycle with no load to ensure the drum rotates smoothly and there are no unusual noises or issues.

Important Note: For visual guidance, it is highly recommended to search for installation videos specific to your Samsung dryer model on platforms like YouTube. These videos can provide step-by-step visual instructions that complement this written guide.



The drum dryer felt seal is guaranteed for 2 years! If you have any difficulties and needs, you can contact us at any time. We will reply you within 24 hours, our aim is to serve customers.

S A M S U N G W A S H I N G M A C H I N E

RENDERED BY ROKRPC EDITED BY DELOSPUP

OE

Accessories

100%

Inspection

2 YEARS

Warranty

24h

Online service

Image: A detailed view of the felt seal, highlighting the durable stitching and material.

MAINTENANCE

Proper maintenance can extend the life of your dryer and its components, including the felt seal.

- **Regular Cleaning:** Periodically clean the lint trap before or after every load. This prevents lint buildup that can affect dryer performance and potentially damage components.
- **Inspect for Wear:** During routine dryer maintenance (e.g., cleaning the exhaust vent), visually inspect the felt seal for signs of wear, fraying, or detachment. Early detection of wear can prevent larger issues.
- **Avoid Overloading:** Overloading the dryer can put excessive strain on the drum and its support components, potentially leading to premature wear of the felt seal and other parts.

TROUBLESHOOTING COMMON ISSUES

If you experience issues after replacing the felt seal, consider the following:

- **Drum Not Spinning Smoothly or Unusual Noises:**

- Ensure the felt seal is properly seated and not interfering with other moving parts like rollers.
- Check that all dryer components (rollers, idler pulley, belt) were reinstalled correctly and are in good condition.
- Verify that the adhesive has fully cured and the seal is securely attached.

- **Clothes Not Drying Efficiently:**

- While a felt seal primarily prevents heat loss and clothes from getting caught, ensure the dryer vent is clear and not obstructed.
- Confirm the heating element is functioning correctly.

- **Felt Seal Detaching:**

- This often indicates insufficient cleaning of the drum surface before application or inadequate drying time for the adhesive. Re-clean the surface thoroughly and reapply the seal, allowing ample time for the adhesive to cure.

If troubleshooting steps do not resolve the issue, it is advisable to consult a qualified appliance technician.

PRODUCT SPECIFICATIONS

| | |
|----------------------------------|--|
| Brand | Qagea |
| Model Number | DC97-07618A |
| Item Weight | Approximately 5 ounces |
| Package Dimensions | Approximately 7.72 x 4.84 x 1.65 inches |
| Replaces OEM Part Numbers | DC97-07618A, AP4453798, PD00025731, PS4218879, 3998155 |

WARRANTY AND SUPPORT

The Qagea DC97-07618A dryer drum felt seal is backed by a **2-year warranty**.

If you encounter any difficulties, have questions, or require assistance, please contact Qagea customer support. We aim to respond to inquiries within 24 hours.

For installation guidance, you may also refer to online video resources by searching for your specific dryer model and "felt seal replacement."

