

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [YARDMAX](#) /

› [YARDMAX 22 in. 201cc Select PACE 6 Speed CVT High Wheel RWD 3-in-1 Gas Walk Behind Self Propelled Lawn Mower Instruction Manual](#)

YARDMAX YG2760

YARDMAX 22 in. 201cc Self Propelled Lawn Mower

Model: YG2760

INTRODUCTION

This manual provides essential information for the safe and efficient operation, maintenance, and troubleshooting of your YARDMAX 22 in. 201cc Self Propelled Lawn Mower. This mower features a 3-in-1 system for mulching, side discharge, and rear bagging, powered by a durable 201cc OHV YARDMAX engine with an automatic choke system for easy starting. Its continuously variable transmission (CVT) allows for adjustable mowing speeds, and the single-lever height adjustment offers 7 cutting positions. The design includes double ball bearings on wheels and a MaxFlow volute deck for optimal performance.

SETUP AND ASSEMBLY

The YARDMAX Self Propelled Lawn Mower is designed for quick and easy setup. It comes largely pre-assembled, requiring minimal effort to prepare for use.

Unfolding the Handle

Upon unboxing, the mower's handle will be folded for compact storage. Carefully unfold the handle into its upright operating position. Ensure all locking mechanisms are securely engaged to prevent accidental folding during operation.



Image: The YARDMAX lawn mower with its handle unfolded and ready for use. This illustrates the mower's compact storage capability and ease of deployment.

Adding Fuel and Oil

Before starting the engine, ensure the oil reservoir is filled to the proper level with the recommended oil (often included with new units). Add fresh, unleaded gasoline to the fuel tank. Refer to the engine's specific instructions for fuel type and oil capacity. Do not overfill.

OPERATING INSTRUCTIONS

Proper operation ensures efficient mowing and extends the life of your equipment.

Starting the Engine

The 201cc OHV YARDMAX engine features an automatic choke system, eliminating the need for manual priming or choking. Simply pull the starter cord firmly to initiate engine operation.

Adjusting Mowing Speed (CVT)

The mower is equipped with an exclusive Continuously Variable Transmission (CVT) offering superior speed variability. Use the 6-speed shift lever located on the handle to adjust the mower's pace to your walking speed and terrain conditions. This allows for comfortable and efficient mowing.



Image: Close-up view of the 6-speed shift lever on the handle, used to adjust the mower's self-propelled speed.

Setting Cutting Height

Adjust the cutting height using the convenient single lever. There are 7 cutting positions available, ranging from 1.38 inches to 3.55 inches, allowing you to customize the lawn finish.



Image: Detail of the single-lever cutting height adjustment mechanism on the mower's wheel assembly.

Grass Clipping Disposal

The mower offers 3-in-1 functionality: mulching, side discharge, and rear bagging. Select the appropriate method based on your lawn care needs. The MaxFlow volute deck is designed to keep grass clippings airborne longer for superior mulching or efficient flow into the rear bag.



Image: Rear view of the YARDMAX lawn mower, showing the attached grass collection bag.

MAINTENANCE

Regular maintenance is crucial for optimal performance and longevity of your lawn mower.

Deck Cleaning

The mower features a convenient deck clean-out port. Simply attach a standard garden hose to the port to quickly clean the underside of the cutting deck, removing accumulated grass clippings and debris.



Image: Close-up of the deck clean-out port, designed for easy hose attachment to clean the mower's underside.

Blade Inspection and Care

Periodically inspect the cutting blade for sharpness and damage. A sharp blade ensures a clean cut and reduces strain on the engine. The mower features a durable 16-gauge seamless stamped steel deck, designed for reduced vibration and long-term durability.



Image: View of the mower's underside, showing the cutting blade and the robust steel deck construction.

Wheel Maintenance

The 8-inch front wheels and 11-inch rear wheels are equipped with double ball bearings for smooth rolling and extended durability. The exclusive aggressive spiked tread rubber tires provide increased traction and maneuverability. Keep wheels free of debris for optimal performance.

TROUBLESHOOTING

This section addresses common issues you might encounter with your lawn mower.

Problem	Possible Cause	Solution
Engine Fails to Start	No fuel, stale fuel, low oil, fouled spark plug, clogged air filter.	Check fuel level and quality. Ensure oil is at proper level. Inspect and clean/replace spark plug. Clean or replace air filter.
Mower Not Self-Propelling	Drive belt loose or damaged, drive cable issue, transmission problem.	Inspect drive belt and cables for proper tension and condition. If issues persist, consult a qualified service technician.
Uneven Cut	Dull or bent blade, uneven wheel height adjustment, excessive grass height.	Sharpen or replace blade. Ensure all wheels are set to the same cutting height. Mow tall grass in multiple passes.
Excessive Vibration	Bent blade, loose blade, engine imbalance.	Check blade for damage and ensure it is securely fastened. If vibration continues, professional inspection is recommended.

Problem	Possible Cause	Solution
Grass Catcher Not Filling Properly	Discharge chute clogged, bag full, blade not creating enough lift, wet grass.	Clear any blockages in the chute. Empty the grass bag. Ensure blade is sharp. Avoid mowing wet grass.

SPECIFICATIONS

Key technical specifications for the YARDMAX 22 in. 201cc Self Propelled Lawn Mower.

Brand: YARDMAX

Model Number: YG2760

Power Source: Gasoline-Powered

Engine: 201cc OHV YARDMAX

Cutting Width: 22 Inches

Cutting Height Positions: 7

Cutting Height Range: 1.38 in. to 3.55 in.

Drive System: Rear Wheel Drive (RWD) Self Propelled with 6 Speed CVT

Wheel Size: 8 in. front, 11 in. rear (with double ball bearings and aggressive spiked tread rubber tires)

Deck Material: 16-gauge seamless stamped steel

Functions: 3-in-1 (Mulching, Side Discharge, Rear Bagging)

Item Weight: 84.2 Pounds

Product Dimensions: 69"D x 22.9"W x 35.9"H

UPC: 850015852152

Country of Origin: Mexico

WARRANTY AND SUPPORT

For warranty information, technical support, or to order replacement parts, please refer to the official YARDMAX website or contact their customer service department. Keep your purchase receipt and model number (YG2760) readily available for any inquiries.

An official User Manual in PDF format is available for download: [Download User Manual \(PDF\)](#)

© 2024 YARDMAX. All rights reserved.

For assistance, please visit the [YARDMAX Store on Amazon](#).