

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [GROHE](#) /

› [GROHE Concetto Single-Handle Pull-Down Kitchen Faucet \(Model 326652433\) Instruction Manual](#)

GROHE 326652433

GROHE Concetto Single-Handle Pull-Down Kitchen Faucet (Model 326652433) Instruction Manual

Comprehensive guide for installation, operation, and maintenance of your GROHE Concetto kitchen faucet.

1. INTRODUCTION

Thank you for choosing the GROHE Concetto Single-Handle Pull-Down Kitchen Faucet. This manual provides detailed instructions for the proper installation, operation, and maintenance of your new faucet. Please read this manual thoroughly before installation and retain it for future reference.





Image 1.1: The GROHE Concetto Single-Handle Pull-Down Kitchen Faucet in Matte Black finish.

2. SAFETY INFORMATION

Observe the following safety precautions during installation and operation:

- Always turn off the main water supply before beginning any installation or maintenance work.
- Wear appropriate personal protective equipment, such as safety glasses and gloves.
- Ensure all connections are secure to prevent leaks.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Do not use abrasive cleaners or harsh chemicals on the faucet finish.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- GROHE Concetto Faucet Body
- Pull-Down Spray Head
- Mounting Hardware
- Hot and Cold Water Supply Lines
- Counterweight
- Instruction Manual (this document)

4. SETUP AND INSTALLATION

This section outlines the general steps for installing your GROHE Concetto kitchen faucet. Specific details may vary based on your sink and countertop configuration. Refer to the included diagrams for visual guidance.

1. **Prepare the Sink Area:** Turn off the main water supply. Clear the area under the sink. Remove any existing faucet.
2. **Install the Faucet Body:** Insert the faucet body into the mounting hole on your sink or countertop. Ensure the base gasket is properly seated.
3. **Secure the Faucet:** From underneath the sink, thread the mounting nut onto the faucet shank and tighten it securely. Ensure the faucet is aligned correctly before fully tightening.
4. **Connect Water Supply Lines:** Connect the hot and cold water supply lines from the faucet to your home's water supply valves. Use thread sealant tape as needed and tighten connections firmly but do not overtighten.
5. **Install the Pull-Down Hose and Counterweight:** Feed the pull-down hose through the faucet spout. Attach the counterweight to the hose at the specified location (typically below the sink, allowing for smooth retraction).
6. **Connect Spray Head:** Attach the spray head to the pull-down hose.
7. **Test for Leaks:** Slowly turn on the main water supply and check all connections for leaks. Operate the faucet to ensure proper water flow and spray function.



Image 4.1: The GROHE Concetto faucet seamlessly integrated into a kitchen environment.

5. OPERATING INSTRUCTIONS

Your GROHE Concetto faucet is designed for intuitive use with advanced features:

- **Water Flow and Temperature Control:** The single lever handle controls both water flow and temperature. Move the handle up to increase flow and down to decrease. Move it left for hot water and right for cold water. The GROHE SilkMove ceramic disc cartridge ensures smooth and precise control.
- **Dual Spray Function:** The pull-down spray head features a toggle button. Press this button to switch between a regular aerated stream for filling pots and a powerful spray for rinsing dishes or cleaning the sink.
- **Pull-Down Spray Head:** The spray head extends for increased reach and flexibility. After use, the EasyDock system ensures smooth retraction and secure docking of the spray head back into the spout.
- **360° Swivel Spout:** The faucet spout can swivel 360 degrees, providing extensive coverage for various sink tasks.



GROHE



GROHE SilkMove
Smooth, effortless
handle operation



GROHE StarLight
Durable coating wipes
clean, maintains finish
for life



EasyDock
Smooth retraction and
docking of spray head



Speed Clean
Wipe away limescale
on nozzles with your
fingertip



Smooth Turn
360° spout rotation
allows for full sink
coverage

Image 5.1: Key features of GROHE faucets, including SilkMove for smooth operation, StarLight for durable finish, EasyDock for spray head retraction, Speed Clean for easy nozzle cleaning, and Smooth Turn for 360° spout rotation.

6. MAINTENANCE

Proper care will ensure the longevity and appearance of your GROHE Concetto faucet:

- **Cleaning the Finish:** Clean the faucet regularly with a soft cloth and mild soap. Rinse thoroughly with clean water and dry with a soft cloth. The GROHE StarLight finish is designed for resistance to scratches and tarnishing.
- **Cleaning Speed Clean Nozzles:** The spray head features GROHE Speed Clean nozzles. Limescale buildup can be easily wiped away with your fingertip, maintaining optimal water flow.
- **Avoid Harsh Cleaners:** Do not use abrasive cleaners, scouring pads, ammonia-based cleaners, or any products containing bleach, acids, or alcohol, as these can damage the finish.
- **Check for Leaks:** Periodically inspect connections under the sink for any signs of leaks.

7. TROUBLESHOOTING

If you encounter issues with your faucet, refer to the table below for common problems and solutions:

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator/nozzles, partially closed shut-off valves, kinked supply line.	Clean Speed Clean nozzles. Ensure shut-off valves are fully open. Check supply lines for kinks.
Leaking from Faucet Base	Loose mounting nut, damaged gasket.	Tighten mounting nut. Inspect and replace gasket if damaged.
Leaking from Spray Head/Hose	Loose connection, damaged O-rings or hose.	Ensure spray head connection is tight. Inspect O-rings and hose for damage; replace if necessary.
Difficulty Switching Spray Modes	Mineral buildup in spray head mechanism.	Clean the spray head and toggle button thoroughly to remove mineral deposits.
Spray Head Does Not Retract Smoothly	Counterweight obstruction, hose friction.	Ensure counterweight is free from obstructions. Check hose path for kinks or friction points.

If the problem persists after attempting these solutions, please contact GROHE customer support.

8. SPECIFICATIONS

Feature	Detail
Brand	GROHE
Model Name	Concetto
Model Number	326652433
Color	Matte Black
Material	Brass
Finish Type	Matte
Mounting Type	Deck Mount
Installation Type	Single Hole
Number of Handles	1
Hole Count	1
Special Features	Dual Function Sprayer, Pull Down Sprayer
Maximum Flow Rate	1.75 Gallons Per Minute
Spout Height	7.37 Inches
Spout Reach	8.75 Inches

Feature	Detail
Hose Length	33.68 Inches
Item Weight	6.2 Pounds
Product Dimensions	8.75"D x 5.37"W x 15"H
Certifications	ADA, ASME A112.18.1, CALGreen Compliant, CEC Certified, CSA B125.1, Energy Policy Act of 1992, Low Lead Certified, Massachusetts Plumbing Board Approved, NSF 372, NSF 61



Image 8.1: Dimensional drawing of the GROHE Concetto faucet, indicating key measurements for installation planning.

9. WARRANTY AND SUPPORT

Warranty Information: Your GROHE Concetto faucet comes with a Limited Lifetime Warranty. This warranty

covers defects in material and workmanship under normal use and service. For full warranty details, please refer to the official GROHE warranty documentation or visit the GROHE website.

Customer Support: If you require assistance with installation, troubleshooting, or warranty claims, please contact GROHE customer service. Contact information can typically be found on the official GROHE website or on the product packaging.

For more information, visit the official [GROHE Store on Amazon](#).

© 2023 GROHE. All rights reserved. Information in this manual is subject to change without notice.