

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [ELEGANT](#) /

› [ELEGANT Neo-Angle Frameless Shower Door \(Model A33S111CO\) User Manual](#)

ELEGANT A33S111CO

ELEGANT Neo-Angle Frameless Shower Door (Model A33S111CO) User Manual

Model: A33S111CO | Brand: ELEGANT

INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your ELEGANT Neo-Angle Frameless Shower Door. Please read all instructions carefully before beginning installation to ensure safe and proper assembly and use. This shower enclosure is designed for corner installations, featuring 1/4-inch clear tempered glass and a black finish frame.



Image: ELEGANT Neo-Angle Frameless Shower Door, 36.5 x 72 inches, Black Finish, showcasing its design and dimensions.

SAFETY INFORMATION

- Always wear safety glasses during installation.
- Handle glass panels with extreme care. Tempered glass, while strong, can shatter if struck at the edges.
- Ensure the installation surface is level and structurally sound to support the weight of the shower door.
- Do not overtighten screws, as this can damage components or glass.
- Keep children and pets away from the installation area.
- If you are unsure about any step, consult a qualified professional.

PACKAGE CONTENTS

Verify that all components are present and undamaged before beginning installation. The package typically includes:

- Fixed glass panels (2)
- Pivot glass door (1)
- Stainless steel handle (1)
- Aluminum frame profiles
- Magnetic seal strips
- Hardware kit (screws, anchors, gaskets, etc.)
- Installation instructions

TOOLS REQUIRED

The following tools are generally required for installation:

- Measuring Tape
- Pencil
- Level
- Drill with appropriate drill bits (e.g., masonry bits for tile/concrete)
- Screwdriver (Phillips head)
- Caulk Gun and Silicone Sealant (mildew-resistant)
- Utility Knife
- Safety Glasses

SETUP AND INSTALLATION

The ELEGANT Neo-Angle Shower Door is designed for straightforward installation. It is reversible, allowing for either a right or left door opening configuration. Ensure your shower base is properly installed and level before proceeding.

1. Wall Profile Adjustment

The wall profiles allow for a width adjustment of approximately 0.5 inches (12 mm) per side to accommodate minor variations in wall plumb. This adjustment helps achieve a secure and watertight fit.



Image: Illustration of the 0.5-inch width adjustment feature on the wall profile, ensuring a flexible fit.

2. Assembling the Frame and Glass Panels

Carefully assemble the aluminum frame profiles according to the provided diagrams. Insert the fixed glass panels into their respective channels. The black finish frame provides structural integrity and secures the glass panels.



Image: Detail of the sturdy black finish frame, highlighting its construction.

3. Installing the Pivot Door and Handle

Attach the pivot glass door using the provided hardware. Ensure the pivot mechanism operates smoothly. Install the stainless steel handle on the pivot door. The handle is designed for durability and ease of use.



Image: Detailed view of the stainless steel handle, emphasizing its robust design.

4. Sealing and Waterproofing

Apply silicone sealant to all exterior joints where the frame meets the wall and shower base to prevent water leakage. Install the magnetic seal strips along the edges of the pivot door and fixed panels. These strips ensure

a tight, waterproof closure and reduce noise during operation.



Image: Close-up of the magnetic seal strip, illustrating its function in preventing water leaks.

5. Final Inspection

After installation, allow the silicone sealant to cure completely as per the manufacturer's instructions (typically 24-48 hours) before using the shower. Check all connections for tightness and ensure the door swings freely and closes securely.



Image: Overhead view demonstrating how the neo-angle shower enclosure utilizes corner space efficiently.

OPERATING INSTRUCTIONS

To open the shower door, gently pull the handle outwards. To close, push the door until the magnetic strips engage, ensuring a secure seal. Avoid slamming the door to prevent damage to the glass or frame.

MAINTENANCE

Cleaning the Glass

Clean the tempered glass panels regularly with a soft cloth and a non-abrasive glass cleaner. Avoid using harsh chemicals, abrasive pads, or scouring powders, as these can scratch the glass or damage protective coatings.

Cleaning the Frame and Hardware

Wipe down the black finish aluminum frame and stainless steel handle with a soft, damp cloth. For stubborn spots, a mild soap solution can be used. Rinse thoroughly and dry to prevent water spots. Do not use abrasive cleaners or solvents on the frame, as this may damage the finish.

Inspecting Seals and Hardware

Periodically inspect the magnetic seal strips for wear or damage. Ensure all screws and hardware remain tight. If any components appear loose or damaged, tighten or replace them as necessary to maintain proper function and prevent leaks.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Water leakage from enclosure	Improperly sealed joints; Worn or misaligned magnetic strips; Loose hardware.	Reapply silicone sealant to all exterior joints. Check and adjust magnetic strips for proper alignment and contact. Tighten all frame and panel hardware.
Door does not close properly or is stiff	Misaligned pivot hinges; Obstruction; Wall profiles not plumb.	Check pivot hinges for proper alignment and lubrication. Ensure no debris obstructs the door's path. Verify wall profiles are plumb and adjust if necessary using the 0.5-inch adjustment feature.
Glass appears scratched or stained	Use of abrasive cleaners; Hard water deposits.	Use only non-abrasive glass cleaners and soft cloths. For hard water spots, use a vinegar-based solution or specialized hard water stain remover.

SPECIFICATIONS

Model: A33S111CO

Dimensions: 36.5 in. W x 72 in. H

Glass Thickness: 1/4 inch (ANSI-certified clear tempered glass)

Frame Material: Aluminum

Finish: Black

Walk-in Opening: 22 inches

Width Adjustment: Up to 0.5 inches per side

Door Type: Pivot

Assembly Required: Yes

Item Weight: 99 Pounds

WARRANTY INFORMATION

ELEGANT products are manufactured to high-quality standards. For specific warranty details regarding your Neo-Angle Frameless Shower Door, please refer to the warranty card included with your product or contact ELEGANT customer support directly. Keep your proof of purchase for warranty claims.

CUSTOMER SUPPORT

If you have any questions about the installation, operation, or maintenance of your ELEGANT Neo-Angle Frameless Shower Door, please contact ELEGANT customer support. Contact information can typically be found on the product packaging or the official ELEGANT website.