

Manuals.plus /

› CKB /

› CKB Sliding Shower Door Installation and User Manual (Model: Sliding Shower Door for Tub)

CKB Sliding Shower Door for Tub

CKB Sliding Shower Door Installation and User Manual

Brand: CKB | Model: Sliding Shower Door for Tub

1. INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your CKB Sliding Shower Door. This frameless bathtub door features 5/16" (8mm) SGCC tempered glass, offering both durability and safety. Its design allows for adjustable width and reversible installation, accommodating various bathroom layouts. The door is equipped with stainless steel rollers for smooth and quiet operation, and high-quality sealing strips combined with an aluminum bottom water barrier ensure excellent waterproof performance.

Product Overview

Your browser does not support the video tag.

Video Description: This video provides a general overview of the CKB Sliding Shower Door, showcasing its design and smooth operation within a bathroom setting.

2. SAFETY INFORMATION

- Always wear appropriate safety gear, including gloves and eye protection, during installation.
- Glass is heavy and fragile. Handle with extreme care to prevent injury or damage.
- It is recommended that this door be installed by professionals with a minimum of two installers due to the weight of the glass panels.
- Ensure all components are securely fastened before use.
- Allow 24 hours for silicone sealant to cure completely before using the shower to ensure a watertight seal.

3. INSTALLATION GUIDE

Follow these steps carefully for proper installation. Refer to the included video for visual guidance.

Installation Video

Your browser does not support the video tag.

Video Description: This video provides step-by-step instructions for the installation of the CKB Frameless Bathtub Door.

Step-by-Step Instructions

1. **Unboxing and Component Check:** Carefully unbox all components and verify against the parts list. Ensure no parts are missing or damaged.



Image Description: A person unboxing the shower door, revealing the glass panels and hardware components.

2. **Step 1: Measurement:** Measure the width of your bathtub opening to ensure compatibility. The door is adjustable from 55 3/4" to 59" W.



Image Description: A person measuring the width of the bathtub opening with a tape measure.

3. **Step 2: Mark the Bottom Channel Position:** Place the bottom channel (8) on the bathtub edge. Mark the position, ensuring approximately 6/10" distance between the edge of the bottom channel and the flat surface of the tub. Use a level to ensure proper alignment.



Image Description: A person marking the position for the bottom channel on the bathtub edge, ensuring it is level.

4. **Step 3: Install Bottom Channel:** Drill pilot holes at the marked positions. Insert wall plugs (1) and secure the bottom channel (8) using screws (3). Apply silicone sealant along the bottom channel for a watertight seal.



Image Description: A person drilling and securing the bottom channel to the bathtub, followed by applying silicone sealant.

5. **Step 4: Install Wall Jambs and Fixed Panel:** Position the wall jambs (2) against the wall, ensuring they are plumb with a level. Mark and drill pilot holes, insert wall plugs, and secure the wall jambs. Carefully place the fixed glass panel (4) into the wall jamb and bottom channel.



Image Description: A person installing the wall jambs and carefully positioning the fixed glass panel.

6. **Step 5: Mark Top Rail Installation Location:** Assemble the rail bracket assembly (12) and attach it to the top rail (14). Position the top rail assembly on top of the fixed panel and wall jambs. Mark the drilling locations for the rail bracket on the wall.



Image Description: A person assembling the rail bracket and marking the top rail's position on the wall.

7. **Step 6: Install Top Rail Wall Mounts:** Remove the wall mounts from the rail bracket assemblies. Drill pilot holes at the marked locations, insert wall plugs, and secure the wall mounts to the wall.



Image Description: A person drilling holes and securing the wall mounts for the top rail.

8. **Step 7: Install Top Rail:** Attach the top rail (14) to the installed wall mounts, ensuring it is level and secure.



Image Description: A person attaching the top rail to the previously installed wall mounts.

9. **Step 8: Install Bottom Guide:** Position the bottom guide (6) on the bottom channel, ensuring it is centered and aligned with the sliding door's path. Mark and drill pilot holes, then secure the bottom guide with screws. Ensure the plastic insert block is installed at the '8' position for 8mm glass.



Image Description: A person marking and installing the bottom guide on the bathtub edge.

10. **Step 9: Assemble Upper Roller Assemblies:** Attach the rollers (16) to the sliding door panel. Ensure they are securely fastened.



Image Description: A person assembling the rollers onto the top edge of the sliding glass door panel.

- Step 10: Hanging the Door:** Carefully lift the sliding door panel and hang it onto the top rail rollers. Ensure the door is properly seated in the bottom guide. Lock in the knob sets (17) to secure the door.



Image Description: A person carefully hanging the sliding glass door onto the top rail and securing it.

- Step 11: Roller Adjustment:** Adjust the rollers to ensure smooth and even sliding. Loosen the center bolt with a hex wrench, rotate the outer edge of the roller assembly using a small hex while holding the large hex wrench in place, then tighten the center bolt.



Image Description: A person adjusting the rollers on the sliding door for optimal movement.

- Step 12: Assemble Gasket, Handle, and Cover Strip Profile:** Install the door gasket strips (18) along the vertical edges of the glass panels. Attach the handle (11) to the sliding door. Install the door seals (7, 10) as indicated.




Image Description: A person installing the door gasket, handle, and other sealing components.

- Final Sealing:** Apply a continuous bead of silicone sealant along all exterior seams where the wall jambs meet the wall and where the bottom channel meets the tub.



Image Description: A person applying silicone sealant to the edges of the installed shower door for a watertight seal.

- Curing Time:** Allow 24 hours for the silicone sealant to cure completely before using the shower.

4. OPERATING INSTRUCTIONS

To open or close the CKB Sliding Shower Door, gently grasp the handle and slide the door along the top rail. The stainless steel rollers are designed for effortless and quiet movement. Ensure the door is fully closed before showering to prevent water leakage.

5. MAINTENANCE

Regular cleaning and maintenance will ensure the longevity and appearance of your shower door.

- Glass Cleaning:** Clean the tempered glass regularly with a soft cloth and a non-abrasive glass cleaner. Avoid harsh chemicals or abrasive pads that can scratch the glass or damage the protective coating.
- Hardware Cleaning:** Wipe down metal components (frame, handles, rollers) with a soft, damp cloth. For stubborn spots, use a mild, non-abrasive cleaner specifically designed for the finish (e.g., matte black).
- Seal Maintenance:** Periodically check the sealing strips and silicone for any signs of wear or damage. Replace if necessary to maintain a watertight enclosure.
- Roller Maintenance:** Keep the rollers and top rail free of debris to ensure smooth operation. A small amount of silicone-based lubricant can be applied to the rollers if they become stiff.

6. TROUBLESHOOTING

If you encounter any issues with your CKB Sliding Shower Door, please refer to the following common solutions or contact customer support.

- Door does not slide smoothly:** Check the top rail and rollers for any obstructions or debris. Ensure

the rollers are properly adjusted (refer to Step 11 of the installation guide).

- **Water leakage:** Verify that all sealing strips are correctly installed and in good condition. Inspect the silicone sealant along the edges and reapply if any gaps or cracks are present. Ensure the door is fully closed during use.
- **Door misalignment:** Check if the wall jambs and top rail are level and plumb. Minor adjustments to the rollers may correct slight misalignments.

7. SPECIFICATIONS

Feature	Specification
Brand	CKB
Model Number	Sliding Shower Door for Tub
Size	55 3/4"- 59" W x 60" H
Material	8mm Tempered Glass, Stainless Steel
Color	Matte Black
Assembly Required	Yes
Item Weight	107.8 pounds
Product Dimensions	0.31 x 59 x 60 inches

8. WARRANTY INFORMATION

This CKB Sliding Shower Door comes with a **Limited Warranty**. For specific terms and conditions, please refer to the warranty documentation included with your product or contact CKB customer support.

9. CUSTOMER SUPPORT

For any questions, assistance, or to report missing/damaged parts, please contact CKB Customer Support. Contact information can typically be found on the product packaging or the official CKB website.