Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

LEKATO JA-02 II

LEKATO Mini Guitar Amplifier JA-02 II User Manual

Model: JA-02 II

1. Introduction

Thank you for purchasing the LEKATO Mini Guitar Amplifier JA-02 II. This compact and versatile amplifier is designed for guitarists seeking a portable solution for practice and small performances. It features two sound channels, Bluetooth connectivity, and a rechargeable battery for extended use.
Please read this manual thoroughly before using the product to ensure proper operation and to maximize its lifespan.



Image 1.1: Front view of the LEKATO Mini Guitar Amplifier JA-02 II, showcasing its compact design and control knobs.

2. Package Contents

Upon opening the package, please verify that all items listed below are included:

- LEKATO Mini Guitar Amplifier JA-02 II (x1)
- USB Charging Cable (x1)
- User Manual (x1)

3. Product Overview

3.1. Controls and Ports



Image 3.1: Front panel controls of the amplifier.

1. **Bluetooth Button:** Press to activate/deactivate Bluetooth pairing mode.
2. **B.T./AUX VOL Knob:** Adjusts the volume for Bluetooth and AUX input.
3. **VOLUME Knob:** Adjusts the main output volume of the guitar.
4. **POWER Button:** Turns the amplifier on/off.
5. **TONE Knob:** Adjusts the tonal characteristics (treble/bass) of the guitar sound.
6. **CLEAN / OVER DRIVE Switch:** Toggles between Clean and Overdrive sound channels.
7. **GAIN Knob:** Adjusts the input sensitivity and distortion level for the Overdrive channel.
8. **INPUT Jack:** 1/4-inch input for connecting your guitar.



Image 3.2: Rear panel with AUX IN and Headphone Output.

9. **AUX IN Jack:** 3.5mm input for connecting external audio devices (e.g., smartphone, MP3 player).
10. **3.5mm Headphone Output:** For private practice with headphones.
11. **USB Charging Port:** USB-C port for charging the internal battery.

4. Setup

4.1. Charging the Amplifier

Before first use, fully charge the amplifier. Connect the supplied USB charging cable to the USB Charging Port on the rear of the amplifier and to a standard USB power adapter (not included) or a computer USB port. The charging indicator light will show charging status (e.g., red for charging, off when fully charged).



Image 4.1: Connecting the USB charging cable to the amplifier.

4.2. Initial Power On

Press and hold the POWER button for a few seconds to turn the amplifier on. The power indicator light will illuminate.

5. Operating Instructions

5.1. Connecting Your Guitar

Plug your guitar cable into the **INPUT Jack** on the front panel of the amplifier.

5.2. Adjusting Sound Channels (Clean/Overdrive)

The amplifier offers two distinct sound channels:

- **Clean Channel:** Provides a clear, undistorted guitar tone.
- **Overdrive Channel:** Adds distortion and sustain for rock and blues tones.

Use the **CLEAN / OVER DRIVE Switch** to select your desired channel. When the Overdrive channel is active, you can use the **GAIN Knob** to adjust the amount of distortion.



Image 5.1: Illustration of the two sound channels: Clean and Overdrive.

5.3. Volume and Tone Control

- Use the **VOLUME Knob** to control the overall output volume of your guitar.
- Use the **TONE Knob** to adjust the brightness or warmth of your guitar sound. Turning it clockwise generally increases treble, while counter-clockwise increases bass.

5.4. Bluetooth Connectivity

To connect an external device via Bluetooth:

1. Press the **Bluetooth Button** on the amplifier. The Bluetooth indicator light will flash, indicating pairing mode.
2. On your external device (smartphone, tablet, computer), enable Bluetooth and search for available devices.
3. Select "JA-02 II" from the list of devices. Once connected, the Bluetooth indicator light will remain solid.
4. Play music from your device. Adjust the playback volume using the**B.T./AUX VOL Knob** on the amplifier and your device's volume controls.



Image 5.2: Connecting the amplifier to a smartphone via Bluetooth.

5.5. Using AUX Input

To connect an external audio device via AUX cable (not included):

1. Connect a 3.5mm audio cable from your external device's headphone jack to the**AUX IN Jack** on the rear of the amplifier.
2. Play music from your device. Adjust the playback volume using the**B.T./AUX VOL Knob** on the amplifier and your device's volume controls.

5.6. Headphone Practice

For silent practice, connect a pair of headphones to the**3.5mm Headphone Output** on the rear of the amplifier. The main speaker output will be muted, allowing you to practice without disturbing others.



Image 5.3: A user practicing guitar with the amplifier.

6. Maintenance

- Keep the amplifier clean by wiping it with a soft, dry cloth. Do not use liquid cleaners or abrasive materials.
- Avoid exposing the amplifier to extreme temperatures, humidity, or direct sunlight.
- Store the amplifier in a dry, cool place when not in use.
- Do not attempt to disassemble or repair the amplifier yourself. Refer to qualified service personnel for any repairs.

7. Troubleshooting

Problem	Possible Cause	Solution

Problem	Possible Cause	Solution
No sound from guitar.	• Amplifier is off. • Volume knob is too low. • Guitar cable is not connected properly. • Guitar volume is off.	• Turn on the amplifier. • Increase the VOLUME knob. • Ensure guitar cable is securely connected. • Check guitar's volume controls.
No sound from Bluetooth/AUX.	• B.T./AUX VOL knob is too low. • Bluetooth not paired or AUX cable not connected. • External device volume is low.	• Increase the B.T./AUX VOL knob. • Ensure Bluetooth is paired or AUX cable is connected. • Increase volume on the external device.
Bluetooth connection issues.	• Amplifier not in pairing mode. • Device too far from amplifier. • Interference.	• Press the Bluetooth button to enter pairing mode. • Move device closer to the amplifier. • Turn off other Bluetooth devices nearby.
Short battery life.	• Battery not fully charged. • High volume usage.	• Ensure battery is fully charged before use. • Lower volume settings can extend battery life.

8. Specifications

Feature	Detail
Model	JA-02 II (M02294)
Brand	LEKATO
Power Output	5W
Sound Channels	Clean, Overdrive
Connectivity	Bluetooth 5.0, 3.5mm AUX Input, 3.5mm Headphone Output, 1/4" Guitar Input
Battery	Rechargeable, approximately 6 hours continuous use
Dimensions (L x W x H)	14.7 cm x 7.5 cm x 9.6 cm (5.8 x 3.0 x 3.8 inches)
Weight	0.42 kg (0.93 lbs)
Color (Current Variant)	Orange



Image 8.1: Dimensions of the LEKATO Mini Guitar Amplifier JA-02 II.

9. Warranty and Support

This LEKATO Mini Guitar Amplifier comes with a 1-year warranty from the date of purchase. If you encounter any issues or have questions regarding your product, please contact our customer support team via email. We are committed to providing prompt assistance according to our store policy.

For further assistance, please refer to the contact information provided with your purchase or visit the official LEKATO website.



Image 9.1: The portable amplifier being used outdoors.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0BFDW3GGJ

More documents and user manuals: **https://manuals.plus/**