

[Manuals.plus](#) /

> [Pride Mobility](#) /

> Pride Mobility Victory 9 SC609 Mobility Scooter Instruction Manual

Pride Mobility Victory 9

Pride Mobility Victory 9 SC609 Mobility Scooter Instruction Manual

Model: SC609

1. INTRODUCTION

This manual provides essential information for the safe and effective use of your Pride Mobility Victory 9 SC609 3-Wheel Mobility Scooter. Please read this manual thoroughly before operating your scooter to ensure proper setup, operation, and maintenance. The Victory 9 offers a balance of style, comfort, and performance, designed to support users up to 300 lbs. with a maximum speed of 5.3 mph and a range of up to 13 miles per charge.

2. SAFETY GUIDELINES

Always prioritize safety when operating your mobility scooter. Adhere to all local traffic laws and regulations. Ensure you are familiar with all controls before operating the device in public areas.

- **Weight Capacity:** Do not exceed the maximum weight capacity of 300 lbs.
- **Speed Control:** Operate at a speed appropriate for your surroundings and conditions.
- **Stability:** Be aware of the scooter's turning radius (4 feet) and avoid sharp turns at high speeds to prevent tipping.
- **Visibility:** Use the high-intensity LED headlight in low-light conditions.
- **FDA Class II Medical Device:** This device is designed to aid individuals with mobility impairments.

3. SETUP AND ASSEMBLY

The Victory 9 scooter features feather-touch disassembly for convenient transport and storage. The heaviest piece when disassembled is the front section, weighing 48.5 lbs.

3.1 Unpacking and Initial Assembly

Carefully remove all components from the packaging. Refer to the included diagrams for proper assembly sequence. Ensure all connections are secure before proceeding.

3.2 Charging the Battery

Before first use, fully charge the scooter's batteries. The easy-access charger port is conveniently located on the tiller. Connect the charger to the port and then to a standard wall outlet. The battery is covered by a separate six-month warranty from the battery manufacturer.

Battery Requirements: Two (2) U1 standard batteries, each weighing 24 lbs.

Battery Charger: 3.5-amp, off-board charger.

Proper charging care is essential for long-lasting battery life.

4. OPERATING YOUR SCOOTER

Familiarize yourself with the tiller console and its controls before operating the scooter.

4.1 Controls and Features

- **Tiller Console:** Contains the controls for speed, lights, and battery gauge.
- **Easy-Grip Tiller Adjustment Knob:** Allows for comfortable positioning of the tiller.
- **Ambient Voltmeter:** Displays battery charge level.
- **High-Intensity LED Headlight:** Provides optimal pathway illumination.
- **Standard Front Basket:** For carrying personal items.
- **Pinchless Hinge, Black Vinyl Seat:** Features an 8-point swivel and sliders for increased comfort.
- **Non-Scuffing Low-Profile Tires:** Designed for durability and smooth operation.

STYLE, COMFORT, PERFORMANCE

18" x 17"
Pinchless hinge,
black vinyl seat
with 8-point
swivel and
sliders for
increased
comfort



Ambient voltmeter

Standard
front basket

Easy-to-grip
tiller adjustment
knob

Long-lasting,
maximum-
intensity LED
headlight
offers optimal
pathway
illumination

Exclusive stylish, lightweight, non-scutting, black, low-profile tires



Tiller console



Feather-touch disassembly

Image: Side view of the Pride Mobility Victory 9 SC609 scooter, highlighting key features such as the 18"x17" pinchless hinge black vinyl seat, standard front basket, easy-grip tiller adjustment knob, long-lasting LED headlight, ambient voltmeter, and exclusive stylish, lightweight, non-scutting, black, low-profile tires. The tiller console and feather-touch disassembly components are also shown.

4.2 Driving the Scooter

Use the controls on the tiller to accelerate, brake, and steer. The scooter has a maximum speed of 5.3 mph. The dual braking system is electronic, regenerative, and electromechanical, providing reliable stopping power.

5. MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your Victory 9 scooter.

- **Battery Care:** Always charge the batteries fully after each use. Avoid deep discharges. Store the scooter with fully charged batteries if not in use for extended periods.
- **Cleaning:** Clean the scooter regularly with a damp cloth. Avoid using harsh chemicals or abrasive cleaners.
- **Tire Inspection:** Periodically check the solid tires for wear and tear.
- **General Inspection:** Regularly inspect all visible components for any signs of damage or loose connections.

6. TROUBLESHOOTING

If you encounter any issues with your scooter, please refer to the following general advice. For complex problems, contact an authorized Pride Mobility service provider.

- **Scooter Not Powering On:** Check battery connections and ensure batteries are charged. Verify the key is fully inserted and turned to the 'On' position.
- **Reduced Performance:** This may indicate low battery charge. Fully charge the batteries.
- **Unusual Noises:** Discontinue use immediately and contact a service technician.

7. SPECIFICATIONS

Detailed specifications for the Pride Mobility Victory 9 SC609 Mobility Scooter.



Image: The Pride Mobility Victory 9 SC609 scooter shown with its overall dimensions: 43.5 inches in length, 22.5 inches in width,

and 33 inches in height.

Feature	Specification
Model	Victory 9
Part Number	SC609
Weight Capacity	300 lbs.
Maximum Speed	Up to 5.3 mph
Ground Clearance	1.8" at transaxle, 1.4" at anti-tip, 2.7" at side deck
Turning Radius	40.25" (approx. 4 feet)
Overall Length	43.5"
Overall Width	22.5"
Seat-to-Ground Height	22.5"-24"
Seat-to-Deck Height	17.25"-18.75"
Front Tires	3" x 8" solid
Rear Tires	3" x 9" solid
Suspension	N/A
Range Per Charge	Up to 13 miles
Total Weight (with batteries)	165 lbs.
Total Weight (without batteries)	117 lbs.
Heaviest Piece When Disassembled	48.5 lbs. (front section)
Standard Seating	Type: Compact, foldable; Weight: 28 lbs.; Material: Black Vinyl; Dimensions: 18" width, 17" depth
Drive System	Rear-wheel drive sealed transaxle with 24-volt DC motor
Dual Braking System	Electronic, regenerative and electromechanical
Battery Requirements	Size: (2) U1 standard; Weight: 24 lbs. each
Battery Charger	3.5-amp, off-board
Color	Candy Apple Red
Material Type	Metal, Plastic, Rubber
Frame Material	Either 'Carbon Steel', 'Alloy Steel', or 'Stainless Steel'
UPC	606509600538

8. WARRANTY AND SUPPORT

Pride Mobility provides comprehensive warranty coverage for your Victory 9 scooter.

8.1 Warranty Details

- **Lifetime Warranty:** From the date of purchase, Pride will repair or replace structural frame components (main frame, seat post, fork, tiller frame) found to be defective in material and/or workmanship.
- **Two-Year Warranty:** For two years from the date of purchase, Pride will repair or replace transaxle, bushings, brake, motor brake, bearings, and electronic assemblies (controllers, harnesses, chargers, other electrical subassemblies) found to be defective. Warranty claims for electronic assemblies may be void if damage results from non-Pride original parts.
- **Six-Month Battery Warranty:** The battery is covered by a separate six-month warranty provided by the battery manufacturer, not by Pride.

This warranty does not cover items requiring replacement due to normal wear and tear.

8.2 Customer Support

For warranty claims, technical assistance, or service, please contact an authorized Pride Mobility representative or visit the official Pride Mobility website. Ensure you have your model number (SC609) and date of purchase available.