



[Manuals.plus](#) /

> [LIVINGBASICS](#) /

> LivingBasics 42-Inch Door Bottom Sealing Strip Guard Instruction Manual

LIVINGBASICS HI_HRD_DS_BR3PC

LivingBasics 42-Inch Door Bottom Sealing Strip Guard Instruction Manual

Model: HI_HRD_DS_BR3PC

INTRODUCTION

This manual provides instructions for the proper installation, use, and maintenance of your LivingBasics 42-Inch Door Bottom Sealing Strip Guard. This product is designed to enhance comfort and energy efficiency in your home by sealing gaps under doors.

PRODUCT FEATURES

- **Noise Reduction:** Helps to reduce sound transmission through door gaps.
- **Light Blocking:** Prevents unwanted light from entering or exiting a room.
- **Insect Prevention:** Acts as a barrier against insects and pests.
- **Washable Material:** Constructed from non-woven fabric and PU foam, allowing for easy cleaning.
- **Rain Protection:** Helps to prevent rainwater from entering under doors.
- **Draft and Dust Control:** Seals gaps to block drafts, dust, and sand.
- **Energy Efficiency:** Contributes to maintaining indoor temperatures, reducing heating and cooling costs.
- **Durable Construction:** Made with non-woven fabric and PU foam for long-lasting use.
- **Universal Fit:** 42-inch length fits most standard and larger doors.



Image: LivingBasics Door Gap Sealer highlighting features like noise reduction, light blocking, insect prevention, washability, and rain prevention.

PACKAGE CONTENTS

Your package should contain the following items:

- 3 x Door Bottom Sealing Strips

SPECIFICATIONS

| | |
|---------------------|-----------------|
| Brand | LIVINGBASICS |
| Model Number | HI_HRD_DS_BR3PC |
| Color | Dark Brown |

| | |
|---------------------------|---|
| Material | Non Woven Fabric, PU Foam |
| Product Dimensions | 107L x 9W x 2Th Centimeters (approximately 42 inches in length) |
| Number of Pieces | 3 |
| Item Weight | 50 g |

SETUP AND INSTALLATION

Follow these steps to install your door bottom sealing strip guard:

- 1. Prepare the Door:** Ensure the bottom edge of your door is clean and free from obstructions.
- 2. Position the Strip:** Slide the door bottom sealing strip under the door. The two foam cylinders should be positioned on either side of the door bottom.
- 3. Adjust Length:** If the strip is too long for your door, carefully cut off the excess material with scissors to achieve a snug fit.
- 4. Verify Fit:** Once trimmed and positioned, ensure the strip moves smoothly with the door without snagging on the floor or carpet.



1. Place The Door Bottom Strip Under the Door.

2. Cut Off The Excess.



3. The Door Bottom Sealing Strip is Ready to Protect Your Room.

LIVINGBASICS

Fits Any Door
with It's
42 Inch Length

PACK OF 3
DOOR STRIPS



Image: The door bottom sealing strip installed on a door, demonstrating its length and fit.

OPERATING INSTRUCTIONS

The LivingBasics Door Bottom Sealing Strip Guard operates passively. Once installed, it will automatically move with your door, providing continuous sealing against drafts, dust, light, noise, insects, and rain. No further action is required for its daily function.



Image: The door bottom sealing strip in place, sealing the gap under a door.

MAINTENANCE

To ensure the longevity and effectiveness of your door bottom sealing strip, follow these maintenance guidelines:

- **Cleaning:** The strip is washable. You can gently wipe it with a damp cloth to remove dust and dirt. For deeper cleaning, hand wash with mild soap and water, then air dry completely before re-installing.
- **Regular Inspection:** Periodically check the strip for any signs of wear or damage. Replace if the foam cylinders are significantly compressed or the fabric is torn.

TROUBLESHOOTING

| Problem | Possible Cause | Solution |
|---------|----------------|----------|
|---------|----------------|----------|

| | | |
|--|--|--|
| Strip does not fit the door or comes out when moving the door. | Incorrect sizing or door thickness incompatibility. | Ensure the strip is cut to the correct length for your door. Verify that your door's thickness allows the strip to slide in and remain securely in place. The product is designed for standard door thicknesses. |
| Reduced effectiveness in blocking drafts/light/noise. | Wear and tear of foam cylinders or improper positioning. | Check if the foam cylinders are still plump and providing adequate pressure against the door and floor. Reposition the strip if it has shifted. Consider replacement if the material is worn out. |

WARRANTY INFORMATION

This LivingBasics product comes with a **1-Year Warranty** from the date of purchase. This warranty covers manufacturing defects under normal use. Please retain your proof of purchase for any warranty claims.

SUPPORT

For customer service, technical support, or warranty inquiries, please contact LivingBasics using the information below:

- **Website:** <https://www.livingbasics.in>
- **Email:** customerservice@livingbasics.in
- **Customer Service Number:** +91 6262422422