

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [TOPCHARGEUR](#) /

› [TOPCHARGEUR Power Adapter User Manual](#)

TOPCHARGEUR 14.5V Power Adapter for Norauto N1200

TOPCHARGEUR 14.5V Power Adapter

USER MANUAL

1. Product Overview

This TOPCHARGEUR power adapter is designed to provide a stable 14.5V DC output, suitable for charging devices such as the Norauto N1200 Jump Starter. It features a compact design and incorporates multiple safety protections to ensure reliable operation.



Image: The TOPCHARGEUR 14.5V Power Adapter, showing the main unit with a standard European AC plug and the attached cable ending in a DC barrel connector. The cable is neatly coiled.

2. Safety Instructions

Please read and understand all safety instructions before using this product. Failure to follow these instructions may result in electric shock, fire, or serious injury.

- Ensure the adapter's input voltage (100-240V AC) matches your power outlet's specifications.
- Do not expose the adapter to water, moisture, or extreme temperatures.
- Avoid dropping or subjecting the adapter to strong impacts.
- Do not disassemble or modify the adapter. Refer all servicing to qualified personnel.

- Always disconnect the adapter from the power outlet before cleaning or if it will not be used for an extended period.
- Verify the polarity of the output connector (+ in the center, - on the side) matches the requirements of your device before connecting.
- This adapter is equipped with safety protections against overvoltage, overheating, short circuit, and overcharge.

3. Setup

1. **Unpack:** Carefully remove the power adapter from its packaging.
2. **Inspect:** Check the adapter and cable for any visible damage. Do not use if damaged.
3. **Connect to Device:** Plug the DC barrel connector of the adapter into the appropriate charging port of your device (e.g., Norauto N1200 Jump Starter). Ensure a secure fit and correct polarity (+ in the center, - on the side).
4. **Connect to Power Outlet:** Insert the AC plug of the adapter into a standard wall power outlet (100-240V AC).

4. Operating Instructions

Once properly connected, the adapter will begin supplying power to your device. Follow the charging indicators or instructions provided with your specific device (e.g., Norauto N1200) to monitor the charging process.

- The adapter is designed for continuous use within its specified limits.
- Disconnect the adapter from the power outlet and your device once charging is complete or if the device is fully powered.

5. Maintenance

- **Cleaning:** Disconnect the adapter from all power sources before cleaning. Use a soft, dry cloth to wipe the surface. Do not use liquid cleaners or aerosols.
- **Storage:** When not in use, store the adapter in a cool, dry place, away from direct sunlight and moisture. Avoid tightly coiling the cable to prevent damage.
- **Inspection:** Periodically inspect the cable and connectors for any signs of wear or damage. Replace the adapter if any damage is found.

6. Troubleshooting

If you encounter issues with your TOPCHARGEUR power adapter, please refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Adapter not providing power	Not properly plugged in; Faulty power outlet; Damaged adapter/cable; Device issue.	Ensure both ends are securely connected. Try a different power outlet. Inspect adapter for damage. Test with another compatible device if possible.

Problem	Possible Cause	Solution
Device not charging	Incorrect polarity; Device charging port issue; Device not compatible.	Verify polarity (+ center, - side). Check device's charging port. Confirm device compatibility with 14.5V DC output.
Adapter feels hot	Normal operation under load; Overload; Poor ventilation.	A slight warmth is normal. Ensure adequate ventilation around the adapter. If excessively hot, disconnect immediately and check device's power requirements.

7. Specifications

Feature	Specification
Model	14.5V Power Adapter for Norauto N1200
Input Voltage	100-240V AC, 50-60 Hz
Output Voltage	14.5V DC
Output Polarity	+ in the center, - on the side
Cable Length	Approx. 120 cm
Dimensions (Adapter)	9.8 x 8.3 x 3.2 cm (approx.)
Weight	80 grams (approx.)
Certifications	CE & ROHS certified

8. Warranty and Support

For warranty information and customer support, please refer to the documentation provided with your purchase or visit the official TOPCHARGEUR website. Keep your proof of purchase for warranty claims.