Bell+Howell 8792

Bell+Howell Triburst Color Select LED Garage Light User Manual

Model: 8792 | Brand: Bell+Howell

1. Introduction

The Bell+Howell Triburst Color Select LED Garage Light is designed to provide bright, energy-efficient illumination for various spaces. This light features a super bright 5500 Lumen output with 144 LED bulbs and offers three adjustable light tones: Warm 3000K, White 4500K, and Daylight 5500K. Its unique tri-panel design allows for 360° light direction, ensuring comprehensive coverage.

The Triburst light is engineered for easy installation, screwing into any standard light bulb socket, and is constructed from durable, rust-proof steel for longevity. It is suitable for indoor use in areas such as garages, basements, workshops, and attics.



Image 1.1: The Bell+Howell Triburst Color Select LED Garage Light, shown with its packaging, highlighting its key features and design.

2. Important Safety Information

Please read all safety instructions before installing or using this product. Failure to follow these instructions may result in electric shock, fire, or other hazards.

- **Disconnect Power:** Always ensure the power supply to the light socket is turned off at the circuit breaker before installation, removal, or maintenance.
- **Indoor Use Only:** This product is designed for indoor use. Do not expose to water or moisture. Water Resistance Level: Not Water Resistant.
- **Standard Socket:** Install only into a standard E26 light bulb socket.
- **Voltage:** Ensure the voltage of your electrical system matches the product's voltage requirement (120 Volts).
- **Do Not Disassemble:** Do not attempt to disassemble or modify the light fixture. There are no user-

serviceable parts inside.

- **Avoid Direct Eye Exposure:** The LED light is very bright. Avoid looking directly into the light source for extended periods.
- **Proper Handling:** Handle the light by its base, not by the adjustable panels, during installation.

3. Package Contents

Verify that all items are present in the package:

- Bell+Howell Triburst Color Select LED Garage Light (1 unit)
- Mounting Hardware (Deep socket extender included)

4. Installation Instructions

The Bell+Howell Triburst Color Select LED Garage Light is designed for simple, tool-free installation into any standard E26 light bulb socket.

1. **Turn Off Power:** Before beginning installation, locate the circuit breaker that controls the light socket where you intend to install the Triburst light. Turn off the power to that circuit. Verify that the power is off by attempting to turn on the existing light fixture.
2. **Remove Existing Bulb:** Carefully unscrew and remove any existing light bulb from the socket.
3. **Screw in Triburst Light:** Screw the Bell+Howell Triburst Color Select LED Garage Light into the standard E26 light bulb socket. Turn clockwise until it is securely fastened. No tools are required for this step. If your socket is deep, use the included deep socket extender.
4. **Adjust Panels:** Once the light is securely installed, you can adjust the three metal LED panels. Each panel is independently adjustable, allowing you to direct the light a full 360 degrees to illuminate specific areas as needed.
5. **Restore Power:** Once the light is installed and panels are adjusted, return to your circuit breaker and turn the power back on.
6. **Test Light:** Turn on the light switch to ensure the Triburst light is functioning correctly.



Image 4.1: The Triburst light is designed to screw into a standard light socket. It features three adjustable panels and includes a deep socket extender for versatile installation.



Image 4.2: Illustration of replacing an existing dim lightbulb with the ultra-bright Triburst light, demonstrating the ease of upgrade.

5. Operating Instructions

The Triburst Color Select LED Garage Light offers adjustable light tones and directional lighting.

5.1 Adjusting Light Tones

The Triburst Color Select features three interchangeable light tones. To cycle through the light tones (Warm 3000K, White 4500K, and Daylight 5500K), simply toggle the light switch off and on. Each toggle will switch to the next available color temperature.

- **Warm 3000K:** A softer, yellowish light, suitable for creating a comfortable ambiance.
- **White 4500K:** A neutral white light, ideal for general tasks and everyday illumination.
- **Daylight 5500K:** A bright, crisp white light, best for detailed work and maximizing visibility.

5.2 Adjusting Light Direction

The three LED panels are independently adjustable. Gently pivot each panel to direct the light beam precisely where it is needed. This allows for 360° coverage and eliminates dark spots in your space.



Image 5.1: The Triburst light offers three distinct color temperatures: Warm 3000K, White 4500K, and Daylight 5500K, alongside its high brightness and adjustable design.

6. Care and Maintenance

The Bell+Howell Triburst Color Select LED Garage Light is designed for durability and requires minimal maintenance.

- **Cleaning:** Ensure the power is off before cleaning. Use a soft, dry cloth to wipe the surface of the light fixture. Do not use abrasive cleaners, solvents, or liquids, as these can damage the finish or electrical components.
- **Durability:** The fixture is constructed from alloy steel and metal, making it rust-proof and designed for long-term use.
- **No User Serviceable Parts:** Do not attempt to open or repair the light fixture. Refer to the warranty section for service inquiries.

7. Troubleshooting

If you encounter issues with your Triburst Color Select LED Garage Light, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Light does not turn on.	No power to the socket. Light not screwed in properly. Faulty light switch.	Check the circuit breaker and ensure power is restored. Ensure the light is securely screwed into the E26 socket. Test the socket with another working bulb or check the switch.
Light flickers or dims.	Loose connection. Incompatible dimmer switch (if applicable).	Turn off power, then re-tighten the light in the socket. This light is not specified as dimmable. Ensure it is connected to a standard on/off switch.
Cannot change light color.	Incorrect toggling method.	Ensure you are quickly toggling the light switch off and on to cycle through the color temperatures.

If the problem persists after attempting these solutions, please contact customer support.

8. Product Specifications

Brand	Bell+Howell
Model Number	8792
UPC	080313087929
Light Source Type	LED
Brightness	5500 Lumens
Number of LED Sources	144
Light Color Options	Warm 3000K, White 4500K, Daylight 5500K
Bulb Base	E26 (Standard Screw-in)
Voltage	120 Volts
Power Source	Corded Electric
Material	Alloy Steel, Metal
Product Dimensions	7.48"L x 8.99"W x 4.27"H
Item Weight	1.48 pounds
Indoor/Outdoor Usage	Indoor

Water Resistance Level	Not Water Resistant
Assembly Required	No
Included Components	Mounting Hardware (Deep socket extender)

9. Warranty and Customer Support

For warranty information or customer support, please refer to the documentation included with your purchase or visit the official Bell+Howell website. Keep your purchase receipt as proof of purchase for any warranty claims.

Manufacturer: E Mishan & Sons

For further assistance, you may contact the seller directly through the platform where the product was purchased.

© 2023 Bell+Howell. All rights reserved.