

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Tevlaphee](#) /

› [Tevlaphee Steering Wheel Lock - Model T5JSY001 Instruction Manual](#)

Tevlaphee T5JSY001

Tevlaphee Steering Wheel Lock

Model: T5JSY001

INTRODUCTION

The Tevlaphee Steering Wheel Lock (Model T5JSY001) is a robust anti-theft device designed to enhance vehicle security. Constructed from high-grade steel with a plastic-dipped finish, it provides a visible deterrent and physical barrier against theft. This manual provides essential information for the proper setup, operation, maintenance, and troubleshooting of your steering wheel lock.

SAFETY INFORMATION

- Ensure the vehicle is parked and the engine is off before installing or removing the lock.
- Do not attempt to drive the vehicle with the steering wheel lock installed.
- Keep keys in a secure location, separate from the vehicle, to prevent unauthorized access.
- Avoid forcing the lock or key, as this may cause damage to the device or your vehicle's steering wheel.
- Store the lock in a safe place when not in use to prevent it from becoming a projectile in case of sudden stops or accidents.

PACKAGE CONTENTS

- 1 x Tevlaphee Steering Wheel Lock
- 3 x Keys
- 1 x Instruction Manual (this document)

SETUP AND INSTALLATION

The Tevlaphee Steering Wheel Lock is designed for quick and easy installation. Follow these steps to secure your vehicle:

1. **Prepare the Lock:** Hold the steering wheel lock with the key cylinder facing you. Insert one of the provided keys and turn it to unlock the mechanism, allowing the hooks to extend freely.
2. **Position on Steering Wheel:** Place one of the lock's hooks over the top or bottom section of your vehicle's steering wheel.

3. **Extend and Secure:** Pull the other end of the lock outwards, extending the adjustable bar until the second hook can firmly grip the opposite side of the steering wheel. Ensure both hooks are securely attached and the lock is snug against the steering wheel. The lock features a ratcheting mechanism that will tighten as you pull.
4. **Lock the Device:** Once the lock is securely in place and tight against the steering wheel, turn the key to the locked position and remove it. The lock will now prevent the steering wheel from being turned, making the vehicle immobile.

EASY OPERATION, FAST INSTALLATION



Image: Step-by-step installation of the Tevlaphee Steering Wheel Lock.

Your browser does not support the video tag.

Video: Demonstration of how to install and remove the Tevlaphee Steering Wheel Lock.

OPERATING INSTRUCTIONS

To operate your Tevlaphee Steering Wheel Lock:

1. **To Lock:** Follow the "Setup and Installation" steps above. Ensure the lock is tightly secured and the key is removed.
2. **To Unlock:** Insert the key into the lock cylinder and turn it to the unlocked position. The lock mechanism will release, allowing you to compress the device and remove it from the steering wheel.



Image: The unique double-row atomic lock cylinder and three keys provided with the lock.

MAINTENANCE

- Regularly inspect the lock for any signs of wear or damage.
- Keep the lock mechanism clean and free from dirt or debris. A small amount of graphite lubricant can be used if the key becomes stiff.
- The plastic-dipped finish helps protect your steering wheel; ensure it remains intact.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Lock is difficult to install/remove.	Not fully extended/compressed; steering wheel position.	Ensure the key is fully turned to the unlocked position. Adjust the steering wheel slightly to find the optimal fit.
Key is stiff or difficult to turn.	Dirt or debris in the lock cylinder; lack of lubrication.	Apply a small amount of graphite lubricant into the keyhole. Avoid oil-based lubricants.
Lock does not feel secure.	Not fully ratcheted into place.	Ensure the lock is pulled firmly until it clicks into the tightest possible position on the steering wheel.

SPECIFICATIONS

Brand: Tevlaphee

Model Name: Double hook steering wheel lock

Model Number: T5JSY001

Lock Type: Key Lock

Material: Metal

Color: Yellow

Item Weight: 4.7 Pounds

Product Dimensions: 15.3 x 4.5 x 3.9 inches

Adjustable Inner Diameter: 5.3" - 14.1" (fits most sedans, SUVs, pickup trucks, vans, trucks)

Special Features: Anti-theft Steering Wheel Lock with Twin Bars, Plastic Dipped Finish



FLEXIBILITY TO ADJUST AS YOU WANT

Fit Steering Wheels with Inner Diameter Between 4.9"-13"



Image: Dimensions and adjustability of the Tevlaphee Steering Wheel Lock.

WARRANTY AND SUPPORT

For any questions or concerns regarding your Tevlaphee Steering Wheel Lock, please contact the Tevlaphee team via Amazon. Your satisfaction is important, and they are committed to providing friendly products and service.

Note: Specific warranty details may vary. Please refer to your purchase documentation or contact customer support for precise warranty information.