

PROVISION ISR DAI-340IPEN-28

PROVISION ISR DAI-340IPEN-28 4MP Fixed Lens Dome Camera User Manual

Model: DAI-340IPEN-28

1. INTRODUCTION

The PROVISION ISR DAI-340IPEN-28 is a 4MP fixed lens dome camera designed for high-security surveillance in both indoor and outdoor environments. Featuring a 2.8mm fixed lens, it is optimized for short-distance monitoring up to 20 meters. This camera incorporates advanced DDA2 Analytics for object recognition, counting, and detailed classification, significantly reducing false alarms. Its robust IK10 vandal-proof and IP67 waterproof ratings ensure durability and reliable performance in challenging conditions.



Figure 1: Front view of the PROVISION ISR DAI-340IPEN-28 Dome Camera, showing the lens and microphone.

2. PRODUCT FEATURES

The DAI-340IPEN-28 camera is equipped with a range of features to enhance security and monitoring capabilities:

- **Sensor:** 1/3" CMOS (16:9) with 2592×1520 resolution at 25/30FPS (4MP).
- **Lens:** 2.8mm fixed lens providing a 100° viewing angle.
- **Night Vision:** True Day&Night with ICR and 20m illumination from 3 High-Power IR LEDs.
- **Compression:** Supports H.265+/ H.264+ / H.265 / H.264 / MJPEG.
- **General Analytics:** Camera Tampering detection.
- **AI (Object Recognition):** DDA Sterile Area, DDA Line Crossing, DDA Object Counting (Line), DDA Object Counting (Area), DDA Loitering Detection, DDA Illegal Parking Detection.
- **AI (Face Detection):** Capable of detecting up to 10 faces per frame.
- **Advanced Analytics:** DDA2 for advanced object classification, including age, color, gender, and vehicle brand.
- **Audio:** Built-in Microphone and Audio input.
- **Image Enhancement:** True WDR (120dB), BLC, HLC, ROI.
- **Storage:** SD Card slot for event/schedule recording (Up to 128GB).
- **Connectivity:** Alarm in + Alarm out.
- **Durability:** IP67 waterproof and IK10 vandal-proof ratings.
- **Power:** DC12V/~415mA / PoE/~5W.



IK 10 **DDA**
VANDAL PROOF **VIDEO ANALYTICS**

4MP
Resolution

IP67
Protection rating

3 Axis

20m IR
IR View 0 Lux

DC12V POE
Power supply

Audio IN



SD card

Figure 2: Key features and specifications represented by icons, including 4MP resolution, IP67, IK10, 20m IR, DC12V/PoE, Audio IN, and SD card support.

3. PACKAGE CONTENTS

Please verify that all items are present in the package:

- PROVISION ISR DAI-340IPEN-28 Camera Body
- Instruction Manual (this document)

4. SAFETY INFORMATION

To ensure safe operation and prevent damage, please observe the following safety guidelines:

- **Power Supply:** Use only the specified power supply (DC12V or PoE). Ensure the power source is stable and meets the camera's requirements.
- **Installation:** Installation should be performed by qualified personnel. Ensure the mounting surface can support the camera's weight.
- **Environment:** Do not expose the camera to extreme temperatures, humidity, or corrosive environments beyond its specified operating conditions.
- **Cleaning:** Disconnect power before cleaning. Use a soft, dry cloth. Avoid harsh chemicals or abrasive cleaners.
- **Disassembly:** Do not attempt to disassemble or modify the camera. This will void the warranty and may cause damage or injury.

5. SETUP AND INSTALLATION

The DAI-340IPEN-28 is designed for ceiling mount installation. Follow these steps for proper setup:

5.1 Mounting the Camera

1. Choose a suitable ceiling location that provides the desired viewing angle and is within reach of power and network cables.
2. Use the provided mounting template (if applicable) to mark drill holes on the ceiling.
3. Drill pilot holes and insert appropriate anchors if necessary.
4. Secure the camera base to the ceiling using screws.

5.2 Wiring Connections

Refer to the wiring diagram for proper connections:




Figure 3: Dimensions of the camera (119mm diameter, 87.8mm height) and wiring connections including Power In, RJ-45 (+PoE), Audio In, COM, Alarm Out, Alarm In, and GND.

- **Power In:** Connect the DC12V power adapter or use Power over Ethernet (PoE) via the RJ-45 port.
- **RJ-45 (+PoE):** Connect an Ethernet cable from your network switch or NVR. If using PoE, this cable will also provide power.
- **Audio In:** Connect an external microphone if desired (the camera also has a built-in microphone).
- **Alarm In/Out:** Connect external alarm devices or sensors as required for integration with security systems.

5.3 Initial Configuration

After physical installation and wiring, connect the camera to your NVR or network. Refer to your NVR's

manual or PROVISION ISR's software documentation for initial network configuration, IP address assignment, and password setup.

6. OPERATION

Once the camera is installed and configured on your network, you can access its features through a compatible NVR or client software.

6.1 Live View and Recording

Access the live video feed through your NVR or client software. Configure recording schedules, motion detection recording, or continuous recording as per your surveillance needs. The camera supports SD card recording up to 128GB for local storage.

6.2 DDA2 Analytics

The DAI-340IPEN-28 features advanced DDA2 Analytics. These can be configured via the camera's web interface or compatible NVR software:

- **Sterile Area:** Define specific zones where any unauthorized entry triggers an alert.
- **Line Crossing:** Set virtual lines, and an alert is triggered when an object crosses the line in a specified direction.
- **Object Counting:** Count objects (e.g., people, vehicles) crossing a line or entering/exiting an area.
- **Loitering Detection:** Detect individuals or objects remaining in a defined area for an unusual duration.
- **Illegal Parking Detection:** Identify vehicles parked in restricted zones.
- **Face Detection:** Detect and identify faces within the camera's field of view.
- **Advanced Object Classification:** Utilize DDA2 to classify objects by age, color, gender, and vehicle brand for more granular analysis.

Proper calibration and definition of detection rules are crucial for accurate analytics and to minimize false alarms.



Figure 4: Top-down view of the camera's lens, showing the IR illuminators and light sensor.

7. MAINTENANCE

Regular maintenance helps ensure the longevity and optimal performance of your camera:

- **Lens Cleaning:** Gently wipe the lens with a soft, lint-free cloth. For stubborn dirt, use a lens cleaning solution designed for optical surfaces.
- **Housing Cleaning:** Clean the camera housing with a damp cloth. Avoid harsh chemicals.
- **Firmware Updates:** Periodically check the PROVISION ISR website for firmware updates. Keeping the firmware updated can improve performance, add features, and enhance security.
- **Cable Inspection:** Regularly inspect all cables for signs of wear or damage. Replace damaged cables immediately.

8. TROUBLESHOOTING

If you encounter issues with your camera, refer to the following common problems and solutions:

- **No Power:**
 - Check power connections (DC12V adapter or PoE).

- Ensure the power source is active and providing the correct voltage.

- **No Video Output:**

- Verify network cable connection to the RJ-45 port.
- Check network settings (IP address, subnet mask, gateway) on the camera and NVR/client software.
- Ensure the camera is added correctly to the NVR or monitoring software.
- Restart the camera and NVR/client software.

- **Poor Image Quality:**

- Clean the camera lens.
- Check lighting conditions. Ensure IR illumination is active in low light.
- Adjust image settings (brightness, contrast, WDR) in the camera's configuration.

- **Analytics Not Triggering:**

- Review the analytics rule configurations (sterile areas, lines, sensitivity).
- Ensure the camera's firmware is up to date.
- Check for environmental factors (e.g., strong light, moving objects outside the detection zone) that might interfere.

If problems persist, contact PROVISION ISR technical support.

9. SPECIFICATIONS

Feature	Specification
Model Name	DAI-340IPEN-28
Video Capture Resolution	4MP (2592x1520)
Lens	2.8mm Fixed Lens
Viewing Angle	100 Degrees
Night Vision Range	20 Meters
Connectivity Technology	Wired (Ethernet)
Power Source	Corded Electric (DC12V) / PoE
Indoor/Outdoor Usage	Indoor, Outdoor
International Protection Rating	IP67, IK10
Mounting Type	Ceiling Mount
Dimensions (L x W x H)	6.25 x 5.5 x 5.5 inches (119mm x 87.8mm)

Included Components	Camera Body, Instruction Manual
Special Features	HD Resolution, Night Vision, Portable, Vandal Proof, Weather Proof, DDA2 Analytics, Built-in Microphone

10. WARRANTY AND SUPPORT

This product is manufactured by PROVISION ISR. For warranty information, technical support, or service inquiries, please refer to the official PROVISION ISR website or contact your authorized dealer.

You can visit the official PROVISION ISR store for more information:[PROVISION ISR Store on Amazon](#)

Related Documents

	<p>Provision-ISR DI-320IPSN-28-V2: 2MP IR Dome/Turret Security Camera</p> <p>Discover the Provision-ISR DI-320IPSN-28-V2, a 2MP IP dome/turret security camera featuring 20m IR, IP67 rating, and NDAA compliance. Ideal for indoor and outdoor surveillance with advanced analytics.</p>
	<p>Provision-ISR DI-340IPSN-28: 4MP IR Fixed Lens Dome/Turret Camera Datasheet</p> <p>Comprehensive datasheet for the Provision-ISR DI-340IPSN-28, a 4MP IR fixed lens dome/turret IP camera. Features include 20m IR range, IP67 rating, 102° field of view, WDR, 3D-DNR, and NDAA compliance. Ideal for indoor and outdoor surveillance applications.</p>
	<p>Provision-ISR I2-340IPSN-28-V2 4MP Bullet Camera - Specifications and Features</p> <p>Detailed specifications and features of the Provision-ISR I2-340IPSN-28-V2, a 4MP fixed lens bullet camera with 20m IR, IP67 rating, and advanced analytics for indoor and outdoor surveillance.</p>
	<p>Provision-ISR DI-340IPS-28: 4MP IR Dome/Turret IP Camera Datasheet</p> <p>Detailed specifications and features for the Provision-ISR DI-340IPS-28, a 4MP IR fixed lens dome/turret IP camera with 20m IR range, IP67 rating, and advanced analytics for surveillance.</p>

[pdf] Quick Start Guide



7 mark NDAA Compliance Bezpeka ShopProvision ISR cameras and network video recorders NVRs which do not use or deploy critical components including SoCs produced by NDAA provision ndaa compliance 2023bezpeka shop manuals provision 2023 srsitid AfmBOor4s5N1n 2RQ90sfD1FmTxZ3f pW66T2Fj0YJGf 3fgHr9qUCAG ShopNDAA NDAA Provision DB 320WIPN DI 320IPSN 28 V2 380IPSN MVF V3 I4 VF BMH provision 2023provision 3fgHr9qUCAGbezpeka

AfmBOoqSGTTBpfsf3wAWRnmCW0PydYIhjThGSoWhzAH93YMXhjt7xDTU ||| Nov 1st 2023 NDAA Compliance NDAA Summary The John S. McCain National Defense Authorization Act NDAA for the Fiscal Year 2019 was passed on August 13, 2018. The law, specifically Section 889, prohibits federal agencies, their contractors, and their suppliers from procuring or using "telecommunications and video surveillance equipment or services" from specific Chinese companies as a "substantial or essential component of any system, component, or service."

The NDAA ban includes telecommunications equipment produced by Huawei Technologies Company, ZTE Corporation, and surveillance and telecommunications equipment produced by Hytera Communications Corporation, Hangzhou Hikvision Digital Technology Company, or Dahua Technology Company.

Nov 1st 2023 NDAA Compliance NDAA Summary The John S. McCain National Defense Authorization Act NDAA ... 6 BSV-320SRN-36 BSV-340SRN-36 DAI-320IPEN-28 DAI-320IPEN-28-V4 DAI-320IPEN-MVF-V4 DAI-320IPSN-28-V4 **DAI-340IPEN-28 DAI-340IPEN-28-V4** DAI-340IPEN-MVF DAI-340IPEN-MVF-V4 DAI-340IPSN-28 DAI-340IPSN-28-V2...

lang:en score:21 filesize: 215.42 K page_count: 3 document date: 2023-11-12




[pdf] Accessories Catalog

PROVISION ISR מצלמות אבטחה לעסק ולבית Catalog OCTOBER 2022 EN ZBM 6 zbm co il 10 ||| קטלוג

CATALOG OCTOBER 2022 Catalog Index Provision-ISR Provision-ISR NDAA Check Point OSSIA O.S. ... cial intelligence: DDATM Line crossing, DDATM Sterile area, DDATM Object counting, Face detection. **DAI-340IPEN-28 DAI-340IPE-MVF** Lens IR Distance WDR Audio Alarm Power supply Brackets/ junction box...

lang:en score:20 filesize: 37.66 M page_count: 70 document date: 2022-10-24




[pdf] Documentation Declaration of Conformity

MOST judy C E R T I F A O N di 340ipsn 28 declaration eng 2022 atkm cz files cctv provision atesty uj ||| Holder Product Name C E R T I F I C A T I O N of Conformity No.:

MOSTCG22010215 : PROVISION-ISR LIM ... 320IPEN-MVF DI-320IPEN-28 DI-320IPEN-MVF DMA-320IPEN-28 I4-340IPEN-36 I4-340IPEN-MVF I6-340IPEN-MVF **DAI-340IPEN-28 DAI-340IPEN-MVF** DI-340IPEN-28 DI-340IPEN-MVF I4-340AD-MVF DI-340AD-MVF FEI-360IPN AP...

lang:en score:19 filesize: 41.87 K page_count: 2 document date: 2022-08-02



[\[pdf\] Accessories Catalog](#)

Provision isr General Catalog 2023 DAF EVof5Kc BAFXUBHTv M DM JA CATALOG Dec 10 2024 ·

Private houses Small medium business Buildings Ossia is the latest OS for ISR s DVR NVR systems it one of most innovative file jakartaalarm co id 12 11 13 49 |||

GENERAL CATALOG PROVISION-ISR CCTV SYSTEM Catalog Index Provision-ISR Design Video Surveillance ... cial intelligence: DDATM Line crossing, DDATM Sterile area, DDATM Object counting, Face detection. **DAI-340IPEN-28** DAI-340IPEN-MVF-V4 Lens IR Distance Audio Alarms Power supply Brackets/ junction bo...

lang:en **score:17** filesize: 10.67 M page_count: 71 document date: 2024-12-11



[\[pdf\] Accessories Catalog](#)

General Catalog 2024 12 hours ago — 5VDC Output Micro USB Plug Supplied Audio in with Built

Speaker PAL NTSC Support Status LED Indicators In Long Life Rechargeable Raising the bar CCTV

Cyber Security! an ever evolving landscape of Flash and sound serve as deterrents strobe light speaker

When D Order 1604 catalogue PAGES provision isr 10 |||

General Catalog 2024 FOLLOW THE RED LINE Download the digital version of the Provision-ISR catalog ... A.I. Analytics Eye-Sight DDA1, Eye-Sight DDA2 , Remote Monitoring Browser, Cam2 App, Ossia VMS **DAI-340IPEN-28-V4** DAI-340IPEN-MVF-V4 Cyber Protection NDAA Lens Illumination Audio Alarm SD Card B...

lang:en **score:17** filesize: 40.62 M page_count: 71 document date: 2024-10-31